



- NOTES:
1. CONDUIT BOX CAN BE ROTATED IN 90° STEPS.
 2. CONDUIT BOX CAN BE MOUNTED ON OPPOSITE SIDE BY REMOVING BRACKETS AND TURNING FRAME 180°.
 3. NAMEPLATE TO BE READ FROM CONDUIT BOX SIDE OF MOTOR.

								TOLERANCES UNLESS SPECIFIED		ELECTRIC MOTORS GEARMOTORS AND DRIVES		DRAWN NJS 05-15-2002							
								DEC.	INCHES			CHK	ML	05-20-2002					
								.XX	±.03	TITLE OUTLINE		APPD	TB	05-20-2002					
								.XXX	±.005	400TC FR. - TEBC - C'FACE		SCALE 1=6							
1525	404TC	48.22	41.22	14.75	12.25		6.12	2	REVISED BS DIM. FROM 4.87 TO 6.87 PER CN 32575	CTO	03-17-2004	ML	.XXX	±.005	REF				
1675	405TC	49.72	42.72	16.25	13.75		6.87	1	NEW DRAWING	NJS	05-20-2002	TB	.XXXX	±.0005	FMF				
								NO.	REVISION	BY & DATE	CHK	ANG	±1/2"	FINISH	PREV				
								THIS DRAWING IN DESIGN AND DETAIL IS OUR PROPERTY AND MUST NOT BE USED EXCEPT IN CONNECTION WITH OUR WORK ALL RIGHTS OF DESIGN AND INVENTION ARE RESERVED THIS IS AN ELECTRONICALLY GENERATED DOCUMENT - DO NOT SCALE THIS PRINT				RFP	CAD FILE	SS518552LE	SIZE	DRAWING NO.	PAGE	OF	REV.
DASH	FRAME	C	AG	B	2F	2FF	2FFF	BS					DIST	WA	B	SS518552LE	2		