


- NOTES:
 1. CONDUIT BOX CAN BE ROTATED IN 90° STEPS.
 2. CONDUIT BOX CAN BE MOUNTED ON OPPOSITE SIDE BY REMOVING BRACKETS AND TURNING FRAME 180°.
 3. NAMEPLATES TO BE READ FROM CONDUIT BOX SIDE OF MOTOR.

(B-SS504688)

						TOLERANCES UNLESS SPECIFIED		 ELECTRIC MOTORS GEARMOTORS AND DRIVES	DRAWN KL 02-16-2004								
						DEC.	INCHES		CHK ML 02-16-2004								
						.X	±.1		APPD JES 02-16-2004								
						.XX	±.03		TITLE OUTLINE - TEFC								
						.XXX	±.005		360T FR. - TAPPED LEAD HOLE								
						.XXXX	±.0005	MATL	FMF MU80127								
DASH	FRAME	B	C	2F	BS	NO.	REVISION	BY & DATE	CHK	ANG	±7'30"	FINISH	PREV				
1350	364T	13.25	31.50	11.25	5.62												
1450	365T	14.25	32.50	12.25	6.12												
						THIS DRAWING IN DESIGN AND DETAIL IS OUR PROPERTY AND MUST NOT BE USED EXCEPT IN CONNECTION WITH OUR WORK ALL RIGHTS OF DESIGN AND INVENTION ARE RESERVED THIS IS AN ELECTRONICALLY GENERATED DOCUMENT - DO NOT SCALE THIS PRINT						RFP 02-16-2004	CAD FILE SS508590LE	SIZE B	DRAWING NO. SS508590LE	PAGE OF	REV.
												DIST WA					