



DECAL - CONNECTION UNDER COVER (WHEN REQ'D)
 (1) 3/4-14 NPT (PLUGGED)

(4) 1/2-13 UNC-2B X .75 DEEP ON A ø7.250 B.C.

MAXIMUM FACE RUNOUT TO BE .004 T.I.R.
 MAXIMUM PILOT ECCENTRICITY TO BE .004 T.I.R.
 PERMISSIBLE SHAFT RUNOUT TO BE .002 T.I.R.
 ALIGN BASE TO C-FACE MOUNTING HOLES WITHIN ±1/16"

SPECIAL FEATURES:

- BUNA-N GASKETS THROUGHOUT
- SHAFT SEALS - BOTH ENDS OF MOTOR
- V-RING AT SHAFT END OF MOTOR
- STAINLESS STEEL SHAFT, NAMEPLATE & HARDWARE

DASH NO.	"C"	"AD"
1100	17.71	4.75
1150	18.21	5.25
1200	18.71	5.75
1250	19.21	6.25
1300	19.71	6.75
1350	20.21	7.25

		TOLERANCES UNLESS SPECIFIED		LEESON ELECTRIC MOTORS GEARMOTORS AND DRIVES		DRAWN RDW 2/19/03		
		DEC.	INCHES			CHK		
02	UPDATED PER ISAAC 10-0580	LST	5/11/10	.X	±.1	APPD SW 2/19/03		
01	ADDED: WARNING DECAL - LIFTING LUG & WARNING DECAL - WITH/OUT PROTECTOR; REMOVED: DECAL - WIRING INSTRUCTION	KVN	4/6/2010	.XX	±.03	SCALE 3=8		
NAMEPLATE - was- TV SCREEN STYLE (080884.01)				.XXX	±.005	REF		
				.XXXX	±.0005	FMF		
NO.	REVISION	BY & DATE	CHK	ANG	±1/2"	FINISH	PREV	
THIS DRAWING IN DESIGN AND DETAIL IS OUR PROPERTY AND MUST NOT BE USED EXCEPT IN CONNECTION WITH OUR WORK ALL RIGHTS OF DESIGN AND INVENTION ARE RESERVED THIS IS AN ELECTRONICALLY GENERATED DOCUMENT - DO NOT SCALE THIS PRINT		RFP	2/19/03	CAD FILE	037608	SIZE B	DRAWING NO. 037608	REV. 02
		DIST						