



DASH NO.	"C"	"AD"
500	14.00	5.01
550	14.50	5.51
600	15.00	6.01
650	15.50	6.51

MAXIMUM FACE RUNOUT TO BE .004 TIR
 MAXIMUM PILOT ECCENTRICITY .004 TIR
 PERMISSIBLE SHAFT RUNOUT .002 TIR

WASHGUARD FEATURES:

- 1) SHAFT SEAL & V-RING
- 2) DRAIN HOLES IN ENDBELLS & CONDUIT BOX
- 3) STAINLESS STEEL SHAFT, HARDWARE & NAMEPLATE
- 4) GASKETS THROUGHOUT

NO.	REVISION	BY & DATE	CHK	ANG	FINISH	TOLERANCES UNLESS SPECIFIED		MATERIAL	TITLE	DRAWN	LST	REV.	
						DEC.	INCHES						
03	ADDED DRAIN SCREWS TO ALL HOLES ECR-0034519	ARV 7/30/13	SK	.X	±.1						1/19/04		
02	NOTE WAS (1) 1/2-14 NPT (PLUGGED) FOR BRAKE	ARV 5/30/09		.XX	±.03					CHK	RW	1/19/04	
01	REV'D DRAIN HOLE SCREW LOC'NS IN L.E ENDBELL TO MATCH ENDBELL MACHINING	BJB 03/18/04		.XXX	±.005					APPD	KH	1/19/04	
				.XXXX	±.0005					SCALE	1=2		
										REF	028575		
										FMF			
										PREV			
THIS DRAWING IN DESIGN AND DETAIL IS OUR PROPERTY AND MUST NOT BE USED EXCEPT IN CONNECTION WITH OUR WORK ALL RIGHTS OF DESIGN AND INVENTION ARE RESERVED THIS IS AN ELECTRONICALLY GENERATED DOCUMENT - DO NOT SCALE THIS PRINT						RFP	CAD FILE	028577		SIZE	DRAWING NO.	REV.	
						DIST				B	028577	03	