



SPECIAL FEATURES:
DOUBLE LIP OIL SEAL BOTH ENDS
GASKETS THROUGHOUT
O-RING SEALED ENDBELLS & THRU BOLTS
LOCKED BEARING W/ SEALED LOCK SCREWS

MAXIMUM FACE RUNOUT TO BE .004 T.I.R.
MAXIMUM PILOT ECCENTRICITY TO BE .004 T.I.R.
PERMISSIBLE SHAFT RUNOUT TO BE .002 T.I.R.

DASH NO.	"C"	"AD"
850	14.27	4.61
900	14.77	5.11
950	15.27	5.61
1000	15.77	6.11

			TOLERANCES UNLESS SPECIFIED		 REGAL-BELOIT CORPORATION	DRAWN JJK 4/4/02			
			DEC INCHES			CHK			
			X ±.1			APPR			
02	ADDED DASH NO. 1000 (132208.00)	PG 9/21/2010	XX ±.03	TITLE OUTLINE - 180TC FRAME		SCALE 1:2			
01	ADDED NOTE FOR BUILD STICKER LOC. PER ISAAC 10-1677	PG 5/4/2010	XXX ±.005	TEFC - RIGID "C"		REF OLG131167			
-	UPDATED & REDRAWN TO SOLIDWORKS	LST 12/11/2009	XXXX ±.0005	MATL STAINLESS STEEL DUCK		FMF G131901.00			
NO REVISION		BY & DATE	CHK ANG ±1/2°	FINISH		PAGE OF			
<div>THIRD ANGLE PROJECTION</div> 			RFP		PREV		SIZE B	DRAWING NO	REV
			NETWORK FILE NAME 035437		035437				
									02