



- WASHGUARD MOTOR**
- SPECIAL FEATURES:
1. SHAFT SEALS & V-RING.
  2. PLUGGED DRAIN HOLES IN ENDBELLS & CONDUIT BOX.
  3. BUNA-N GASKETS THROUGHOUT.
  4. STAINLESS STEEL SHAFT, HARDWARE & NAMEPLATE.
  5. SOLID STATE SWITCH MOUNTED TO CONDUIT BOX.

DASH NO.	"C"	"AD"	"XO"	DASH NO.	"C"	"AD"	"XO"
450A	10.37	2.00	2.00	450B	10.37	2.00	2.25
475A	10.62	2.25	2.00	475B	10.62	2.25	2.25
500A	10.87	2.50	2.00	500B	10.87	2.50	2.25
525A	11.12	2.75	2.00	525B	11.12	2.75	2.25
550A	11.37	3.00	2.00	550B	11.37	3.00	2.25
575A	11.62	3.25	2.00	575B	11.62	3.25	2.25
600A	11.87	3.50	2.00	600B	11.87	3.50	2.25
625A	12.12	3.75	2.00	625B	12.12	3.75	2.25
650A	12.37	4.00	2.00	650B	12.37	4.00	2.25

TOLERANCES UNLESS SPECIFIED		ELECTRIC MOTORS GEARMOTORS AND DRIVES		DRAWN PG 02/08/11	
DEC	INCHES	LEESON		CHK	
X	±.1	TITLE OUTLINE - 56C FRAME		APPR	
XX	±.03	TEFC - RIGID "C" FACE		SCALE	3:8
XXX	±.005	MATERIAL WASHGUARD		REF	028881
XXXX	±.0005	FINISH		FMF	113580.00
NO	REVISION	BY & DATE	CHK ANG ±1/2°	PAGE	OF
	THIRD ANGLE PROJECTION	RFP	PREV	SIZE	DRAWING NO
		NETWORK FILE NAME	607-0008	<b>B</b>	<b>607-0008</b>
					REV