



**WASHGUARD MOTOR**  
 SPECIAL FEATURES:  
 1. SHAFT SEALS & V-RING.  
 2. PLUGGED DRAIN HOLES IN ENDBELLS & CONDUIT BOX.  
 3. BUNA-N GASKETS THROUGHOUT.  
 4. STAINLESS STEEL SHAFT, HARDWARE & NAMEPLATE.  
 5. SOLID STATE SWITCH MOUNTED TO CONDUIT BOX.

DASH NO.	"C"	"AD"	"XO"	DASH NO.	"C"	"AD"	"XO"
650A	12.37	4.00	2.00	650B	12.37	4.00	2.25
700A	12.87	4.50	2.00	700B	12.87	4.50	2.25
750A	13.37	5.00	2.00	750B	13.37	5.00	2.25
800A	13.87	5.50	2.00	800B	13.87	5.50	2.25
850A	14.37	6.00	2.00	850B	14.37	6.00	2.25

TOLERANCES - UNLESS SPECIFIED		FINISH		PAGE	
DEC	INCHES	CHK	ANG	REV	CF
X	±.1				
XX	±.03				
XXX	±.005				
XXXX	±.0005				
NO		CHK	ANG	±1/2"	
		RFP		±REV	
				NETWORK FILE NAME	607-0009



**ELECTRIC MOTORS  
 GEARMOTORS  
 AND DRIVES**

DRAWN	PG 02/08/11
CHK	
APPR	
SCALE	3:8
REF	028868
PMF	113300.00
PAGE	OF
SIZE	DRAWING NO
B	607-0009
REV	