



WASHGUARD MOTOR

SPECIAL FEATURES:

1. SHAFT SEALS & V-RING.
2. PLUGGED DRAIN HOLES IN ENDBELLS & CONDUIT BOX.
3. BUNA-N GASKETS THROUGHOUT.
4. STAINLESS STEEL SHAFT, HARDWARE & NAMEPLATE.
5. SOLID STATE SWITCH MOUNTED TO CONDUIT BOX.

DASH NO.	"C"	"AD"	"XO"
450A	10.00	1.63	2.00
475A	10.25	1.88	2.00
500A	10.50	2.13	2.00
525A	10.75	2.38	2.00
550A	11.00	2.63	2.00
575A	11.25	2.88	2.00
600A	11.50	3.13	2.00
625A	11.75	3.38	2.00
650A	12.00	3.63	2.00

DASH NO.	"C"	"AD"	"XO"
450B	10.00	1.63	2.25
475B	10.25	1.88	2.25
500B	10.50	2.13	2.25
525B	10.75	2.38	2.25
550B	11.00	2.63	2.25
575B	11.25	2.88	2.25
600B	11.50	3.13	2.25
625B	11.75	3.38	2.25
650B	12.00	3.63	2.25

TOLERANCES UNLESS SPECIFIED	
DEC	INCHES
X	±.1
XX	±.03
XXX	±.005
XXXX	±.0005
NO	REVISION
	BY & DATE
	CHK LANG ±1/2°
	RFP
	PREV
	NETWORK FILE NAME 607-0011



ELECTRIC MOTORS GEARMOTORS AND DRIVES		DRAWN PG 02/10/11
TITLE OUTLINE - 56 FRAME TEFC - RIGID		CHK
MAT'L WASHGUARD		APPR
FINISH		SCALE 3:8
REV		REF 028880
SIZE B		FMF 112431.00
DRAWING NO 607-0011		PAGE OF
REV		REV