



WASHGUARD MOTOR

- SPECIAL FEATURES:
1. SHAFT SEALS & V-RING.
 2. PLUGGED DRAIN HOLES IN ENDBELLS & CONDUIT BOX.
 3. BUNA-N GASKETS THROUGHOUT.
 4. STAINLESS STEEL SHAFT, HARDWARE & NAMEPLATE.
 5. SOLID STATE SWITCH MOUNTED TO CONDUIT BOX.

DASH NO.	"C"	"AD"	"XO"	DASH NO.	"C"	"AD"	"XO"
650A	12.43	4.19	2.00	650B	12.43	4.19	2.25
700A	12.93	4.69	2.00	700B	12.93	4.69	2.25
750A	13.43	5.19	2.00	750B	13.43	5.19	2.25
800A	13.93	5.69	2.00	800B	13.93	5.69	2.25

		TOLERANCES UNLESS SPECIFIED		LEESON	ELECTRIC MOTORS GEARMOTORS AND DRIVES	DRAWN PG 02/10/11
	DEC	INCHES				CHK
	X	±.1				APPR
	.XX	±.03				SCALE 3:8
	.XXX	±.005		REF 028894		
	.XXXX	±.0005		MATL WASHGUARD	FMF 120589.00	
NO	REVISION	BY & DATE	CHK ANG ±1/2"	FINISH	PAGE OF	
	THIRD ANGLE PROJECTION		RFP	PREV	SIZE DRAWING NO	
			NETWORK FILE NAME 607-0012		B 607-0012	