



NOTES:

1. CONDUIT BOX CAN BE ROTATED IN 90° STEPS.
2. CONDUIT BOX CAN BE MOUNTED IN OPPOSITE SIDE BY REMOVING BRACKETS AND TURNING FRAME 180.
3. NAMEPLATE TO BE READ FROM CONDUIT BOX SIDE OF MOTOR.

1212	215	20.47	11.76	10	7	5
912	213/215	17.47	8.63	7	5.5	3.5
DASH	FRAME	C	B	2F	2FF	BS

		TOLERANCES UNLESS SPECIFIED		LEESON		ELECTRIC MOTORS GEARMOTORS AND DRIVES		DRAWN UD 08/13/13	
		DEC	INCHES					CHK	SR 08/13/13
		.X	±.1					APPR	
		.XX	±.03					SCALE	1:1
		.XXX	±.005					REF	037873LN
		.XXXX	±.0005					FMF	
NO	REVISION	BY & DATE	CHK	ANG	±1/2°	FINISH		PREV	
THIS DRAWING IN DESIGN AND DETAIL IS OUR PROPERTY AND MUST NOT BE USED EXCEPT IN CONNECTION WITH OUR WORK. ALL RIGHTS OF DESIGN AND INVENTION ARE RESERVED.						RFP		CAD FILE	
THIS IS AN ELECTRONICALLY GENERATED DOCUMENT - DO NOT SCALE THIS PRINT						DIST		037875LE	
								SIZE	DRAWING NO
								B	037875LE
								REV	