


- NOTES:  
 1. CONDUIT BOX CAN BE ROTATED IN 90° STEPS.  
 2. NAMEPLATE TO BE READ FROM CONDUIT BOX SIDE OF MOTOR.  
 3. MOTOR HAS F2 CAPABILITY.

DASH	FRAME	C	AG	B	2F	BS
1050	254TC	23.38	19.63	10.25	8.25	4.12
1225	256TC	25.13	21.38	12.00	10.00	5.00

			TOLERANCES UNLESS SPECIFIED		 ELECTRIC MOTORS GEARMOTORS AND DRIVES	DRAWN NJS 05-16-2002	
			DEC.	INCHES		CHK	ML 05-20-2002
			.X	±.1		APPD	TB 05-20-2002
2	UPDATED C' BOX	CN 28427 TAT 05-16-2004	.XX	±.03	TITLE	SCALE	1=4
1	NEW DRAWING	CN 35134 NJS 05-20-2002	.XXX	±.005	OUTLINE - BB - TEFC - C' FACE	REF	
			.XXXX	±.0005	250TC FR. - TS - PROV. FOR SL56 TACH.	FMF	
NO.	REVISION	BY & DATE	CHK	ANG	MAT'L	PREV	
THIS DRAWING IN DESIGN AND DETAIL IS OUR PROPERTY AND MUST NOT BE USED EXCEPT IN CONNECTION WITH OUR WORK ALL RIGHTS OF DESIGN AND INVENTION ARE RESERVED THIS IS AN ELECTRONICALLY GENERATED DOCUMENT - DO NOT SCALE THIS PRINT			RFP		CAD FILE	ss207655le	
			DIST	LB	SIZE	B	DRAWING NO. PAGE OF REV. SS207655LE 2