



- NOTES:
1. CONDUIT BOX BE ROTATED IN 90° STEPS.
 2. NAMEPLATE TO BE READ FROM CONDUIT BOX SIDE OF MOTOR.
 3. CONDUIT BOX CAN BE MOUNTED ON OPPOSITE SIDE BY REMOVING BRACKETS AND TURNING FRAME 180°.

							TOLERANCES UNLESS SPECIFIED				DRAWN CTO 02-25-2002	
							DEC.	TOLERANCE			CHK DRS 02-25-2002	
							.X	± .1	APPD JMM 02-25-2002		SCALE	
							.XX	± .03	TITLE OUTLINE - TFFA		REF	
							.XXX	± .005	320 FR. - BB - STD. - 12.50 LAM.		FMF	
DASH	FRAME	B	C	2F	2XF	BS	JMM	±.0005	✓ SURFACE ROUGHNESS UNLESS SPECIFIED	MAT'L.	PREV	
1475	324T	14.00	28.97	10.50		5.25	CHK	ANG ±7'30"	FINISH			
1625	324/6T	14.00	30.47	12.00	10.50	6.00	THIS DRAWING IN DESIGN AND DETAIL IS OUR PROPERTY AND MUST NOT BE USED EXCEPT IN CONNECTION WITH OUR WORK. ALL RIGHTS OF DESIGN AND INVENTION ARE RESERVED. THIS IS AN ELECTRONICALLY GENERATED DOCUMENT - DO NOT SCALE THIS PRINT		PURCHASED	CAD FILE SS3110B1LN	SHOP BOOK	
							DIST WA - LB - WC - UX - DR - EX		SIZE	DRAWING NO.	REV.	
									B	SS3110B1LN	I	