



- NOTES:  
 1. CONDUIT BOX CAN BE ROTATED IN 90° STEPS.  
 2. CONDUIT BOX CAN BE MOUNTED ON OPPOSITE SIDE BY REMOVING BRACKETS AND TURNING FRAME 180°.  
 3. NAMEPLATES TO BE READ FROM CONDUIT BOX SIDE OF MOTOR.

CONDUIT BOX DIMENSIONS				
FRAME	CB	CE	OW	
404	15.24	18.78	29.66	
405	16.24	19.78	30.66	

(B-SS504699)

DASH	FRAME	B	C	2F	BS
1525	404TS	14.75	32.62	12.25	6.12
1675	405TS	16.25	34.12	13.75	6.88

				TOLERANCES UNLESS SPECIFIED				DRAWN KL 02-21-2002	
				DEC.	TOLERANCE			CHK DJK 02-21-2002	
				.X	± .1	APPD JES 02-21-2002		SCALE	
				.XX	± .03	TITLE OUTLINE		REF	
				.XXX	± .005	400TS FR. - TEFC - STD.		FMF	
				.XXXX	± .0005	SURFACE ROUGHNESS UNLESS SPECIFIED		PREV	
				CHK	ANG ± 7'30"	FINISH			
NO. 1 NEW DRAWING MU40666 REVISION BY DATE				PURCHASED CAD FILE 55504698LN DIST WA - <del>06</del> - <del>08</del> - <del>09</del> - <del>09</del>		SHOP BOOK SIZE B		DRAWING NO. SS504698LN	
THIS DRAWING IN DESIGN AND DETAIL IS OUR PROPERTY AND MUST NOT BE USED EXCEPT IN CONNECTION WITH OUR WORK. ALL RIGHTS OF DESIGN AND INVENTION ARE RESERVED. THIS IS AN ELECTRONICALLY GENERATED DOCUMENT - DO NOT SCALE THIS PRINT									