



(B-SS504698)

NOTES:

1. CONDUIT BOX CAN BE ROTATED IN 90° STEPS.
2. CONDUIT BOX CAN BE MOUNTED ON OPPOSITE SIDE BY REMOVING BRACKETS AND TURNING FRAME 180°.
3. NAMEPLATE TO BE READ FROM CONDUIT BOX SIDE OF MOTOR.

CONDUIT BOX DIMENSIONS			
FRAME	AB	AC	OW
404	18.78	15.25	29.66
405	19.78	16.25	30.66

DASH	FRAME	B	C	2F	BS
1525	404TS	14.75	32.62	12.25	6.12
1675	405TS	16.25	34.12	13.75	6.88

NO.	REVISION	BY & DATE	TOLERANCES UNLESS SPECIFIED		FINISH	DRAWN	CHK	APPD	SCALE	REF	FMF	PREV
			DEC.	INCHES								
			.X	±.1		JJB	MH	MJS	.17=1	SS504698LN	MU87723	
			.XX	±.03								
			.XXX	±.005								
			.XXXX	±.0005								
THIS DRAWING IN DESIGN AND DETAIL IS OUR PROPERTY AND MUST NOT BE USED EXCEPT IN CONNECTION WITH OUR WORK ALL RIGHTS OF DESIGN AND INVENTION ARE RESERVED THIS IS AN ELECTRONICALLY GENERATED DOCUMENT - DO NOT SCALE THIS PRINT					ANG	±7°30"	RFP	10-20-2008	CAD FILE	SS509125LE	SIZE	B
					MAT'L						DRAWING NO.	SS509125LE
					CHK						PAGE	OF
					DIST	WA					REV.	



ELECTRIC MOTORS
GEARMOTORS
AND DRIVES

TITLE OUTLINE - TAPPED LEAD HOLE
400TS/US FR. - TEFC - STD.