


NOTES:  
 1. CONDUIT BOX CAN BE ROTATED IN 90° STEPS.  
 2. CONDUIT BOX CAN BE MOUNTED ON OPPOSITE SIDE BY REMOVING BRACKETS AND TURNING FRAME 180°.  
 3. NAMEPLATE TO BE READ FROM CONDUIT BOX SIDE OF MOTOR.

DASH	FRAME	B	C	2F	2FF	BS
1525	404T	14.75	35.62	12.25		6.12
1675	404/405T	16.25	37.14	12.25	13.75	6.88

		TOLERANCES UNLESS SPECIFIED		 <b>ELECTRIC MOTORS GEARMOTORS AND DRIVES</b>		DRAWN KL 02-16-2004	
		DEC INCHES				CHK ML 02-16-2004	
		X ±.1		TITLE OUTLINE - TEFC		APPR JES 02-16-2004	
		.XX ±.03		400T FR. - TAPPED LEAD HOLE		SCALE 1:5	
		.XXX ±.005		MATL		REF SS508859	
1	UPDATED FRAME & REDRAWN IN SOLIDWORKS MU102119	JSB	09-13-2011	JB	XXXXX ±.0005	PAGE OF	
NO		REVISION		BY & DATE		FINISH	
		THIRD ANGLE PROJECTION		CHK ANG ±1/2°		RFP 05-22-1988	
				RFP 05-22-1988		PREV	
				NETWORK FILE NAME SS508859LE		SIZE DRAWING NO	
						B SS508859LE	
						REV 1	