



- NOTES:
1. CONDUIT BOX CAN BE ROTATED IN 90 ° STEPS.
 2. CONDUIT BOX CAN BE MOUNTED ON OPPOSITE SIDE BY REMOVING BRACKETS AND TURNING FRAME 180 °.
 3. NAMEPLATES TO BE READ FROM CONDUIT BOX SIDE OF MOTOR.

1275	284U	26.56	11.50	9.50	---	4.75
1425	284/286U	28.06	13.00	9.50	11.00	5.50
DASH	FRAME	C	B	2F	2FF	BS

		TOLERANCES UNLESS SPECIFIED		Lincoln Motors		DRAWN HLB 10-10-2000
		DEC	INCHES			CHK ML 10-16-2000
		X	±.1			APPR TB 10-16-2000
3	UPDATED TO NEW FRAME DESIGN MU109232	MSG 08-16-2012	TB XX ±.03	TITLE OUTLINE - TEFC - TFPA		SCALE 1:4
2	286 FR. WAS 284 FR. (IN NOTE) CN 29200-1344	HLB 01-25-2001	ML XXX ±.005	280U FR. - STD. - 11.00 LAM. - CAST C' BOX		REF
1	NEW DRAWING MU33973	HLB 10-16-2000	ML XXXX ±.0005	MATL		FMF MU33973
NO	REVISION	BY & DATE	CHK LANG ±7'30"	FINISH		PAGE OF
			RFP 10-16-2000	PREV		SIZE DRAWING NO
			THIRD ANGLE PROJECTION	NETWORK FILE NAME SS311055LN		B SS311055LN
						REV 3