



- NOTES:
1. CONDUIT BOX CAN BE ROTATED IN 90° STEPS.
 2. CONDUIT BOX CAN BE MOUNTED ON OPPOSITE SIDE BY REMOVING BRACKETS AND TURNING FRAME 180°
 3. NAMPLATES TO BE READ FROM CONDUIT BOX SIDE OF MOTOR.

		TOLERANCES UNLESS SPECIFIED		ELECTRIC MOTORS GEARMOTORS AND DRIVES		DRAWN MSG 02-18-2013	
		DEC	INCHES			CHK TB 02-18-2013	
		X	±.1			APPR MSG 02-18-2013	
		XX	±.02	TITLE	OUTLINE	SCALE 5:32	
		XXX	±.005	444/445T FR. - TEFC - STD		REF	
1	UPDATED OUTLINE PER MU112461	JJB	03-19-2013	MH	XXXX ±.0005	FMF	
	REVISION	CHK	LANG	±7'30"	FINISH	PAGE OF	
	THIRD ANGLE PROJECTION	RFP	02-18-2013	PREV		REV	
		NETWORK FILE NAME SS517026LE			SIZE B	DRAWING NO SS517026LE	REV 1

DASH	FRAME	B	C	BS	2F	2FF
2025	444/445T	19.75	43.35	8.25	14.50	16.50