



3/8x3/8x2.88 KEY

Ø 1.625
1.624

SPECIAL DRAIN HOLES BOTH BRACKETS

- NOTES:
 1. CONDUIT BOX CAN BE ROTATED IN 90° STEPS.
 2. CONDUIT BOX CAN BE MOUNTED ON OPPOSITE SIDE BY REMOVING BRACKETS AND TURNING FRAME 180°.
 3. NAMEPLATE READ FROM CONDUIT BOX SIDE OF MOTOR.

| | | TOLERANCES UNLESS SPECIFIED | | LEESON ELECTRIC MOTORS GEARMOTORS AND DRIVES | | DRAWN MSG 07-03-2013 | |
|---|-----------------------------|-----------------------------|--------|--|--|----------------------|-----------------------|
| | | DEC | INCHES | TITLE OUTLINE - TEAO - HORIZONTAL OR SHAFT UP/DOWN | | CHK DR 07-16-2013 | |
| | | X | ±.1 | 250T FR. - INPRO SEALS <td colspan="2">APPR TB 07-16-2013</td> | | APPR TB 07-16-2013 | |
| | | XX | ±.03 | REF <td colspan="2">SCALE 5:16</td> | | SCALE 5:16 | |
| | | XXX | ±.005 | REF <td colspan="2">REF</td> | | REF | |
| 1 | REMOVED GROUND LUG MU113203 | MSG | ±.0005 | FINISH | | FMF MU113203 | |
| | | CHK | ±7'30" | REV | | PAGE OF | |
| | | RFP 07-17-2013 | | NETWORK FILE NAME SS208349LE | | SIZE B | DRAWING NO SS208349LE |
| | | REV 1 | | | | | |

| | | | | | | |
|------|-------|-------|-------|------|-------|------|
| 1050 | 254T | 20.95 | 10.50 | --- | 8.25 | 4.12 |
| 1225 | 256T | 22.70 | 12.00 | 8.25 | 10.00 | 5.00 |
| DASH | FRAME | C | B | 2F | 2FF | BS |

