



NOTES:
 1. CONDUIT BOX CAN BE ROTATED IN 90° STEPS.
 2. CONDUIT BOX CAN BE MOUNTED ON OPPOSITE SIDE BY REMOVING BRACKETS AND TURNING FRAME 180°.
 3. NAMEPLATES TO BE READ FROM CONDUIT BOX SIDE OF MOTOR.

| DASH | FRAME | B | C | 2F | 2FF | BS |
|------|----------|-------|-------|------|-------|------|
| 1275 | 284T | 12.50 | 25.47 | 9.50 | --- | 4.75 |
| 1425 | 284/286T | 13.00 | 26.97 | 9.50 | 11.00 | 5.50 |

| | | | |
|-----------------------------|------------------------|---|-----------------------|
| TOLERANCES UNLESS SPECIFIED | | LEESON ELECTRIC MOTORS GEARMOTORS AND DRIVES | DRAWN TDB 07-18-2013 |
| DEC | INCHES | | CHK MH 07-19-2013 |
| X | ±.1 | TITLE OUTLINE - TEAO - HORIZONTAL OR SHAFT UP/DOWN 280T FR. - 12.50 LAM. | APPR TB 07-22-2013 |
| XX | ±.03 | | SCALE 1:4 |
| XXX | ±.005 | | REF |
| XXXX | ±.0005 | | FMF MU113209 |
| NO | REVISION | BY & DATE | PAGE OF |
| | THIRD ANGLE PROJECTION | CHK LANG ±7°30' | FINISH |
| | | RFP 07-22-2013 | PREV |
| | | NETWORK FILE NAME SS312536LE | SIZE B |
| | | | DRAWING NO SS312536LE |
| | | | REV |