- Available with Parallel or Junction-style Wiring
- Simplifies Wiring Installations
- Tough Molded TPU Body





Connector Style	Part Number	Features	Pinout	
RSM RKM  e1.024 [26.0]  7/8-16UN  e1.024 [26.0]  7/8-16UN  e1.024 [26.0]  1.370 [34.8]	RSM-2RKM 20	1 male and 2 female connectors, 250 V, 9.0 A, 80°C, parallel wired, 2 conductor	$\begin{array}{c} 1 \\ 2 \\ \hline \\ 1 \\ 2 \end{array} \longrightarrow \begin{array}{c} 1 \\ 2 \\ \hline \end{array}$	
	RSM-2RKM 30	1 male and 2 female connectors, 250 V, 9.0 A, 80°C, parallel wired, 3 conductor	$ \begin{array}{cccccccccccccccccccccccccccccccccccc$	
	RSM-2RKM 40	1 male and 2 female connectors, 250 V, 9.0 A, 80°C, parallel wired, 4 conductor	1	
	RSM-2RKM 50	1 male and 2 female connectors, 250 V, 9.0 A, 80°C, parallel wired, 5 conductor	1	
	RSM 50-2RKM 30	1 male 5-pin connector, 2 female 3-pin connectors, 250 V, 9.0 A, 80°C, combine 2 cables into 1	$ \begin{array}{cccccccccccccccccccccccccccccccccccc$	

## **Pinouts**

Female			Male				
2	2 6 0	3 1	1 5	1	3 2	1 3	3 4 5
2-Pin	3-Pin	4-Pin	5-Pin	2-Pin	3-Pin	4-Pin	5-Pin

B2007 F53