

CPE Rubber *flexlife*® (S600)

Thermo-set CPE jacket over EPDM rubber insulation. Thermo-set rubber is impervious to flame and temperature extremes making it the cable of choice for many welding applications. CPE rubber jacket provides superior resistance to tears, cuts and abrasions, and has a flexlife rating of over 2 million cycles.

Rubber Cable	No. Of Cond.	AWG	Jacket Characteristics	ID Number	Ship Wt. (lbs)	Cond. Colors	Shield	UL	CSA	Type	MSHA	Temp. (°C)
	3	16	10.31 mm OD, CPE, YE, 600 V	RF50596-30M RF50596-100M RF50596-200M	31 103 205	GN, RD/BK, RD/WH		•	•	SOOW	•	105° -50°
	3	18	8 mm OD, CPE, YE, 300 V	RF50654-30M RF50654-100M RF50654-200M	19 63 131	BK, BN, BU				SJOOW		105° -50°
	3	18	8.0 mm OD, CPE, YE, 1000 V	RF50658-30M RF50658-100M RF50658-200M	20 66 131	GN, RD/BK, RD/WH				SJOOW		90° -50°
	4	16	11.05 mm OD, CPE, YE, 600 V	RF50595-30M RF50595-100M RF50595-200M	36 119 238	WH, RD, GN, BK		•	•	SOOW	•	105° -50°
	4	18	8.5 mm OD, CPE, YE, 300 V	RF50644-30M RF50644-100M RF50644-200M	25 83 165	BN, WH, BU, BK		•	•	SJOOW	•	105° -50°
	5	16	13.0 mm OD, CPE, YE, 600 V	RF50597-30M RF50597-100M RF50597-200M	50 166 333	RD1, RD2, GN3, RD4, RD5		•	•	SOOW	•	105° -50°
	5	18	9.2 mm OD, CPE, YE, 300 V	RF50659-30M RF50659-100M RF50659-200M	26 88 176	RD/WH, RD/BU, GN, RD/OG, RD/BK		•	•	SJOOW	•	105° -50°
	5	18	9.4 mm OD, CPE, YE, 300 V	RF50937-30M RF50937-100M RF50937-200M	28 92 184	BN, WH, BU, BK, GY		•	•	SJOOW	•	90° -50°
	6	16	13.3 mm OD, CPE, YE, 600 V	RF51019-30M RF51019-100M RF51019-200M	51 167 334	OG, BU, BK, WH, RD, GN		•	•	SOOW	•	105° -50°
	7	16	13.3 mm OD, CPE, YE, 600 V	RF51020-30M RF51020-100M RF51020-200M	51 170 340	WH/BK, BK, WH, RD, OG, BU, GN		•	•	SOOW	•	105° -50°
	8	16	14.4 mm OD, CPE, YE, 600 V	RF50976-30M RF50976-100M RF50976-200M	61 202 404	OG, BU, WH/BK, BK, WH, RD, GN, RD/BK		•	•	SOOW		105° -50°
	9	16	15.2 mm OD, CPE, YE, 600 V	RF51021-30M RF51021-100M RF51021-200M	68 228 456	OG, BU, RD/BK, GN/BK, WH, RD, GN, WH/BK, BK		•	•	SOOW	•	105° -50°
	10	16	15.7 mm OD, CPE, YE, 600 V	RF51022-30M RF51022-100M RF51022-200M	71 235 470	OG, BU, WH/BK, RD/BK, GN/BK, OG/BK, RD, GN, BK, WH		•	•	SOOW	•	105° -50°
	12	16	16.5 mm OD, CPE, YE, 600 V	RF51023-30M RF51023-100M RF51023-200M	81 269 538	OG, BU, WH/BK, RD/BK, GN/BK, OG/BK, BU/BK, WH/BK, GN, RD, WH, BK		•	•	SOOW	•	105° -50°