

## 14 and 19-Pin Field Wireable, In-line Connectors

- Male Connectors
- For use with Custom Wiring or Junction Boxes
- IEC IP67 Protection



Connector Style	Female Part Number	Male Part Number	Features	Pinout
<p><b>BK ..</b></p>	BK 14-0	BS 14-0	Nylon PG 9 cable gland, accepts 6-8 mm cable diameter, solder cup, accepts up to 14x24 AWG conductors, 85°C, 60 VAC/DC, 3 A, Mates with <i>picofast</i> junction boxes, unshielded	<p><b>Female</b></p> <p><b>Male</b></p>
<p><b>BS ..</b></p>	BK 19-0	BS 19-0		Nylon PG 9 cable gland, accepts 6-8 mm cable diameter, solder cup, accepts up to 19x24 AWG conductors, 85°C, 60 VAC/DC, 3 A, Mates with <i>picofast</i> junction boxes, unshielded
<p><b>WBK ..</b></p>	WBK 14-0	WBS 14-0	Nylon PG 9 cable gland, accepts 6-8 mm cable diameter, solder cup, accepts up to 14x24 AWG conductors, 85°C, 60 VAC/DC, 3 A, Mates with <i>picofast</i> junction boxes, unshielded	<p><b>Female</b></p> <p><b>Male</b></p>
<p><b>WBS ..</b></p>	WBK 19-0	WBS 19-0		Nylon PG 9 cable gland, accepts 6-8 mm cable diameter, solder cup, accepts up to 19x24 AWG conductors, 85°C, 60 VAC/DC, 3 A, Mates with <i>picofast</i> junction boxes, unshielded

Accessories