



Low voltage products

Low voltage current transformers
type: IMW, IMP, IMS, ISW, INSOA, IMR

Power and productivity
for a better world™

ABB

Low voltage current transformers

type: IMW, IMP, IMS, ISW, INSOA, IMR

INDEX

General information

Application	3
Operating conditions	3
Design	3
Mounting	3
Packing, transport, storage	4
Spare parts	4
Compliance with standards	4
Warranty	4
Handling used products	4
Submitting an order	4
Example of an order	4
Transformer selection	5

Technical data, dimensional drawings

Transformers type IMW with primary winding	6
Transformers type IMS on busbar	
IMSa	8
IMSB	10
IMSc	12
IMSd	14
Transformers type IMP on cable	
IMPa	16
IMPb	18
Transformers type ISW on busbar or cable	
ISWb	20
ISWb2	22
ISWc	24
ISWd1	26
ISWd2	28
ISWe	30
ISWf	32
ISWg	34
ISWh1	36
ISWh2	38

Transformers type IMR to switchgear

IMR0	40
IMR1a	42
IMR1b	44
IMR2	46

Special transformers INSOA

48

Accessories

Voltage terminal	50
Support for mounting transformer on a TS35 mounting busbar	50
Busbar mounting assembly	50
Standard bolt with holder for a 30 mm or 60 mm busbar	50
Copper sleeve	50
Busbars	51
Transformer selection table	52
Primary current range	56
Certificates	56

General information

APPLICATION

Low voltage current transformers are intended for supplying measuring instruments and protection circuits of electrical power devices with a maximum operating voltage of 0.72 kV and frequency of 50 Hz (or 60 Hz after prior arrangement with the manufacturer). Transformers of power utility installations. The transformers are manufactured for secondary currents 1A and 5A. The range of primary currents depends on the transformer and can range from 1 A up to 6,000 A.

OPERATING CONDITIONS

The transformers are designed for operation in indoor equipment in climatic conditions: temperate (N3) or tropical (T3). The long-term thermal rated current and limits of deviations of these transformers correspond to an extended current range of 120% of I_{pn} within the ambient temperature range from 248 K (-25°C) to 328 K (+55°C). It is possible to produce some transformers with a 150% or 200% current range by special arrangement with the manufacturer.

DESIGN

The low voltage current transformers are single-phase, low power transformers, operating in quasi short-circuit conditions and transforming the current flowing through the primary circuit to the current in the secondary circuit with a level of accuracy specified in relevant standards. Their insulation class is E or A. The windings of the current transformers are enclosed in the housings made of heat and fire resistant material.

The current transformers are produced for different types of primary circuits: busbar or cable according to the transformer selection table (page 52). The range of primary currents is from 1 A up to 6000 A. Transformer types: IMW, IMP, IMS, IMR2 and ISW (with the exception of ISWc) have offer the option of a sealing cover for

secondary terminals. Transformers are permanently marked with the rated ratio on both sides of the casing. They have slides allowing assembly to the base and screws or holder for mounting on the current circuit. Equipment details are stated in the transformer selection table (page 52).

MOUNTING


Low voltage current transformers can be mounted on:

- current busbars,
- TS35 mounting busbars,
- solid cables or cores of multicore cables,
- plates.

The current transformer can be mounted in any position. In order to mount a given type of transformer it should be drawn onto the busbar, next it should be fastened with the holders or mounting bolts to be found on both sides of the transformer. Mounting of the transformer on a plate, depending on the type, is made possible by two or four slides with which the device is furnished. A special base allows mounting on the TS35 mounting busbar. When mounting a transformer equipped with its own busbar, it should be fastened to the current circuit with the supplied bolt terminals with which the transformer busbar is furnished.

Low voltage current transformers cannot be used as support elements for current busbars (they cannot replace support insulators).

Details of mounting possibilities are indicated in the transformer selection table (page 52) and in the Accessories chapter (page 50).



General information

Packing, transport, storage

Current transformers transported over significant distances should be packed in wooden crates, that protect the devices from damage. Transformers transported for short distances can be transported by truck without packing, but should be protected from damage by separating them from other products. During loading and unloading, crates with transformers must not be thrown or turned over. Wooden crates should be appropriately marked, in accordance with requirements concerning transport of products susceptible to mechanical damage. Transformers should be stored in dry and clean locations at temperatures close to 20°C. Storage of transformers in wooden crates outdoors is not recommended. Waste packing material should be recycled utilised in suitable plants.

Spare parts

Current transformers are unreparable devices. No spare parts are provided.

Compliance with standards

- PN-EN 60044-1,
- IEC 60044-1,
- DIN-EN 60044-1.

Transformers have IEL attestations and PTB approval.

Warranty

The manufacturer grants a 24 month warranty for purchased transformers from the date of commissioning, however not longer than 30 months from the delivery date. The manufacturer is not liable for defects and damages arising as the result of:
incorrect transport after receipt of transformers by the Ordering Party
incorrect storage, installation and operation of transformers,
inappropriate selection of transformers for a specific electric system.

Handling used products

Due to the materials and technology used in their manufacture, transformers do not present a hazard to the environment. The used or damaged product should be disassembled, segregating parts of steel, non-ferrous metals, plastic and rubber. Segregated parts should be recycled or utilised at appropriate plants.

Submitting an order

In order to submit an order the following data should be stated:

- transformer type,
- ratio – I_{pn}/I_{sn} ,
 I_{pn} – primary current,
 I_{sn} – secondary current,
- power in VA – MV,
- accuracy class,
- safety coefficient FS5 or FS10,
- climate in which the transformer will be installed: (moderate, tropical) – moderate is assumed by default,
- number of ordered pieces.

Example of order:

Low voltage current transformer type IMSC, ratio 600/5 A/A; power 10 VA; class 0.5; FS5; pieces 300

Simplified notation

	IMSC	600/5	10	–	0,5	FS5	pieces 300
type	IMSC	600/5	10	–	0,5	FS5	pieces 300
ratio							
power							
class							
security factor							
quantity							

Transformer selection

In matching the current transformer with a measurement system a number of key factors must be considered.

Primary current to be converted by the transformer

The nominal value of the primary current (I_{pn}) should be selected from the offered series range of available types to provide the closest match with the expected primary current of the system.

All low voltage transformers produced by ABB have an extended rating of 120% which makes conversion possible within a range 20% higher than the rated value.

Secondary current

To adapt to the system found on the secondary side of the transformer.

5 A and 1 A are standardised values.

Note: primary current/secondary current (I_{pn}/I_{sn}) is the standard transformer ratio.

Power – the transformer load

The total load that will be connected to the transformer should be considered, including the load from the connected device as well as losses on connection leads and terminals. According to the standard IEC 60044-1 the current and angle errors of the transformer should not exceed values given in table 1 at any secondary load in the range from 25% to 100% of the rated load.

Dimensions of the transformer internal opening and external dimensions

Specified to ensure that it is possible to install the transformer on the current circuit and that it can be accommodated in the planned locations.

Selection of accuracy class to obtain satisfactory measurement accuracy


In many systems, transformer applications can be analysed according to class 0.2S or 0.5S. It is then possible to obtain more accurate current conversion of values significantly lower than the transformer rated value, up to 1% of the rated current value.

Table 1. Limits of current and phase errors of current transformers acc. to IEC 60044-1


Accuracy class	% I_{pn} – percent of rated primary current											
	1	5	20	100	120	1	5	20	100	120		
	Current error in percent +- percent					Angle error +- minutes						
0.2	–	0.75	0.35	0.2	0.2	–	30	15	10	10		
0.5	–	1.5	0.75	0.5	0.5	–	90	45	30	30		
0.2S	0.75	0.35	0.2	0.2	0.2	30	15	10	10	10		
0.5S	1.5	0.75	0.5	0.5	0.5	90	45	30	30	30		
1	–	3	1.5	1	1	–	180	90	60	60		

Fig. 1. Accuracy class characteristics:

a) classes 0.2; 0.5; 1



b) comparison of classes 0.5 and 0.5S






Transformers type IMW with primary winding

Current transformers with their own primary wiring, intended for installation in supply system current circuits. Busbars or cables can be screwed to the primary terminals of these transformers. They allow high accuracy current conversion from the lowest values. Primary current range from 1 A to 300 A.



Dimensional drawing

IMW – transformers with a flat outlet 20 x 5 mm



Type	Class	I_{pn} [A]	I_{sn} [A]	Security factor FS						Rated operation current short-time: thermal I_{th} [A]	I_{dyn} peak [A]	Maximum permissible voltage U_m [kV]	Rated test voltage U_p [kV]	Weight (approx.) [kg]					
				Burden															
				2.5 [VA]	5 [VA]	7.5 [VA]	10 [VA]	15 [VA]	20 [VA]										
IMW	0.2S	5; 75																	
		100; 150	5		5; 10														
		250; 300																	
	0.5S	5		5; 10															
		20; 30					5; 10												
		50; 75						5; 10											
		100; 150	5	5; 10	5; 10	5; 10	5; 10	5; 10											
	0.2	200		10;	5; 10;														
		250; 300		5; 10;	5; 10;	5; 10	5; 10	5; 10											
		1; 2; 3; 5																	
	0.5	10; 15; 20			10;														
		25; 30; 40	5																
		50	or	5; 10	5; 10														
		75	1	5; 10	5; 10	5; 10													
		100		5; 10	5; 10	5; 10	5; 10												
		125; 150																	
		200; 250	5	5; 10	5; 10	5; 10	5; 10				60x I_{pn}	150x I_{pn}	0.72	3	0.8				
		300		5; 10	5; 10	5; 10	5; 10	5; 10											
	1; 3	1; 2; 3; 5																	
		10; 15; 20		10	5; 10	5; 10	5; 10	5; 10	5; 10										
		25; 30; 40	5																
		50; 60; 75	or																
	1; 3	100; 125	1																
		150; 200		5; 10	5; 10	5; 10	5; 10	5; 10	5; 10										
		250; 300																	


It is possible to order transformers of other parameters after prior arrangement with the manufacturer.

Transformers type IMSa

Current transformers designed for placing on current busbars of maximum dimensions 40×10 mm.
Primary current range from 150 A to 600 A.



Dimensional drawing



Type	Class	I_{pn} [A]	I_{sn} [A]	Security factor FS						Rated operation current short-time thermal I_{th} [A]	Maximum permissible voltage U_m [kV]	Rated test voltage U_p [kV]	Weight (approx.) [kg]					
				Burden														
				2.5 [VA]	5 [VA]	7.5 [VA]	10 [VA]	15 [VA]	20 [VA]									
IMSa	0.2S	500	5	5; 10	10													
		600			5; 10													
		250			5; 10													
		300			5; 10													
		400	5		5; 10	5; 10												
	0.5S	500		5; 10	10	5; 10												
		600			5; 10	5; 10	5; 10	5; 10	5; 10	5; 10								
		250			10													
		300			5; 10	5; 10												
		400	5	5; 10	5; 10	5; 10	5; 10											
IMSe	0.2	500		5; 10	5; 10	5; 10	5; 10	5; 10										
		600		5; 10	5; 10													
		150	5	5; 10														
		200		5; 10	5; 10													
		250	5	5; 10	5; 10													
	0.5	300	or	5; 10	5; 10	5; 10	5; 10	5; 10										
		400	1	5; 10	5; 10	5; 10	5; 10	5; 10	5; 10									
		500		5; 10	5; 10	5; 10	5; 10	5; 10	5; 10									
		600	5	5; 10	5; 10	5; 10	5; 10	5; 10	5; 10									
		150			5; 10	5; 10												
IMSe	1; 3	200	5	5; 10	5; 10	5; 10												
		250	or	5; 10	5; 10	5; 10	5; 10	5; 10										
		300	1	5; 10	5; 10	5; 10	5; 10	5; 10	5; 10									
	1; 3	400		5; 10	5; 10	5; 10	5; 10	5; 10	5; 10									
		500		5; 10	5; 10	5; 10	5; 10	5; 10	5; 10									
		600	5	5; 10	5; 10	5; 10	5; 10	5; 10	5; 10									


It is possible to order transformers of other parameters after prior arrangement with the manufacturer.

Transformers type IMSb

Current transformers designed for placing on current busbars of maximum dimensions 60×10 mm.
Primary current range from 400 A to 1000 A.



Dimensional drawing



Type	Class	I_{pn} [A]	I_{sn} [A]	Security factor FS						Rated operation current short-time thermal I_{th} [A]	I_{dyn} [A]	Maximum permissible voltage U_m [kV]	Rated test voltage U_p (approx.) [kV]	Weight [kg]					
				Burden															
				2.5 [VA]	5 [VA]	7.5 [VA]	10 [VA]	15 [VA]	20 [VA]										
0.2S	0.2S	600			5; 10														
		800	5			10													
		1000					5; 10												
	0.5S	500		5; 10	5; 10														
		600			5; 10	5; 10	10	5; 10											
		750	5	5; 10	5; 10														
		800			5; 10	5; 10													
	0.2	1000				5; 10	5; 10	5; 10	5; 10	5; 10									
		400		5; 10	5; 10														
		500			5; 10	5; 10													
		600			5; 10	5; 10	5; 10	5; 10											
		750	5	5; 10	5; 10	5; 10	5; 10	5; 10											
		800			5; 10	5; 10	5; 10	5; 10	5; 10										
		1000				5; 10	5; 10	5; 10	5; 10	5; 10									
IMsB	0.2	600			5; 10	5; 10													
		750				5; 10	5; 10												
		800					5; 10	5; 10	5; 10										
		900						5; 10	5; 10	5; 10									
		1000							5; 10	5; 10									
		1100								5; 10									
		1200									5; 10								
	0.5	400		5; 10	5; 10	5; 10	5; 10	5; 10	5; 10										
		500			5; 10	5; 10	5; 10	5; 10	5; 10	5; 10									
		600			5; 10	5; 10	5; 10	5; 10	5; 10	5; 10									
		750	5	5; 10	5; 10	5; 10	5; 10	5; 10	5; 10	5; 10									
		800			5; 10	5; 10	5; 10	5; 10	5; 10	5; 10									
		900				5; 10	5; 10	5; 10	5; 10	5; 10									
		1000					5; 10	5; 10	5; 10	5; 10									
1; 3	1; 3	400		5; 10	5; 10	5; 10	5; 10	5; 10	5; 10										
		500			5; 10	5; 10	5; 10	5; 10	5; 10	5; 10									
		600	5	5; 10	5; 10	5; 10	5; 10	5; 10	5; 10	5; 10									
		750	or 1	5; 10	5; 10	5; 10	5; 10	5; 10	5; 10	5; 10									
		800		5; 10	5; 10	5; 10	5; 10	5; 10	5; 10	5; 10									
		900				5; 10	5; 10	5; 10	5; 10	5; 10									
		1000					5; 10	5; 10	5; 10	5; 10									


It is possible to order transformers of other parameters after prior arrangement with the manufacturer.

Transformers type IMSc

Current transformers designed for placing on current busbars of maximum dimensions 80×10 mm.
Primary current range from 400 A to 2500 A.



Dimensional drawing



Type	Class	I_{pn} [A]	I_{sn} [A]	Security factor FS							Rated operation current short-time thermal I_{th} [A]	I_{dyn} [A]	Maximum permissible voltage U_m [kV]	Rated test voltage U_p [kV]	Weight (approx.) [kg]					
				Burden																
				2.5 [VA]	5 [VA]	7.5 [VA]	10 [VA]	15 [VA]	20 [VA]	30 [VA]										
0.2S		1000			10							60x I_{pn}	150x I_{pn}	250 kA	0.72					
		1200			10															
		1500	5		10															
		2000			10	10														
		2500				10	10													
0.5S		400		10								60x I_{pn}	150x I_{pn}	250 kA	0.72					
		800		5; 10																
		1000		5; 10	5; 10	5; 10	5; 10													
		1200	5	5; 10	5; 10	5; 10	5; 10													
		1500		5; 10	5; 10	5; 10	5; 10	5; 10												
		2000			10	10	10													
IMSc		2500				10	10					60x I_{pn}	150x I_{pn}	250 kA	0.72					
		400	5	5; 10																
		600		5; 10																
		750		5; 10																
		800	5	5; 10	5; 10	5; 10	5; 10	5; 10	5; 10											
		1000 or 1200	10	5; 10	5; 10	5; 10	5; 10	5; 10	5; 10	5; 10										
		1500		10	10	10	10	10	10											
		1600			10	10	10	10	10	10										
		2000			10	10	10	10	10	10										
		2500	5			10	10	5; 10	5; 10	5; 10										
1; 3		400	5	5; 10	5; 10	5; 10	5; 10	5; 10				60x I_{pn}	150x I_{pn}	250 kA	0.72					
		500		5; 10	5; 10	5; 10	5; 10	5; 10	5; 10											
		600		5; 10	5; 10	5; 10	5; 10	5; 10	5; 10											
		750		5; 10	5; 10	5; 10	5; 10	5; 10	5; 10											
		800	5	5; 10	5; 10	5; 10	5; 10	5; 10	5; 10											
		1000 or 1200	10	5; 10	5; 10	5; 10	5; 10	5; 10	5; 10	5; 10										
		1500		5; 10	5; 10	5; 10	5; 10	5; 10	5; 10	5; 10										
		1600			10	10	5; 10	5; 10	5; 10	5; 10										
		2000			10	10	10	5; 10	5; 10	5; 10										
		2500	5			10	10	5; 10	5; 10	5; 10										


It is possible to order transformers of other parameters after prior arrangement with the manufacturer.

Transformers type IMSd

Current transformers designed for placing on current busbars of maximum dimensions 120 x 30 mm or 100 x 50 mm. Also allows a cable of maximum 85 mm diameter to be pulled through. The transformer allows conversion of high currents and high powers. Can perform measurement class and protection class functions.



Dimensional drawing



Type	Class	I _{pn} [A]	I _{sn} [A]	Security factor FS										Rated operation current		Maximum peak permissible voltage U _m [kV]	Rated test voltage U _p (approx.) [kV]	Weight [kg]	
				Burden										short-time thermal I _{th} [kA]	peak I _{dyn} [kA]				
				5 [VA]	7.5 [VA]	10 [VA]	15 [VA]	20 [VA]	30 [VA]	45 [VA]	60 [VA]	90 [VA]	120 [VA]						
0.2S	2500	5		10										62.5	156.5	0.72	3	1.8	
	3000	5	10	10	10	10	10	10	5; 10					75	187				
	1000					10								37.5	100				
	1600					5; 10								40	105				
	2000					5; 10	5; 10	5; 10	5; 10					50	125				
	2500	5		10	5; 10	5; 10	5; 10	5; 10	5; 10					62.5	156.5				
	3000	5	10	10	5; 10	5; 10	5; 10	5; 10	5; 10					75	187				
	4000				10	10	10	5; 10	5; 10	5; 10	5; 10			100	250				
	5000	5						10	5; 10	5; 10	5; 10								
	1000			10	10														
0.5S	1200	5	10	10	10									37.5	100	0.72	3	1.8	
	1500		10	5; 10	5; 10														
	1600		10	5; 10	5; 10									40	105				
	2000	5 or 1	10	5; 10	5; 10	5; 10								50	125				
	2500	5 or 1	10	10	5; 10	5; 10	5; 10	5; 10	5; 10					62.5	156.5				
	3000	5	10	10	5; 10	5; 10	5; 10	5; 10	5; 10					75	187				
	4000		10	10	10	5; 10	5; 10	5; 10	5; 10	5; 10									
	5000	5						10	5; 10	5; 10	5; 10			100	250				
	500		10											30	75				
	600		10	10	5; 10									36	90				
IMSD	750		10	10	5; 10												0.72	3	1.8
	800		10	10	5; 10														
	1000		10	5; 10	5; 10	5; 10													
	1200	5 or 1	10	5; 10	5; 10	5; 10								37.5	100				
	1500	5 or 1	10	5; 10	5; 10	5; 10	5; 10												
	1600		10	5; 10	5; 10	5; 10	5; 10	5; 10						40	105				
	2000		10	5; 10	5; 10	5; 10	5; 10	5; 10	5; 10					50	125				
	2500		10	10	5; 10	5; 10	5; 10	5; 10	5; 10	5; 10				62.5	156.5				
	3000		10	10	5; 10	5; 10	5; 10	5; 10	5; 10	5; 10				75	187				
	4000		10	10	10	5; 10	5; 10	5; 10	5; 10	5; 10	5; 10				100	250			
1; 3S	5000	5						10	5; 10	5; 10	5; 10	5; 10					0.72	3	1.8
	500		10											30	75				
	600		5; 10	5; 10	5; 10									36	90				
	750		5; 10	5; 10	5; 10														
	800		5; 10	5; 10	5; 10														
	1000		5; 10	5; 10	5; 10	5; 10								37.5	100				
	1200	5 or 1	5; 10	5; 10	5; 10	5; 10													
	1500	1	5; 10	5; 10	5; 10	5; 10	5; 10												
	1600		10	5; 10	5; 10	5; 10	5; 10	5; 10						40	105				
	2000		10	5; 10	5; 10	5; 10	5; 10	5; 10	5; 10					50	125				
1; 3P	2500		10	10	5; 10	5; 10	5; 10	5; 10	5; 10	5; 10				62.5	156.5	0.72	3	1.8	
	3000		10	10	5; 10	5; 10	5; 10	5; 10	5; 10	5; 10				75	187				
	4000		10	10	10	5; 10	5; 10	5; 10	5; 10	5; 10				100	250				
	5000	5						10	5; 10	5; 10	5; 10	5; 10							
	500		10											30	75				


It is possible to order transformers of other parameters after prior arrangement with the manufacturer.
There is a possibility of performing by special order transformers of primary current I_{pn} up to 6000 A and protection classes.

Transformers type IMPa

Current transformers for cables of maximum 20 mm diameter. The transformer is equipped with a holder enabling it to be assembled on current busbars of maximum dimensions 20 x 10 mm.
Primary current range from 100 A to 300 A.



Dimensional drawing



Type	Class	I_{pn} [A]	I_{sn} [A]	Security factor FS						Rated operation current short-time: thermal I_{th} [A]	I_{dyn} [A]	Maximum permissible voltage U_m [kV]	Rated test voltage U_p [kV]	Weight (approx.) [kg]					
				Burden															
				2.5 [VA]	5 [VA]	7.5 [VA]	10 [VA]	15 [VA]	20 [VA]										
IMPa	0.5S	200		10	5; 10	10	10												
		250	5	5; 10	5; 10	10	5; 10												
		300		5; 10	5; 10	5; 10	5; 10												
	0.2	200	5	10	10	10													
		250		5; 10	5; 10	5; 10													
		300		5; 10	10	10													
	0.5	100		10															
		125		10	5; 10														
		150		5; 10	5; 10	5; 10													
		200	5	5; 10	5; 10	5; 10	5; 10	10											
		250	or	5; 10	5; 10	5; 10	5; 10	5; 10	10										
		300	1	5; 10	5; 10	5; 10	5; 10	5; 10	5; 10										
	1; 3	100		10	10														
		125		10	5; 10														
		150		5; 10	5; 10	5; 10	5; 10												
	1; 3	200		5; 10	5; 10	5; 10	5; 10	10											
		250		5; 10	5; 10	5; 10	5; 10	10	10										
		300		5; 10	5; 10	5; 10	5; 10	5; 10	5; 10										


It is possible to order transformers of other parameters after prior arrangement with the manufacturer.

Transformers type IMPb

Current transformers for cables of maximum 30 mm diameter.
The transformer is equipped with a holder for assembly on current
busbars of maximum dimensions 30 x 10 mm.
Primary current range from 100 A to 600 A.



Dimensional drawing



Type	Class	I_{pn} [A]	I_{sn} [A]	Security factor FS						Rated operation current short-time thermal I_{th} [A]	I_{dyn} [A]	Maximum permissible voltage U_m [kV]	Rated test voltage U_p [kV]	Weight (approx.) [kg]					
				Burden															
				2.5 [VA]	5 [VA]	7.5 [VA]	10 [VA]	15 [VA]	20 [VA]										
IMPb	0.2S	250			5; 10														
		300	5			10													
		400		5; 10	5; 10	5; 10	5; 10												
	0.5S	200			5; 10														
		250			10	5; 10	10	5; 10											
		300	5	10	5; 10	5; 10	5; 10	5; 10											
		400		5; 10	5; 10	5; 10	5; 10	5; 10											
		500			5; 10	5; 10	5; 10	5; 10											
	0.2	250	5	10	5; 10														
		300	or	10	5; 10	5; 10	5; 10	5; 10											
		400	1	5; 10	5; 10	5; 10	5; 10	5; 10											
		500	5	5; 10	5; 10	5; 10	5; 10												
		150			10														
		200	5	10	5; 10	5; 10													
		250	or	10	5; 10	5; 10	5; 10	5; 10											
1; 3	0.5	300	1	5; 10	5; 10	5; 10	5; 10	5; 10	5; 10										
		400		5; 10	5; 10	5; 10	5; 10	5; 10	5; 10										
		500	5	5; 10	5; 10	5; 10	5; 10	5; 10	5; 10										
		100			10														
		150			10	10													
	1; 3	200	5	10	10	5; 10	10	10											
		250	or	10	5; 10	5; 10	5; 10	10											
		300	1	5; 10	5; 10	5; 10	5; 10	5; 10	5; 10										
		400		5; 10	5; 10	5; 10	5; 10	5; 10	5; 10										
		500	5	5; 10	5; 10	5; 10	5; 10	5; 10	5; 10										
		600	5		10	10	5; 10	5; 10	5; 10										


It is possible to order transformers of other parameters after prior arrangement with the manufacturer.

Transformers type ISWb

Current transformers for a cable of maximum 48 mm diameter or a busbar of maximum 60 × 30 mm dimensions.
Primary current range from 250 A to 1600 A.



Dimensional drawing



Type	Class	I_{pn} [A]	I_{sn} [A]	Security factor FS							Rated operational short-time thermal I_{th} [A]	peak I_{dyn} [A]	Maximum permissible voltage U_m [kV]	Rated test voltage U_p [kV]	Weight (approx.) [kg]					
				Burden																
				2.5 [VA]	5 [VA]	7.5 [VA]	10 [VA]	15 [VA]	20 [VA]	30 [VA]										
ISWb	0.2S	1200	5			5; 10														
		600			5; 10	5; 10	5; 10													
		1000			5; 10	5; 10	5; 10													
		1200	5			10	5; 10	5; 10	5; 10											
		1500				10	5; 10	5; 10	5; 10	5; 10										
	0.2	500				5; 10														
		600	5			5; 10														
		1000				10	5; 10													
		1200				10	5; 10	5; 10												
		250				5; 10														
ISWb	0.5	300				5; 10														
		400				5; 10	5; 10	5; 10												
		500				5; 10	5; 10	5; 10	5; 10											
		600				5; 10	5; 10	5; 10	5; 10	5; 10										
		750				5; 10	5; 10	5; 10	5; 10	5; 10										
		800	5			5; 10	5; 10	5; 10	5; 10	5; 10										
		1000				5; 10	5; 10	5; 10	5; 10	5; 10	5; 10									
		1200				10	5; 10	5; 10	5; 10	5; 10	5; 10	5; 10								
		1500				5; 10	5; 10	5; 10	5; 10	5; 10	5; 10	5; 10								
		1600	5			5; 10	5; 10	5; 10	5; 10	5; 10	5; 10	5; 10								
	1; 3	250				5; 10	5; 10													
		300				5; 10	5; 10													
		400				5; 10	5; 10	5; 10	5; 10											
		500				5; 10	5; 10	5; 10	5; 10	5; 10										
		600				5; 10	5; 10	5; 10	5; 10	5; 10										
		750				5; 10	5; 10	5; 10	5; 10	5; 10										
	1; 3	800				5; 10	5; 10	5; 10	5; 10	5; 10	5; 10									
		1000				5; 10	5; 10	5; 10	5; 10	5; 10	5; 10	5; 10								
		1200				10	5; 10	5; 10	5; 10	5; 10	5; 10	5; 10								
		1500				5; 10	5; 10	5; 10	5; 10	5; 10	5; 10	5; 10								
		1600				5; 10	5; 10	5; 10	5; 10	5; 10	5; 10	5; 10								


It is possible to order transformers of other parameters after prior arrangement with the manufacturer.

Transformers type ISWb2

Current transformers designed for mounting on current busbars of maximum dimensions 75 x 30 mm.
Primary current range from 500 A to 1200 A.



Dimensional drawing



Type	Class	I_{pn} [A]	I_{sn} [A]	Security factor FS						Rated operation current		Maximum permissible voltage U_m [kV]	Rated test voltage U_p [kV]	Weight (approx.) [kg]		
				Burden						short-time peak	thermal I_{th} [A]					
				2.5 [VA]	5 [VA]	7.5 [VA]	10 [VA]	15 [VA]	20 [VA]							
ISWb2	0.5S	600		10												
		750		10	10	5; 10										
		800	5	10	10	5; 10	5; 10									
		1000		10	10	5; 10	5; 10	5; 10								
		1200		10	10	5; 10	5; 10	5; 10	5; 10							
	0.2	750	5	10	10	5; 10										
		800	or	10	10	10										
		1000	1	10	10	5; 10	5; 10									
		1200	5	10	10	5; 10	5; 10	5; 10	5; 10							
		500		10	10											
ISWb2	0.5	600	5	10	10	5; 10	5; 10					60x I_{pn}	150x I_{pn}	0.72	3	0.7
		750	or	10	10	5; 10	5; 10									
		800	1	10	10	5; 10	5; 10	5; 10								
		1000		10	10	5; 10	5; 10	5; 10	5; 10							
		1200	5	10	10	5; 10	5; 10	5; 10	5; 10							
	1; 3	500		10	10	5; 10	5; 10									
		600	5	10	10	5; 10	5; 10									
		750	or	10	10	5; 10	5; 10									
		800	1	10	10	5; 10	5; 10	5; 10								
		1000		10	10	5; 10	5; 10	5; 10	5; 10							
		1200	5	10	10	5; 10	5; 10	5; 10	5; 10							


It is possible to order transformers of other parameters after prior arrangement with the manufacturer.

Transformers type ISWc

Current transformers designed for mounting on current busbars of maximum dimensions 40 x 10 mm and a cable of maximum 30 mm diameter. Primary current range from 75 A to 500 A. The special transformer window shape allows various busbar locations.



Dimensional drawing



Type	Class	I_{pn} [A]	I_{sn} [A]	Security factor FS								Rated operation current short-time thermal I_{th} [A]	Maximum peak permissible voltage U_m I_{dyn} [A]	Rated test voltage U_p [kV]	Weight (approx.) [kg]					
				Burden																
				1 [VA]	2.5 [VA]	5 [VA]	7.5 [VA]	10 [VA]	15 [VA]	20 [VA]	25 [VA]									
0.5S	300			5; 10									60x I_{pn}	150x I_{pn}	0.72	3				
	400	5		5; 10	5; 10															
	500			5; 10	5; 10	5; 10														
	300		10																	
	400			5; 10																
	500			5; 10	5; 10	5; 10														
	150		10																	
	200		10																	
	250		10; 5; 10																	
	300		10; 5; 10	5; 10	5; 10	5; 10														
ISWc	400			5; 10	5; 10	5; 10	5; 10	5; 10	5; 10	5; 10	5; 10									
	500			5; 10	5; 10	5; 10	5; 10	5; 10	5; 10	5; 10	5; 10									
	150		5; 10; 5; 10										60x I_{pn}	150x I_{pn}	0.72	3				
	200	5	10; 5; 10	5; 10																
	250	or 1	10; 5; 10	5; 10	5; 10	5; 10														
	300	1	10; 5; 10	5; 10	5; 10	5; 10	5; 10													
	400			5; 10	5; 10	5; 10	5; 10	5; 10	5; 10	5; 10	5; 10									
	500			5; 10	5; 10	5; 10	5; 10	5; 10	5; 10	5; 10	5; 10									
	75		10; 5; 10																	
	100		10; 5; 10																	
3	150		5; 10; 5; 10	5; 10																
	200		10; 5; 10	5; 10																
	250		10; 5; 10	5; 10	5; 10															
	300		10; 5; 10	5; 10	5; 10	5; 10														
	400			5; 10	5; 10	5; 10	5; 10	5; 10	5; 10	5; 10	5; 10									
	500			5; 10	5; 10	5; 10	5; 10	5; 10	5; 10	5; 10	5; 10									


It is possible to order transformers of other parameters after prior arrangement with the manufacturer.

Transformers type ISWd1

Current transformers designed for mounting on current busbars of maximum dimensions 80 x 10 mm or 60 x 30 mm and a cable of maximum 55 mm diameter. Primary current range from 250 A to 1000 A. The special transformer window shape allows various busbar locations.



Dimensional drawing



For $I_{pn} = 600$ A dimension A = 40 mm
For $I_{pn} \neq 600$ A dimension A = 55 mm

Type	Class	I_{pn} [A]	I_{sn} [A]	Security factor FS						Rated operation current short-time thermal I_{th} [A]	I_{dyn} [A]	Maximum permissible voltage U_m [kV]	Rated test voltage U_p [kV]	Weight (approx.) [kg]					
				Burden															
				2.5 [VA]	5 [VA]	7.5 [VA]	10 [VA]	15 [VA]	20 [VA]										
ISWd1	0.5S	500		10															
		600		10	5; 10														
		750	5	10	5; 10	5; 10	5; 10	5; 10	5; 10										
		800		10	5; 10	5; 10	5; 10	5; 10	5; 10										
		1000		10	5; 10	5; 10	5; 10	5; 10	5; 10	5; 10									
	0.2	600		10															
		750	5 or 1	10	5; 10	5; 10													
		800		10	5; 10	5; 10													
		1000		10	5; 10	5; 10	5; 10												
		250		10															
1; 3	0.5	300		10															
		400		10	5; 10														
		500		10	5; 10	5; 10													
		600		10	5; 10	5; 10	5; 10												
		750		10	5; 10	5; 10	5; 10	5; 10											
	5 or 1	800		10	5; 10	5; 10	5; 10	5; 10	5; 10										
		1000	5 or 1	10	5; 10	5; 10	5; 10	5; 10	5; 10	5; 10									
		250		10	10														
		300		10	5; 10														
		400		10	5; 10	5; 10	5; 10	5; 10											
1; 3	1; 3	500		10	5; 10	5; 10	5; 10	5; 10											
		600		10	5; 10	5; 10	5; 10	5; 10											
		750		10	5; 10	5; 10	5; 10	5; 10											
		800		10	5; 10	5; 10	5; 10	5; 10	5; 10										
		1000		10	5; 10	5; 10	5; 10	5; 10	5; 10	5; 10									


It is possible to order transformers of other parameters after prior arrangement with the manufacturer.

Transformers type ISWd2

Current transformers designed for mounting on current busbars of maximum dimensions 80 x 30 mm (horizontal) or 60 x 30 mm (vertical) and a cable of maximum 55 mm diameter. Primary current range from 1000 A to 1600 A. The special transformer window shape allows various busbar locations.



Dimensional drawing



Type	Class	I_{pn} [A]	I_{sn} [A]	Security factor FS					Rated operation current short-time thermal I_{th} [A]	I_{dyn} peak [A]	Maximum permissible voltage U_m [kV]	Rated test voltage U_p [kV]	Weight (approx.) [kg]					
				Burden														
				2.5 [VA]	5 [VA]	7.5 [VA]	10 [VA]	15 [VA]										
ISWd2	0.5S	1000	5	10	5; 10													
		1200	5	10	5; 10	5; 10	5; 10											
		1500	5	10	5; 10	5; 10	5; 10	5; 10										
		1600	5	10	5; 10	5; 10	5; 10	5; 10	5; 10									
	0.2	1200	5	10	5; 10	5; 10												
		1500	or 1	10	5; 10	5; 10												
		1600	1	10	5; 10	5; 10												
	0.5	1000	5	10	5; 10	5; 10				60x I_{pn}	150x I_{pn}	0.72	3					
		1200	5	10	5; 10	5; 10	5; 10											
		1500	5	10	5; 10	5; 10	5; 10	5; 10										
		1600	5	10	5; 10	5; 10	5; 10	5; 10	5; 10									
	1; 3	1000	or 1	10	5; 10	5; 10												
		1200	1	10	5; 10	5; 10	5; 10											
		1500	1	10	5; 10	5; 10	5; 10	5; 10	5; 10									
		1600	1	10	5; 10	5; 10	5; 10	5; 10	5; 10									


It is possible to order transformers of other parameters after prior arrangement with the manufacturer.

Transformers type ISWe

Current transformers designed for mounting on current busbars of maximum dimensions 120 x 30 mm.
Primary current range from 400 A to 4000 A.



Dimensional drawing



For $I_{pn} \leq 2500$ A dimension A = 42 mm
For $I_{pn} > 2500$ A dimension A = 62 mm

Type	Class	I_{pn} [A]	I_{sn} [A]	Security factor FS									Rated operation current short-time thermal I_{th} [A]	Rated operation current peak I_{dyn} [A]	Maximum permissible voltage U_m [kV]	Rated test voltage U_p [kV]	Weight (approx.) [kg]				
				Burden																	
				2.5 [VA]	5 [VA]	7.5 [VA]	10 [VA]	15 [VA]	20 [VA]	30 [VA]	45 [VA]	60 [VA]	75 [VA]								
0.2S	5	1500		10;										60x I_{pn}	150x I_{pn}	250 kA	0.72				
		1600		10; 10																	
		2000		10; 10; 10	10									100 kA	250 kA						
		2500		10; 10; 10	10; 10	5; 10															
		3000		10; 10; 10	10; 10	5; 10	5; 10														
		4000		10; 10; 10	10; 10	10	10; 10	10; 5; 10													
0.5S	5	600		10; 10										60x I_{pn}	150x I_{pn}	250 kA	0.72				
		750		10; 10; 5; 10																	
		800		10; 10; 5; 10	10; 5; 10																
		1000		10; 10; 10; 5; 10	10; 5; 10																
		1200		10; 10; 10; 5; 10	10; 5; 10									100 kA	250 kA						
		1500		10; 10; 10; 5; 10	10; 5; 10	5; 10															
ISWe	5 or 1	1600		10; 10; 10; 5; 10	10; 5; 10	5; 10								60x I_{pn}	150x I_{pn}	250 kA	0.72				
		2000		10; 10; 10; 10	10; 5; 10	5; 10															
		2500		10; 10; 10; 10	10; 5; 10	5; 10	10; 5; 10														
		3000		10; 10; 10; 10	10; 5; 10	5; 10	10; 5; 10	10; 5; 10													
		4000		10; 10; 10; 10	10; 5; 10	10; 5; 10	10; 5; 10	10; 5; 10						100 kA	250 kA						
		600		10; 10																	
0.2	5 or 1	750		10; 10										60x I_{pn}	150x I_{pn}	250 kA	0.72				
		800		10; 10; 5; 10																	
		1000		10; 10; 10; 5; 10	10; 5; 10																
		1200		10; 10; 10; 5; 10	10; 5; 10	5; 10															
		1500		10; 10; 10; 5; 10	10; 5; 10	5; 10	10; 5; 10							100 kA	250 kA						
		1600	1	10; 10; 10; 5; 10	10; 5; 10	5; 10	10; 5; 10	10; 5; 10													
ISWe	5 or 1	2000		10; 10; 10; 10	10; 5; 10	5; 10	10; 5; 10	10; 5; 10						60x I_{pn}	150x I_{pn}	250 kA	0.72				
		2500		10; 10; 10; 10	10; 5; 10	5; 10	10; 5; 10	10; 5; 10													
		3000		10; 10; 10; 10	10; 5; 10	5; 10	10; 5; 10	10; 5; 10													
		4000		10; 10; 10; 10	10; 5; 10	5; 10	10; 5; 10	10; 5; 10													
		400		10;										60x I_{pn}	150x I_{pn}						
		500		10; 10																	
0.5	5 or 1	600		10; 10; 5; 10																	
		750		10; 10; 5; 10	10; 5; 10																
		800		10; 10; 5; 10	10; 5; 10	5; 10															
		1000		10; 10; 10; 5; 10	10; 5; 10	5; 10															
		1200	1	10; 10; 10; 5; 10	10; 5; 10	5; 10								100 kA	250 kA						
		1500		10; 10; 10; 5; 10	10; 5; 10	5; 10	10; 5; 10														
1; 3	5 or 1	1600		10; 10; 10; 5; 10	10; 5; 10	5; 10								60x I_{pn}	150x I_{pn}	250 kA	0.72				
		2000		10; 10; 10; 10	10; 5; 10	5; 10	10; 5; 10	10; 5; 10													
		2500		10; 10; 10; 10	10; 5; 10	5; 10	10; 5; 10	10; 5; 10													
		3000		10; 10; 10; 10	10; 5; 10	5; 10	10; 5; 10	10; 5; 10													
		4000		10; 10; 10; 10	10; 5; 10	5; 10	10; 5; 10	10; 5; 10						100 kA	250 kA						
		400		10; 10; 5; 10																	
ISWe	5 or 1	500		10; 10; 5; 10	10; 5; 10	10								60x I_{pn}	150x I_{pn}	250 kA	0.72				
		600		10; 10; 5; 10	10; 5; 10	5; 10															
		750		10; 10; 5; 10	10; 5; 10	5; 10															
		800		10; 10; 5; 10	10; 5; 10	5; 10	10; 5; 10														
		1000	5	10; 10; 10; 5; 10	10; 5; 10	5; 10	10; 5; 10	10; 5; 10						100 kA	250 kA						
		1200	or 1	10; 10; 10; 5; 10	10; 5; 10	5; 10	10; 5; 10	10; 5; 10													
ISWe	5 or 1	1500		10; 10; 10; 5; 10	10; 5; 10	5; 10	10; 5; 10	10; 5; 10						100 kA	250 kA	250 kA	0.72				
		1600		10; 10; 10; 5; 10	10; 5; 10	5; 10	10; 5; 10	10; 5; 10													
		1800		10; 10; 10; 5; 10	10; 5; 10	5; 10	10; 5; 10	10; 5; 10						100 kA	250 kA						
		2000		10; 10; 10; 5; 10	10; 5; 10	5; 10	10; 5; 10	10; 5; 10													
		2500		10; 10; 10; 5; 10	10; 5; 10	5; 10	10; 5; 10	10; 5; 10						100 kA	250 kA						
		3000		10; 10; 10; 5; 10	10; 5; 10	5; 10	10; 5; 10	10; 5; 10													
		4000		10; 10; 10; 5; 10	10; 5; 10	5; 10	10; 5; 10	10; 5; 10													

It is possible to order transformers of other parameters after prior arrangement with the manufacturer.
There is a possibility of performing by special order transformers of primary current I_{pn} up to 6000 A.


Transformers type ISWf

Current transformers designed for mounting on current busbars of maximum dimensions 100 x 55 mm and a cable of maximum 70 mm diameter.

Primary current range from 500 A to 2500 A.



Dimensional drawing



Type	Class	I_{pn}	I_{sn}	Security factor FS								Rated operation current short-time thermal I_{th} [A]	I_{dyn} [A]	Maximum permissible voltage U_m [kV]	Rated test voltage U_p [kV]	Weight (approx.) [kg]					
				Burden																	
				2.5 [VA]	5 [VA]	7.5 [VA]	10 [VA]	15 [VA]	20 [VA]	30 [VA]	45 [VA]										
0.5S	5	600		10								60x I_{pn}	150x I_{pn}	0.72	3	2					
		750		10																	
		800		10	10	5; 10															
		1000		10	10	5; 10															
		1200	5	10	10	5; 10	5; 10														
		1500		10	10	10	5; 10	5; 10													
		1600		10	10	10	5; 10	5; 10													
		2000		10	10	10	5; 10	5; 10	5; 10	5; 10		100 kA	250 kA								
		2500		10	10	10	10	5; 10	5; 10	5; 10	5; 10										
0.2	5	1200		10	10	10						60x I_{pn}	150x I_{pn}	0.72	3	2					
		1500		10	10	10	5; 10	5; 10													
		1600	or 1	10	10	10	5; 10	5; 10													
		2000		10	10	10	5; 10	5; 10	5; 10			100 kA	250 kA								
		2500		10	10	10	10	5; 10	5; 10	5; 10											
		500			10	10	5; 10					60x I_{pn}	150x I_{pn}	0.72	3	2					
		600			10	10	5; 10	5; 10	5; 10												
		750			10	10	5; 10	5; 10	5; 10												
		800			10	10	5; 10	5; 10	5; 10												
		1000	or 1		10	10	5; 10	5; 10	5; 10												
ISWf	0.5	1200		10	10	5; 10	5; 10	5; 10	5; 10			60x I_{pn}	150x I_{pn}	0.72	3	2					
		1500		10	10	10	5; 10	5; 10	5; 10												
		1600		10	10	10	5; 10	5; 10	5; 10												
		2000		10	10	10	5; 10	5; 10	5; 10			100 kA	250 kA								
		2500		10	10	10	10	5; 10	5; 10	5; 10											
		500			10	10	5; 10	5; 10	5; 10			60x I_{pn}	150x I_{pn}	0.72	3	2					
		600			10	10	5; 10	5; 10	5; 10												
		750			10	10	5; 10	5; 10	5; 10												
		800			10	10	5; 10	5; 10	5; 10												
		1000	5 or 1		10	10	5; 10	5; 10	5; 10	5; 10											
1; 3	5	1200		10	10	5; 10	5; 10	5; 10	5; 10			60x I_{pn}	150x I_{pn}	0.72	3	2					
		1500		10	10	10	5; 10	5; 10	5; 10	5; 10											
		1600		10	10	10	5; 10	5; 10	5; 10	5; 10											
		2000		10	10	10	5; 10	5; 10	5; 10	5; 10		100 kA	250 kA								
		2500		10	10	10	10	5; 10	5; 10	5; 10	5; 10										

It is possible to order transformers of other parameters after prior arrangement with the manufacturer.
There is a possibility of performing by special order transformers of primary current I_{pn} up to 3000 A.


Transformers type ISWg

Current transformers designed for mounting on current busbars of maximum dimensions 60 x 30 mm and a cable of maximum 46 mm diameter.

Primary current range from 300 A to 1500 A.



Dimensional drawing



Type	Class	I_{pn} [A]	I_{sn} [A]	Security factor FS							Rated operation current short-time thermal I_{th} [A]	I_{dyn} [A]	Maximum permissible voltage U_m [kV]	Rated test voltage U_p [kV]	Weight (approx.) [kg]					
				Burden																
				2.5 [VA]	5 [VA]	7.5 [VA]	10 [VA]	15 [VA]	20 [VA]	30 [VA]										
ISWg	0.2S	1500	5	10	10	10	5; 10													
		500		5; 10																
		600		10																
		750		10	5; 10	5; 10	5; 10													
		800	5	10	5; 10	5; 10	5; 10													
	0.5S	1000		10	10	5; 10	5; 10	5; 10	5; 10	5; 10										
		1200		10	10	5; 10	5; 10	5; 10	5; 10	5; 10										
		1500		10	10	10	5; 10	5; 10	5; 10	5; 10										
		750		10	5; 10															
		800	5	10	5; 10															
0.2	1	1000	1	10	10	5; 10	5; 10	5; 10												
		1200		10	10	5; 10	5; 10	5; 10												
		1500	5	10	10	5; 10	5; 10	5; 10	5; 10	5; 10										
		300	5	10	10															
		400		5; 10																
	5	500		5; 10	5; 10	5; 10														
		600	5	10	5; 10	5; 10														
		750		10	5; 10	5; 10	5; 10													
		800	1	10	5; 10	5; 10	5; 10													
		1000		10	10	5; 10	5; 10	5; 10	5; 10	5; 10										
	1; 3	1200		10	10	5; 10	5; 10	5; 10	5; 10	5; 10										
		1500	5	10	10	10	5; 10	5; 10	5; 10	5; 10										
		300	5	10	10															
		400		5; 10	5; 10															
		500		5; 10	5; 10	5; 10														
1; 3	5	600	5	10	5; 10	5; 10	5; 10													
		750		10	5; 10	5; 10	5; 10													
		800	1	10	5; 10	5; 10	5; 10	5; 10												
		1000		10	10	5; 10	5; 10	5; 10	5; 10	5; 10										
		1200		10	10	5; 10	5; 10	5; 10	5; 10	5; 10										
	1500	1500	5	10	10	10	5; 10	5; 10	5; 10	5; 10										
		300		5	10	10														
		400		5; 10	5; 10															
		500		5; 10	5; 10	5; 10														
		600	5	10	5; 10	5; 10	5; 10													


It is possible to order transformers of other parameters after prior arrangement with the manufacturer.

Transformers type IWh1

Current transformers designed for mounting on current busbars of maximum dimensions 60 x 10 mm or 50 x 30 mm.
Primary current range from 200 A to 1000 A.



Dimensional drawing



Type	Class	I_{pn} [A]	I_{sn} [A]	Security factor FS								Rated operation current short-time thermal I_{th} [A]	I_{dyn} [A]	Maximum permissible voltage U_m [kV]	Rated test voltage U_p (approx.) [kV]	Weight [kg]						
				Burden																		
				2.5 [VA]	5 [VA]	7.5 [VA]	10 [VA]	15 [VA]	20 [VA]	30 [VA]												
0.5S	0.5	300		10								60x I_{pn}	150x I_{pn}	0.72	3	0.8						
		400		10	5; 10																	
		500		10	5; 10	5; 10																
		600	5	10	10	5; 10	5; 10															
		750		10	10	5; 10	5; 10	5; 10														
	0.2	800		10	10	5; 10	5; 10	5; 10	5; 10													
		1000		10	5; 10	5; 10	5; 10	5; 10	5; 10	5; 10												
		500		10	5; 10																	
		600	5	10	10																	
		750	or 1	10	10																	
ISWh1	0.5	800		10	10							60x I_{pn}	150x I_{pn}	0.72	3	0.8						
		1000		10	5; 10	5; 10	5; 10	5; 10	5; 10													
		200		10																		
		250		10	5; 10																	
		300		10	5; 10	5; 10																
	1; 3	400	5	10	5; 10	5; 10	5; 10															
		500	or 1	10	5; 10	5; 10	5; 10	5; 10														
		600	1	10	10	5; 10	5; 10	5; 10	5; 10													
		750		10	10	5; 10	5; 10	5; 10	5; 10	5; 10												
		800		10	10	5; 10	5; 10	5; 10	5; 10	5; 10												
		1000		10	5; 10	5; 10	5; 10	5; 10	5; 10	5; 10	5; 10											


It is possible to order transformers of other parameters after prior arrangement with the manufacturer.

Transformers type IWh2

Current transformers designed for mounting on cable of maximum 46 mm diameter.
Primary current range from 200 A to 1200 A.



Dimensional drawing



For $I_{pn} \leq 800$ A dimension A = 40 mm
For $I_{pn} > 800$ A dimension A = 40 mm or 60 mm

Type	Class	I_{pn} [A]	I_{sn} [A]	Security factor FS							Rated operation current		Maximum permissible voltage U_m [kV]	Rated test voltage U_p (approx.) [kV]	Weight [kg]
				Burden							short-time peak	thermal I_{th} [A]			
				2.5 [VA]	5 [VA]	7.5 [VA]	10 [VA]	15 [VA]	20 [VA]	30 [VA]					
0.5S	5	300	5; 10												
		400	5; 10	5; 10											
		500	5; 10	5; 10	5; 10										
		600	5; 10	5; 10	5; 10	5; 10									
		750	5; 10	5; 10	5; 10	5; 10	5; 10								
		800	5; 10	5; 10	5; 10	5; 10	5; 10								
		1000	5; 10	5; 10	5; 10*	5; 10*	5; 10*	5; 10*							
		1200	5; 10	5; 10	5; 10*	5; 10*	5; 10*	5; 10*	5; 10*						
	0.2	500	5; 10	5; 10											
		600	5; 10	5; 10											
ISWh2	0.5	750 or 1	5; 10	5; 10											
		800	5; 10	5; 10											
		1000	5; 10	5; 10	5; 10*	5; 10*	5; 10*								
		1200	5	5; 10	5; 10	5; 10*	5; 10*	5; 10*							
		200		5; 10											
		250		5; 10	5; 10										
		300		5; 10	5; 10	5; 10									
	1; 3	400	5	5; 10	5; 10	5; 10	5; 10	5; 10							
		500	or 1	5; 10	5; 10	5; 10	5; 10	5; 10							
		600		5; 10	5; 10	5; 10	5; 10	5; 10							
		750		5; 10	5; 10	5; 10	5; 10	5; 10							
		800		5; 10	5; 10	5; 10	5; 10	5; 10							
		1000		5; 10	5; 10	5; 10*	5; 10*	5; 10*	5; 10*						
		1200	5	5; 10	5; 10	5; 10*	5; 10*	5; 10*	5; 10*	5; 10*					

It is possible to order transformers of other parameters after prior arrangement with the manufacturer.

*dimension A = 60

Transformers type IMR0


Current transformers of small dimensions designed for mounting on a cable or busbar. Applied mainly for control measurements. Primary current range from 50 A to 200 A.






Dimensional drawing

IMR0 – current transformers for a cable max 18 mm or a busbar max 20 x 5 mm.

Version with secondary terminals



Version with leaded cables LYc
length approximately 20 cm



Type	Class	I_{pn} [A]	I_{sn} [A]	Security factor FS					Rated operation current short-time thermal I_{th} [A]	I_{dyn} [A]	Maximum permissible voltage U_m [kV]	Rated test voltage U_p [kV]	Weight (approx.) [kg]						
				Burden															
				1 [VA]	2.5 [VA]	4 [VA]	5 [VA]	7.5 [VA]											
IMR0	0.5	100	5 or 1	5; 10*	5; 10*				60x I_{pn}	150x I_{pn}	0.72	3	0.4						
		150	or	5; 10	5; 10*														
		200	1		5; 10	5; 10*													
	1	50	1	5; 10															
		100		5; 10*	5; 10														
		150		5; 10	5; 10	5; 10*	5; 10*												
		200			5; 10	5; 10*	5; 10*	5; 10*											
	3	40		5; 10*															
		45	5	5; 10*															
		50	or	5; 10*															
		75	1	5; 10*	5; 10*														
		80			10														
		100		5; 10*	5; 10	5; 10*													
		150		5; 10	5; 10	5; 10*	5; 10*												
		200			5; 10	5; 10*	5; 10*	5; 10*											
	5	20		5; 10*															
		25		5; 10*															
		30	1	5; 10*															
		35		5; 10*															
		40		5; 10*															
		45		5; 10*															
		50	5	5; 10*															
		75	or	5; 10*	5; 10*														
		80	1		10														
		100		5; 10	5; 10	5; 10*													
		150		5; 10	5; 10	5; 10*	5; 10*												
		200			5; 10	5; 10*	5; 10*	5; 10*											

It is possible to order transformers of other parameters after prior arrangement with the manufacturer.

*depth A=50 mm

Transformers type IMR1a


Current transformers of small dimensions designed for mounting on a cable or busbar. Applied mainly for control measurements. Primary current range from 75 A to 400 A.




Dimensional drawing

IMR1a – current transformers for a cable max 18 mm or a busbar max 20 x 10 mm.

Version with secondary terminals



Version with leaded cables LYc length approximately 20 cm



Type	Class	I_{pn} [A]	I_{sn} [A]	Security factor FS						Rated operation current short-time thermal I_{th} [A]	Rated peak operating current I_{dyn} [A]	Maximum permissible voltage U_m [kV]	Rated test voltage U_p [kV]	Weight (approx.) [kg]					
				Burden															
				1 [VA]	2.5 [VA]	5 [VA]	7.5 [VA]	10 [VA]	15 [VA]										
IMR1a	0.5	150		10	5; 10														
		200		10	10	5; 10													
		250			10	5; 10													
		300				10	5; 10; 5; 10												
		400					10	10; 5; 10; 5; 10											
	1	75			5; 10														
		100			5; 10	5; 10													
		150			10	5; 10	5; 10												
		200			10	5; 10	5; 10	5; 10											
		250				10	5; 10	5; 10											
	5	300	or		10	5; 10	5; 10	5; 10	5; 10										
		400		1	10	10	5; 10	5; 10	5; 10	5; 10									
		50				5; 10													
		75				5; 10													
		100				5; 10	5; 10												
	3; 5	150				10	5; 10	5; 10											
		200				10	5; 10	5; 10	5; 10										
		250					10	5; 10	5; 10										
		300						10	5; 10	5; 10									
		400							10	10; 5; 10; 5; 10									
		5	40			5; 10													

It is possible to order transformers of other parameters after prior arrangement with the manufacturer.

Transformers type IMR1b


Current transformers of small dimensions designed for mounting on a cable or busbar. Applied mainly for control measurements. Primary current range from 100 A to 500 A.




Dimensional drawing

IMR1b – current transformers for a cable max 23 mm or a busbar max 25 x 10 mm.

Version with secondary terminals



Version with leaded cables LYc length approximately 20 cm



Type	Class	I_{pn} [A]	I_{sn} [A]	Security factor FS							Rated operation current short-time thermal I_{th} [A]	I_{dyn} [A]	Maximum peak permissible voltage U_m [kV]	Rated test voltage U_p [kV]	Weight (approx.) [kg]					
				Burden																
				1 [VA]	1.5 [VA]	2.5 [VA]	5 [VA]	7.5 [VA]	10 [VA]	15 [VA]										
0.5	1	100		5; 10																
		150		5; 10	5; 10															
		200				5; 10														
		250				5; 10														
		300				5; 10	5; 10													
		400				10	5; 10	5; 10												
	1	500				10	10	5; 10	5; 10											
		100		5; 10																
		150		5; 10	5; 10	5; 10														
		200			5; 10	5; 10														
IMR1b	3	250			5; 10	5; 10														
		300				5; 10	5; 10	5; 10												
		400				10	5; 10	5; 10	5; 10	5; 10										
		500				10	5; 10	5; 10	5; 10	5; 10	5; 10									
		75	or 1	5; 10	5; 10	5; 10														
	5	100			5; 10	5; 10						60x I_{pn}	150x I_{pn}	0.72	3	0.4				
		150			5; 10	5; 10														
		200				5; 10	5; 10													
		250				5; 10	5; 10													
		300				5; 10	5; 10	5; 10												
	5	400				10	5; 10	5; 10	5; 10	5; 10	5; 10									
		500				10	5; 10	5; 10	5; 10	5; 10	5; 10									
		50			5; 10															
		75			5; 10															
		100			5; 10	5; 10	5; 10													
	5	150			5; 10	5; 10	5; 10													
		200				5; 10	5; 10													
		250				5; 10	5; 10													
		300				5; 10	5; 10	5; 10												
		400				10	5; 10	5; 10	5; 10	5; 10	5; 10									
		500				10	5; 10	5; 10	5; 10	5; 10	5; 10									

It is possible to order transformers of other parameters after prior arrangement with the manufacturer.

Transformers type IMR2


Current transformers of small dimensions designed for mounting on a cable or busbar. Applied mainly for control measurements. Primary current range from 150 A to 800 A.






Dimensional drawing

IMR2 – current transformers for a cable max 30 mm or a busbar max 40 x 10 mm.

Version with secondary terminals



Version with leaded cables LYc length approximately 20 cm



Type	Class	I_{pn} [A]	I_{sn} [A]	Security factor FS						Rated operation current short-time thermal I_{th} [A]	I_{dyn} [A]	Maximum permissible voltage U_m [kV]	Rated test voltage U_p [kV]	Weight (approx.) [kg]					
				Burden															
				2.5 [VA]	5 [VA]	7.5 [VA]	10 [VA]	15 [VA]	20 [VA]										
IMR2	0.5S	400			10														
		500	5	5; 10	5; 10														
		600		10	10														
		400		10	5; 10														
		500	5		10	5; 10	5; 10												
		600				10	5; 10	5; 10											
	0.2	250		10	5; 10														
		300		10	5; 10	5; 10	5; 10												
		400	5	10	5; 10	5; 10	5; 10	5; 10											
		500	or 1	5; 10	5; 10	5; 10	5; 10	5; 10	5; 10										
		600	1	10	5; 10	5; 10	5; 10	5; 10	5; 10										
		630			5; 10	5; 10	5; 10	5; 10	5; 10	5; 10									
	0.5	650			5; 10	5; 10	5; 10	5; 10	5; 10	5; 10									
		800	5		5; 10	5; 10	5; 10	5; 10	5; 10	5; 10									
		150			10														
		200			10	5; 10													
		250			10	5; 10	5; 10	5; 10											
		300	5	10	5; 10	5; 10	5; 10	5; 10											
	1; 3	400	or 1	10	5; 10	5; 10	5; 10	5; 10	5; 10										
		500	1	5; 10	5; 10	5; 10	5; 10	5; 10	5; 10										
		600		10	5; 10	5; 10	5; 10	5; 10	5; 10	5; 10									
		630			5; 10	5; 10	5; 10	5; 10	5; 10	5; 10									
		650			5; 10	5; 10	5; 10	5; 10	5; 10	5; 10									
		800	5		5; 10	5; 10	5; 10	5; 10	5; 10	5; 10									

It is possible to order transformers of other parameters after prior arrangement with the manufacturer.


Transformers type INSOA

Current transformers for special applications. Their special advantage is fast saturation – FS2. Designed for mounting on leads of maximum 30 mm diameter. The transformer is equipped with holders allowing assembly of the transformer on current busbars of maximum dimensions 30 × 10 mm.

Primary current range from 100 A to 400 A.



Dimensional drawing



Type	Class	I_{pn} [A]	I_{sn} [A]	Security factor FS					Rated operation current short-time thermal I_{th} [A]	I_{dyn} [A]	Maximum permissible voltage U_m [kV]	Rated test voltage U_p [kV]	Weight (approx.) [kg]					
				Burden														
				2.5 [VA]	4 [VA]	5 [VA]	7.5 [VA]	10 [VA]										
INSOA	3; 5	100			2													
		150		5; 10		2		2										
		200	or 5			2	2	2										
		250	1			2	2	2										
		300				2	2	2										
		400		10	5; 10	2	2	2										

It is possible to order transformers of other parameters after prior arrangement with the manufacturer.

Accessories

Voltage terminal

Transformers (excluding IMSd) can be equipped with a voltage terminal. It is an element not connected inside the transformer. It is used to connect the voltage circuit from the busbar to the terminal and then to the measurement system.


In transformers equipped with a cover there is the option of sealing this connection under the cover together with current circuit connections.

The voltage terminal comes as part of a set with the busbar, to which it is connected by a permanently mounted lead.



Support for mounting the transformer on a TS35 mounting busbar


The mounting support allows mounting of some types of transformers on the TS35 mounting busbar (details in the transformer selection, table on page 52).




Sketch drawing of the mounting base

Busbar mounting assembly

Bolt with openings for sealing, with a holder for 30 mm or 60 mm busbars.



Standard bolt with holder for 30 mm or 60 mm busbar



Copper sleeve

Sleeve dimension Ø 20/Ø 13 length 46 mm. Other dimensions available to special order.



Busbars

Copper nickel plated busbars with a set of assembly bolts.



Standard busbars

Busbar dimension [mm]	Number of bolts	Bolt dimension
20x5x150	2	M10
20x10x150	2	M10
30x5x150	2	M12
30x10x150	2	M12
40x5x150	2	M12
40x10x150	2	M12
60x5x150	2	M12
60x10x150	2	M12
80x8x230	4	M12
80x10x230	4	M12

It is possible to order busbars of other dimensions after prior arrangement with the manufacturer.

Transformer selection table

Type	IMSa					IMSb					IMSc					IMSd						
Class	0.2S	0.5S	0.2	0.5	1; 3	0.2S	0.5S	0.2	0.5	1; 3	0.2S	0.5S	0.2	0.5	1; 3	0.2S	0.5S	0.2	0.5	1; 3		
Primary current	1																					
	2																					
	3																					
	5																					
	10																					
	15																					
	20																					
	25																					
	30																					
	40																					
	50																					
	60																					
	75																					
	100					1																
	125																					
	150					2.5	5															
	200						5	7.5														
	250					5	2.5	5	10													
	300					5	5	10	15													
	400					7.5	7.5	15	15		5	10	10	10		2.5	2.5	10	10			
	500					5	7.5	10	15	20	5	5	10	15		10	20			5		
	600					5	15	5	15	20	5	10	10	15	20		5	10	20	10		
	750							5	10	20	20					5	15	20		10		
	800							5	5	10	20	20				5	7.5	15	20	10		
	1000							7.5	15	10	20	20				5	10	20	30	10		
	1200															5	10	20	30	15		
	1500															5	15	15	20	20		
	1600																15	20	20	10	30	
	2000															7.5	10	15	20	30		
	2500															10	10	20	20	7.5		
	3000																30	30	45	60	60	
	4000																	60	60	90	90	
	5000																		60	60	90	120
dimensions [mm]	width					60					80					100					184	
	depth					50					44					52					46	
	height					84					98					127					194	
window [mm]	busbar					40x10					60x10					80x10					120x30; 100x50	
	cable Ø					—					—					—					86	
primary current [A]						150-600					400-1000					400-2500					500-5000	
mounting	slides						●					●					●					●
	assembly support						●					●					●					●
	on a current circuit						U					U					Sd					Sd
insulation class*						A					A					E					E	

S – standard; ● – available as additional equipment; ● – not available; U –holder; Sd – set bolts

Provided data refer to the secondary current value of 5A and FS10.

Transformer maximum loading values in [VA] have been given in the table, at a given value of the primary current in [A] in a given class.

More details and possibility of FS5 design have been given inside the catalogue.

*Insulation class B available by special order.

After arrangement with the manufacturer there is a possibility of transformer design of other: accuracy class, ratio, power or with an extended current range (ext. 150%; 200%).

Transformer selection table

Type	ISWf						ISWg						ISWh1						ISWh2						IMPa							
Class	0.5S	0.2	0.5	1; 3	0.2S	0.5S	0.2	0.5	1; 3	0.5S	0.2	0.5	1; 3	0.5S	0.2	0.5	1; 3	0.5S	0.2	0.5	1; 3	0.5S	0.2	0.5	1; 3							
Primary current	1																															
	2																															
	3																															
	5																															
	10																															
	15																															
	20																															
	25																															
	30																															
	40																															
	50																															
	60																															
	75																															
	100																									2.5	5					
	125																									5	5					
	150																									7.5	10					
	200																	2.5	5						2.5	5						
	250																	5	5						5	5						
	300															5	5	2.5	7.5	10	2.5	7.5	10	10	10	7.5	20	20				
	400															2.5	5	5	10	10	5	10	10	10	10							
	500		10	15						2.5	7.5	7.5	7.5	5	10	15	7.5	5	10	15												
	600		15	15						2.5	7.5	10	10	5	15	15	10	5	15	15	15											
	750	2.5	15	15						10	5	10	10	15	5	15	20	15	5	15	20											
	800	7.5	15	15						10	5	10	15	15	5	15	20	15	5	15	20											
	1000	7.5	15	20						20	15	30	30	20	15	20	30	20	15	20	30											
	1200	10	20	20						30	15	30	30								20	15	20	30								
	1500	15	15	30	30					10	30	20	30	30																		
	1600	15	15	30	30																											
	2000	30	20	45	45																											
	2500	30	20	30	30																											
	3000																															
	4000																															
	5000																															
dimensions [mm]	width						129							88				85														
	depth						60							60				40; 60														
	height						170							130				100														
window [mm]	busbar						100x55							60x30				60x10; 50x30														
	cable Ø						70							46				—														
primary current [A]							500-2500							300-1500				200-1000														
mounting	slides						S							S				S														
	assembly support						●							●				●														
	on a current circuit						Sd							Sd				Sd														
insulation class*							E							E				E														

S – standard; ● – available as additional equipment; ● – not available; U –holder; Sd – set bolts

Provided data refer to the secondary current value of 5A and FS10.

Transformer maximum loading values in [VA] have been given in the table, at a given value of the primary current in [A] in a given class.

More details and possibility of FS5 design have been given inside the catalogue.



*Insulation class B available by special order.

After arrangement with the manufacturer there is a possibility of transformer design of other: accuracy class, ratio, power or with an extended current range (ext. 150%; 200%).

Primary current range

Type	50 A	75 A	100 A	150 A	200 A	250 A	300 A	400 A	500 A	600 A	800 A	1000 A	1200 A	1500 A	1600 A	2500 A	4000 A	5000 A
IMR0	●		●															
IMW	●	●	●	●	●	●	●											
ISWc	●	●	●	●	●	●	●											
IMR1a	●	●	●	●	●	●	●	●	●									
IMPa		●	●	●	●	●	●	●										
INSOA		●	●	●	●	●	●	●	●									
IMR1b		●	●	●	●	●	●	●	●			●						
IMPb		●	●	●	●	●	●	●	●	●	●	●						
IMSa		●	●	●	●	●	●	●	●	●	●	●						
IMR2			●	●	●	●	●	●	●	●	●	●						
ISWh1				●	●	●	●	●	●	●	●	●	●					
ISWh2					●	●	●	●	●	●	●	●	●	●		●		
SWd1						●	●	●	●	●	●	●	●	●				
ISWb						●	●	●	●	●	●	●	●	●				
ISWg							●	●	●	●	●	●	●	●				
IMSb								●	●	●	●	●	●	●				
IMSc								●	●	●	●	●	●	●		●		
ISWe									●	●	●	●	●	●		●		
ISWb2										●	●	●	●	●		●		
ISWf										●	●	●	●	●		●		
IMSd										●	●	●	●	●		●		
ISWd2											●	●	●	●		●		●

Certificates



Contact us

ABB Sp. z o.o.**Branch in Przasnysz**

59 Leszno Str.

06-300 Przasnysz, Poland

Phone: +48 29 75 33 377, +48 29 75 33 233

Fax: +48 29 75 33 327

www.abb.pl

We reserve the right to make technical changes or modify the contents of this document without prior notice. With regard to purchase orders, the agreed particulars shall prevail.

ABB does not accept any responsibility whatsoever for potential errors or possible lack of information in this document.

We reserve all rights in this document and in the subject matter and illustrations contained therein. Any reproduction – in whole or in parts – is forbidden without ABB's prior written consent.

© Copyright 2011 ABB
All rights reserved