

ADAM-4541 ADAM-4542+ ADAM-4561/4562

Multi-mode Fiber Optic to RS-232/422/485 Converter
Single-mode Fiber Optic to RS-232/422/485 Converter
1-port Isolated USB to RS-232/422/485 Converter



ADAM-4541



ADAM-4542+



ADAM-4561/4562



Specifications

General

- Power Input Unregulated 10 ~ 30 V_{DC}
- Connectors 1 x plug-in terminal block (#14 ~ 22 AWG)
2 x ST fiber connector
- Power Consumption 1.5 W @ 24 V_{DC}

Serial Communications

- Communication Mode Asynchronous
- Speed Modes (bps) 1,200, 2,400, 4,800, 9,600, 19.2 k, 38.4 k, 57.6 k, 115.2 k and RS-232/422 mode (switchable)
- Transmission Mode Full/half duplex, bidirectional

Fiber Optic Communications

- Optical Power Budget (Attenuation) 12.5 dB (measured with 62.5/125 μm)
- Transmission Distance 2.5 km
- Transmission Mode Multi mode (Send and Receive)
- Wavelength 820 nm

Specifications

General

- Power Input Unregulated 12 ~ 24 V_{DC}
- Connectors 1 x plug-in terminal block (#14 ~ 22 AWG)
(RS-232/422/485)
1 x SC fiber connector
- Power Consumption 3 W @ 24 V_{DC}
- Operation Modes Support Point-to-Point, Redundant* and Ring (half-duplex)
- Redundant Transfer Time 1 μs

Serial Communications

- Communication Mode Asynchronous
- Speed Modes (bps)* 1,200, 2,400, 4,800, 9,600, 19.2 k, 38.4 k, 57.6 k, 115.2 k, 230.4 k, 460.8 k, 921.6 k and RS-232/422/485 mode (switchable)
- Transmission Modes Full/half duplex, bidirectional

Fiber Optic Communications

- Optical Power Budget (Attenuation) 15 dB
- Transmission Distance 15 km
- Transmission Mode Single mode (Send and Receive)
- Wavelength 1310 nm

Specifications

General

- Connectors Network: USB-type A connector (type A to type B cable provided)
Serial:
ADAM-4561 1 x plug-in terminal (#14 ~ 22 AWG) (3-wire RS-232/422/485)
ADAM-4562 1 x DB-9 serial connectors (9-wire RS-232)

Isolation Voltage

- ADAM-4561: 3,000 V_{DC}
- ADAM-4562: 2,500 V_{DC}

Power Consumption

- ADAM-4561: 1.5 W @ 5 V
- ADAM-4562: 1.1 W @ 5 V

Driver Support

- ADAM-4561: Windows 2000/XP/Vista/7/8 (32&64-bit)
- ADAM-4562: Windows 2000/XP/Vista/7/8(32&64-bit)

USB Specification Compliance

- ADAM-4561: USB 2.0
- ADAM-4562: USB 2.0

Serial Communications

- Speed Modes (bps) 75 bps to 115.2 kbps
- Transmission Modes Full/half duplex, bidirectional

Common Specifications

Environment

- Operating Humidity 5 ~ 95% RH
- Operating Temperature ADAM-4541/4542+: -10 ~ 70°C (14 ~ 158°F)
ADAM-4561/4562: 0 ~ 70°C (32 ~ 158°F)
- Storage Temperature -25 ~ 85°C (-13 ~ 185°F)

Ordering Information

- ADAM-4541 Multi-mode Fiber to RS-232/422/485 Converter
- ADAM-4542+ Single-mode Fiber to RS-232/422/485 Converter
- ADAM-4561 1-port Isolated USB to RS-232/422/485 Converter
- ADAM-4562 1-port Isolated USB to RS-232 Converter