

Four-port Industrial USB 2.0 Hub

Model UH104

B+B SMARTWORX

Powered by

ADVANTECH

www.advantech-bb.com



PRODUCT FEATURES

- Expands 1 USB port to 4 USB ports (USB 2.0)
- 15 kV ESD protection
- USB 2.0, 480 Mbps, high speed
- Wide operating temperature (-40 to +80 °C)
- Rugged panel mount case
- High retention USB connectors hold cables tight

USB Connectivity Where You Need It

Model UH104 is a compact, industrial grade four port USB 2.0 hub. It has high retention USB connectors that work with standard USB cables to ensure a tight connection in high vibration applications – requiring up to 1.54 kg (3.4 lbs) force to disconnect them. It provides true USB 2.0 data transmission through each port, even during heavy load applications. The UH104 is a plug-and-play device, meaning that there are no additional drivers to load.

Bus Power

The hub is powered entirely by your high power USB port, leaving your installation uncluttered by power cabling. As a bus powered device, it provides 100 mA of power to downstream peripherals which is adequate for most applications. *Important: check your device to be sure this power is adequate. If it needs more power, B+B SmartWorx has a variety of externally powered hubs to select from.*

Mount It Anywhere

The compact polycarbonate plastic enclosure comes equipped with mounting brackets to secure it to a panel, counter top or other flat surface. A standard USB cable is required to connect it to your PC.

Industrial Specifications

Industrial EMC specifications make this hub more robust than other office grade products.

ORDERING INFORMATION

MODEL NUMBER	DESCRIPTION
UH104	4-port Industrial USB 2.0 Hub

USB cable required - sold separately.

ACCESSORIES - optional, sold separately

USBAMB-3F - 0.9 m (3 ft) USB extension cable

All product specifications are subject to change without notice.

UH104_4817ds

Four-port Industrial USB 2.0 Hub

Model UH104



SPECIFICATIONS

USB INTERFACE	
Standards	USB 2.0
Upstream Port	(1) Type B Female – High Retention
Downstream Port	(4) Type A Female – High Retention
Speed	480 Mbps on each port Multi-transaction Translator, 1 per port
ESD	15 kV Air, 8 kV Contact
High Retention	USB ports require 15 N - 3.4 lbs (1.54 kg) force withdrawal force using standard USB cable
POWER	
Source	5 VDC from USB Bus
Downstream Power	100 mA per Port
MECHANICAL	
Dimensions	6.1 x 4.45 x 2.79 cm (2.4 x 1.75 x 1.10 in)
Enclosure	IP 30, Polycarbonate Plastic
Weight	49.90 g (0.11 lb)
MTBF	552,747 Hours
MTBF Calc. Method	MIL 217F Parts Count Reliability

ENVIRONMENTAL	
Operating Temperature	-40 to 80 °C (-40 to 176 °F)
Storage Temperature	-40 to 85 °C (-40 to 185 °F)
Operating Humidity	0 to 95% Non-condensing
APPROVALS, DIRECTIVES, STANDARDS	
FCC, CE	
Directives (EU)	2014/30/EU - Electromagnetic Compatibility Directive 2011/65/EU - Reduction of Hazardous Substances Directive (RoHS) 2012/19/EU - Waste Electrical and Electronic Equipment (WEEE)
Standards (EMC)	EN 55032: Class B - Information Technology Equipment - RF Emissions EN 55024 - Information Technology Equipment - Immunity Characteristics - Limits and Methods of Measurements EN 61000-6-1 - Generic Immunity Standard for Residential, Commercial and Light-Industrial Environments

MECHANICAL DIAGRAM

