Dalton Gear Company

212 Colfax Ave. N.


Minneapolis, MN 55405 US

Phone: 612-374-2150 • Fax: 612-374-2467 E-Mail: daltongear@worldnet.att.net

Secondary Adjusting Arm With Base

- The octagon mounting head allows for rough adjustment in any direction. Fine adjustments are achieved by movement of the base using the slots. The position of the mounting head in relation to the slots allows for greater adjusting movement than competitive models.
- Dalton positioners are made of 60-45-10 ductile iron which insures strength and wear resistance.
- · Mounting of idlers is achieved by using high strength bolts which secure the inner race of Dalton idler bearings to the positioner.
- · Please call for discounts on list prices.





Results 1 - 7 of 7	A - Length	B - Length	C - Height	D - Width	E - Pitch	F - Width	List Price
2SB-4	3-13/16 Inch	3-1/2 Inch	5 Inch	2 Inch	2-1/8 Inch	1/2 Inch	\$61.00
2SB-5	3-13/16 Inch	3-1/2 Inch	5 Inch	2 Inch	2-1/8 Inch	1/2 Inch	\$61.80
2SB-6	3-13/16 Inch	3-1/2 Inch	5 Inch	2 Inch	2-1/8 Inch	1/2 Inch	\$64.60
D2SB-4	3-13/16 Inch	3-1/2 Inch	5 Inch	2 Inch	2-1/8 Inch	1/2 Inch	\$62.00
D2SB-5	3-13/16 Inch	3-1/2 Inch	5 Inch	2 Inch	2-1/8 Inch	1/2 Inch	\$63.00
D2SB-6	3-13/16 Inch	3-1/2 Inch	5 Inch	2 Inch	2-1/8 Inch	1/2 Inch	\$66.60

Results 1 - 7 of 7