Dalton Gear Company

212 Colfax Ave. N.


Minneapolis, MN 55405 US

Phone: 612-374-2150 • Fax: 612-374-2467 E-Mail: daltongear@worldnet.att.net

Shaft Mounted Tensioner

- No stripped out threads in the split base because 2 locking screws are used in a strong Ductile iron base.
- · No slippage on mounting shaft occurs because the locking screws insure a firm and uniform lock on the mounting shaft.
- The split base is available with a one inch shaft size as stock and can be supplied for other shaft sizes upon request.
- · Please call for discounts on list prices.





| Results 1 - 5 of 5 | B - Pitch | C - Width | D - Height | E - Diameter | F - Diameter | Length of Bolt | List Price |
|--------------------|-----------|------------|------------|--------------|--------------|----------------|------------|
| | | | | | | | |
| 8SM-5 | 4 Inch | 1-1/2 Inch | 5-7/8 Inch | 1 Inch | 5/8 Inch | 1 1/2 Inch | \$46.00 |
| 8SM-6 | 4 Inch | 1-1/2 Inch | 5-7/8 Inch | 1 Inch | 3/4 Inch | 1 1/2 Inch | \$49.00 |
| D8SM-4 | 4 Inch | 1-1/2 Inch | 5-7/8 Inch | 1 Inch | 1/2 Inch | 2 Inch | \$46.20 |
| D8SM-5 | 4 Inch | 1-1/2 Inch | 5-7/8 Inch | 1 Inch | 5/8 Inch | 2 Inch | \$46.40 |

Results 1 - 5 of 5