

Datasheet - A-K5P-M12-S-G-15M-BK-2-X-A-1

Connector / Connector M12 / A-K5M12



Preferred typ



- Pre-wired cable
- 5-pole

(Minor differences between the printed image and the original product may exist!)

Ordering details

Product type description	A-K5P-M12-S-G-15M-BK-2-X-A-1
Article number	101209948
EAN code	4030661384702

Approval

Approval	-
----------	---

Global Properties

Product name	Anschlussleitung A-K5M12
Versions	Pre-wired cable
Materials	
- Material of the housings	
- Material of the cable mantle	PUR
Connector	female connector
Design	straight
Colouring	
- Enclosure color	Black
- Cable colour	Black
Cable type	
Weight	500 g
Coding	A

Mechanical data

termination	M12
-------------	-----

Bolting device	Screw locking
Cable length	15 m
Conductors	5 x 0,25 mm ²

Ambient conditions

Protection class	IP67
------------------	------

Electrical data

Number of poles	5 piece
Number of cores	5 piece
Rated operating voltage U _e	250 V
Operating current I _e	4 A

LED switching conditions display

LED switching conditions display (Y/N)	No
--	----

Pin assignment

1	Brown
2	White
3	Blue
4	Black
5	Grey

Ordering code

(1)-(2)-(3)-(4)-(5)-(6)-(7)-(8)-(9)-(10)-(11)

notice

(1)	cable
A	Pre-wired cable
V	Interconnector
S	Connector without cable
(2)a	Connector
K	female connector
KK	female connector - female connector
S	male connector
SS	male connector - male connector
SK	male connector - female connector
(2)b	Number of poles
1P	1-pole
2P	2-pole
3P	3-pole
4P	4-pole
5P	5-pole
6P	6-pole
7P	7-pole
8P	8-pole
...	...
(3)	termination
M6.5	round 6.5 mm

M8
M12
M18
M23
DIN43650
TUCHEL

(4)

R
S

(5)

G
W

(6)

X
0.3M
2M
2.5M
3M
5M
10M
15M
20M

(7)

X
BK
GY
OG

(8)

X
1
2
3
4

(9)

X
1LP
2LP
3LP

(10)

X
A
B

(11)

1
2
3
4

M8 / round 8 mm
M12
M18
M23
DIN 43650
TUCHEL

Bolting device

Latching interlocking
Screw locking

Design

straight
angled

Cable length

without
0,3 m
2 m
2.5 m
3 m
5 m
10 m
15 m
20 m

Cable colour

without
Black
Grey
Orange

Material of the cable

-
PVC
PUR
rubber
Silicone

Miscellaneous

Neutral
1x LED - PNP
2x LED - PNP
3x LED - PNP


Coding

without
A-Coding
B-Coding

Approval

without





Contact arrangement

K.A. Schmersal GmbH & Co. KG, Möddinghofe 30, D-42279 Wuppertal

The data and values have been checked thoroughly. Technical modifications and errors excepted.

Generiert am 07.02.2013 - 22:25:48h Kasbase 2.2.2.F DBI

Image

Image
et=sS
e