

Datasheet - A-K8+1P-M23-S-G-5M-BK-1-X-X-4

Connector / Connector M23 / A-K9M23

 Preferred typ

- Pre-wired cable
- 8+1-pole

(Minor differences between the printed image and the original product may exist!)

Ordering details

Product type description	A-K8+1P-M23-S-G-5M-BK-1-X-X-4
Article number	101209959
EAN code	4030661384757

Global Properties

Product name	Anschlussleitung A-K9M23
Versions	Pre-wired cable
Materials	
- Material of the housings	Metal film
- Material of the cable mantle	
Connector	female connector
Design	straight
Colouring	
- Enclosure color	Chromium-plated
- Cable colour	Black
Cable type	LiYY
Weight	681 g
Coding	

Mechanical data

termination	M23
Bolting device	Screw locking
Cable length	5 m
Conductors	8 x 0,75 mm ²

Ambient conditions

Protection class IP67

Electrical data

Number of poles 8 piece + 1P
Number of cores 8 piece
Rated operating voltage U_e
Operating current I_e

LED switching conditions display

LED switching conditions display (Y/N) No

Pin assignment




1	A1 U_e
2	X1 Safety input 1
3	A2 GND
4	Y1 Safety output 1
5	OUT Diagnostic output
6	X2 Safety input 2
7	Y2 Safety output 2
8	IN Solenoid control
9	Not used

Ordering code

(1)-(2)-(3)-(4)-(5)-(6)-(7)-(8)-(9)-(10)-(11)

notice

(1)	cable
A	Pre-wired cable
V	Interconnector
S	Connector without cable
(2)a	Connector
K	female connector
KK	female connector - female connector
S	male connector
SS	male connector - male connector
SK	male connector - female connector
(2)b	Number of poles
1P	1-pole
2P	2-pole
3P	3-pole
4P	4-pole
5P	5-pole
6P	6-pole
7P	7-pole
8P	8-pole
...	...


(3)	termination
M6.5	round 6.5 mm
M8	M8 / round 8 mm
M12	M12
M18	M18
M23	M23
DIN43650	DIN 43650
TUCHEL	TUCHEL
(4)	Bolting device
R	Latching interlocking
S	Screw locking
(5)	Design
G	straight
W	angled
(6)	Cable length
X	without
0.3M	0,3 m
2M	2 m
2.5M	2.5 m
3M	3 m
5M	5 m
10M	10 m
15M	15 m
20M	20 m
(7)	Cable colour
X	without
BK	Black
GY	Grey
OG	Orange
(8)	Material of the cable
X	-
1	PVC
2	PUR
3	rubber
4	Silicone
(9)	Miscellaneous
X	Neutral
1LP	1x LED - PNP
2LP	2x LED - PNP
3LP	3x LED - PNP
(10)	Coding
X	without
A	A-Coding
B	B-Coding
(11)	Approval
1	without
2	 UL
3	 CSA
4	 USA/CAN

Documents

Mounting and wiring instructions (de, en, fr) 42 kB, 23.07.2009

Code: m_ak9p01

Images



Contact arrangement

K.A. Schmersal GmbH & Co. KG, Möddinghofe 30, D-42279 Wuppertal

The data and values have been checked thoroughly. Technical modifications and errors excepted.

Generiert am 07.02.2013 - 22:38:50h Kasbase 2.2.2.F DBI

Image

Image
et=sS