

## Datasheet - SD-2V-F-SK

Accessories SD interface / SD junction boxes (junction box for 2 components)



(Minor differences between the printed image and the original product may exist!)

- field device
- junction box for 2 components, with screw terminals
- the terminals of the junction box are integrated in an enclosure
- Double-insulated
- 4 cable entries M20

### Ordering details

Product type description	SD-2V-F-SK
Article number	101189194
EAN code	4030661352572

### Approval

Approval	VDE 0100
----------	----------

### Global Properties

Product name	SD-Verteiler
Compliance with the Directives (Y/N)	Yes
Protection rating	II
Materials	
- Material of the housings	Plastic, thermoplastic, self-extinguishing
Weight	395 g

### Mechanical data

termination	Screw connection
Cable section	
- Min. Cable section	0,25 mm <sup>2</sup>
- Max. Cable section	2.5 mm <sup>2</sup>
notice	All indications about the cable section are including the conductor ferrules.

### Ambient conditions

Ambient temperature	
- Min. environmental temperature	-25 °C

- Max. environmental temperature	+70 °C
Storage and transport temperature	
- Min. Storage and transport temperature	-25 °C
- Max. Storage and transport temperature	+85 °C
Relative humidity	30 % ... 95 %, non-condensing
Protection class	IP65
Air clearances and creepage distances To IEC/EN 60664-1	
- Rated impulse withstand voltage $U_{imp}$	0,8 kV
- Overvoltage category	III
- Degree of pollution	3

## Electrical data

---

Rated insulation voltage $U_i$	32 VDC
Rated operating voltage $U_e$	24 VDC - 15 % / + 10 % (stabilised PELV)
Operating current $I_e$	16 A
Fuse rating for the operating voltage	3x Safety fuse, 2 A slow blow
Device insulation	16 A

## Dimensions

---

Dimensions	
- Width	160 mm
- Height	106.5 mm
- Depth	57 mm

## notice

---

To each SD junction box, 2 (optionally 3) components can be connected.

## Documents


---

**Mounting and wiring instructions** (de, en, fr) 271 kB, 06.03.2008

Code: m\_sdv01

## Images

---



Dimensional drawing (basic component)

Image

Image  
et=sS  
e