

1 About this document

1.1 Function

This operating instructions manual provides all the information you need for the mounting, set-up and commissioning to ensure the safe operation and disassembly of the safety switchgear. The operating instructions must be available in a legible condition and a complete version in the vicinity of the device.

1.2 Target group: authorised qualified personnel

All operations described in this operating instructions manual must be carried out by trained specialist personnel, authorised by the plant operator only.

Please make sure that you have read and understood these operating instructions and that you know all applicable legislations regarding occupational safety and accident prevention prior to installation and putting the component into operation.

The machine builder must carefully select the harmonised standards to be complied with as well as other technical specifications for the selection, mounting and integration of the components.

1.3 Explanation of the symbols used



Information, hint, note: This symbol is used for identifying useful additional information.

 \triangle

Caution: Failure to comply with this warning notice could lead to failures or malfunctions. **Warning:** Failure to comply with this warning notice could lead to physical injury and/or damage to the machine.

1.4 Appropriate use

The products described in these operating instructions are developed to execute safety-related functions as part of an entire plant or machine. It is the responsibility of the manufacturer of a machine or plant to ensure the proper functionality of the entire machinery or plant.

The safety switchgear must be exclusively used in accordance with the versions listed below or for the applications authorised by the manufacturer. Detailed information regarding the range of applications can be found in the chapter "Product description".

1.5 General safety instructions

The user must observe the safety instructions in this operating instructions manual, the country-specific installation standards as well as all prevailing safety regulations and accident prevention rules.

Further technical information can be found in the Schmersal catalogues or in the online catalogue on the Internet: www. schmersal.net.

The information contained in this operating instructions manual is provided without liability and is subject to technical modifications.



1

The entire concept of the control system, in which the safety component is integrated, must be validated to EN ISO 13849-2.

There are no residual risks, provided that the safety instructions as well as the instructions regarding mounting, commissioning, operation and maintenance are observed.

1.6 Warning about misuse



In case of inadequate or improper use or manipulations of the safety switchgear, personal hazards or damage to machinery or plant components cannot be excluded. The relevant requirements of the standard EN 999 must be observed.

1.7 Exclusion of liability

We shall accept no liability for damages and malfunctions resulting from defective mounting or failure to comply with this operating instructions manual. The manufacturer shall accept no liability for damages resulting from the use of unauthorised spare parts or accessories.

For safety reasons, invasive work on the device as well as arbitrary repairs, conversions and modifications to the device are strictly forbidden; the manufacturer shall accept no liability for damages resulting from such invasive work, arbitrary repairs, conversions and/or modifications to the device.

2 Product description

2.1 Ordering code

These mounting instructions apply to the following types:

SMS ^① - ^②				
No.	Option	Description		
1	4	without ramp profile		
	5	with moulded ramp profile		
2		Width x length		
	250-500	250 x 500 mm		
	500-500	500 x 500 mm		
	500-1000	500 x 1000 mm		
	750-1000	750 x 1000 mm		
	1000-1000	1000 x 1000 mm		
	1000-1500	1000 x 1500 mm		

Only if the information described in this operating instructions manual are realised correctly, the safety function and therefore the compliance with the Machinery Directive is maintained.

2.2 Special versions

For special versions, which are not listed in the order code below 2.1, these specifications apply accordingly, provided that they correspond to the standard version.

2.3 Destination and use

Safety mats are used for the protection of man on machinery and plants with hazardous movements. Typical fields of application are, for instance, the protection of hazardous areas and surfaces on woodprocessing machines, scissor lifts or punching presses. The safety mats build a uniplanar safety device, which detects the presence of persons. The safety mats consist of two separate current-carrying steel plates. The plates are held apart by insulating strips. Upon actuation of the pressure-sensitive safety mat, an electrical cross-wire short is produced between the steel plates. If a person steps onto the safety mat, the connected safety-monitoring module will immediately stop the hazardous movement.

The entire safety mat consists of the safety mat(s) and a safety-monitoring module of the SRB 301HC/R or SRB 301HC/T series.

The safety mats of the SMS 4 and SMS 5 series must not be used without safety-monitoring module. Otherwise, the EC prototype certificate becomes void.

The user must evaluate and design the safety chain in accordance with the relevant standards and the required safety level.

2.4 Safety distance

During the design of the protection, the tun-on time, the approach speed of the operating staff, the safety distance as well as stepping over and the manipulation of the safety guard must be considered in particular. The adequacy of dimensioning and mounting must ensure that the operators cannot reach the nearest danger point before the machine has come to a standstill. The standard EN 999 (Safety of Machinery, Approaching Speed of Body Members) provides a formula to calculate the safety distance for this connection.

Calculation formula to EN 999: S = K x (T1 +T2) + (1200 - 0.4 H)

- S Minimum safety distance in millimetres, measured from the hazardous area to the detection point, the detection line or the protected field
- K Constant in millimetres per second, derived from data through the approaching speed of the body or the body member (1600 mm/s)
- H Distance through the reference plane (e.g. the floor) in millimetres (for safety mats generally 0 mm)
- T1 The maximum response time of the safety device between the triggering of the perceptive element (the safety mat) and the time, at which the safety guard (safety-monitoring module) has switched the output signal to the "OFF" state.
- T2 the response time of the machine, i.e. the time required to shutdown the machine or to eliminate the risk, after the transmission of the output signal of the safety guard

The safety distance therefore generally can be calculated in the following way:

S = 1600 mm/s x (T1 +T2) + 1200 mm

Example:

The safety distance must be calculated with a response time of 142.5 ms for the machine and a response time of 45 ms for the safety guard. The safety mat is installed at ground level.

- S = 1600 mm/s x (0.045 s + 0.1425 s) + 1200 mm
- S = 1600 mm/s x (0.1875 s) + 1200 mm
- S = 300 mm + 1200 mm
- S = 1500 mm

EN

Operating instructions Safety mats

2.5 Technical data

Standards:	EN 1760-1, EN ISO 13849-1
Surface material:	polyurethane, black
Protection class:	IP 65 to EN 60529
Ambient temperature:	0 °C 60 °C
Mounting height:	14 mm
Weight:	17 kg/m ²
Actuating force:	150 N with round body ø 80 mm
Cable:	SMS 4: 4 x 0.34 mm ²
	SMS 5: 2 pcs. 2 x 0.34 mm ²
Cable length:	6 m
Response time:	≤25 ms
Mechanical life:	> 1.5 million operations
Permissible load:	2000 N / 80 mm ø
Inactive edge:	≤ 10 mm

module

up to d

up to 3 1.0 x 10⁻⁷ / h

request.

up to 2

20 years

EN ISO 13849-1

In combination with SRB 301 HC/R

or SRB 301 HC/T safety monitoring

Applicable for applications with up to max. 52,000 switching cycles / year and max. 60 % contact load. Diverging applications upon



Legend:

A = LengthB = Width

(Dimensions according to ordering index)

Ramp rail SMS 4-RS-3000



SMS 4-BS-3000 fixing rail

3 Mounting

3.1 General information

2.6 Safety classification

Standards:

PFH-value:

Service life:

Control category

PI

SIL:

The mounting surface imperatively must be plane, clean and dry. Safety mats must not be glued. All cables must be protected against damages (crushing, shearing, etc.).

Position and align the safety mat at the desired position, the base plate facing down.



The safety mats must not be bend or buckled.



When multiple safety mats are arranged adjacently, their butts must be joined. The safety mats then must be wired (refer to chapter "Electrical connection").

3.2 Dimensions All measurements in mm.



Corner section SMS 4-EV





Operating instructions Safety mats

3.3 Mounting SMS 4

When the cable is laid in the ramp or fixing rail duct, crushing must be excluded. To use the corner section, the ramp rail of each corner section must be shortened by 20 mm.



Insert the corner section in the cable area in such manner that the cable is led into the cable duct (figure 1). Then drill and fix them to the floor by means of 6 mm dowels and appropriate screws.





Slide the ramp rails against the side of the mat and insert them in the guide pin of the corner section (fig. 2). Mark the fixing points on the rail along the marking nut and drill 10 mm for the provided plugs.



Fix the rails to the floor by means of 6 mm dowels and appropriate screws (approx. every 60 cm) and seal the screw holes by means of the plugs (fig. 3).





Slide the other corner sections against the side of the mat and insert the guide pin into the rail socket (fig. 4). Then drill and fix them to the floor by means of 6 mm dowels and appropriate screws.



(Fig. 4)

The mounting is terminated by fixing the SMS 4-BS-3000 fixing rail on the machine side. Fix the cable rail to the floor by means of 6 mm dowels and appropriate screws (approx. every 60 cm). If possible, provide for a cable output on the side.(Fig. 5)



Then realise the electrical connection of the safety mats (refer to chapter Electrical connection).

3.4 Mounting SMS 5

Position and align the safety mat at the desired position. Secure the safety mat on all sides against sliding and movement by means of appropriate screws and dowels (fig. 6).



(Fig. 6)

Adjacent fitting of multiple mats

When multiple safety mats are arranged adjacently, their butts must be joined (fig. 7).



To this end, the moulded ramp rails must be cut accordingly (fig. 8).



Position and align the safety mats at the desired position. The safety mats then must be wired (refer to chapter "Electrical connection"). Secure the safety mat on all sides against sliding and movement by means of appropriate screws and dowels (fig. 9).



Mounting the mats with ramp or fixing rail

The safety mats of the SMS 5 series can also be fixed by means of the SMS 4-RS-3000 and SMS 4-BS-3000 DIN rails. To this end, the moulded ramp rails must be removed and the DIN rails must be fitted as described in chapter 3.3.

3.5 Cable laying

Cable laying on the machine side

- Installing the safety mat directly below the machine body (fig. 10)
- Use of the SMS 4-BS-3000 fixing rail (fig.11)
- Use of an on-site cable duct (fig. 12)



(Fig. 10)



(Fig. 11)



(Fig. 12)



When the SMS 4-BS-3000 aluminium profile is used, the moulded ramp profile must be removed, refer to fig. 8.

Cable laying on the averted machine side

- Installing the safety mat directly on the machine (fig. 13)
- Use of the ramp rail (fig. 14)



(Fig. 13)



(Fig. 14)



When the SMS 4-BS-3000 aluminium profile is used, the moulded ramp profile must be removed, refer to fig. 8.

Cable output

Strip the desired side of the cable output in such manner (fig. 15) to avoid subsequent squeezing or crushing of the cables (fig. 16).





(Fig. 15)

(Fig. 16)

Operating instructions Safety mats

4 Electrical connection



The electrical connection may only be carried out by authorised personnel in a de-energised condition.

The safety mats are connected through the permanently connected four-wire sheathed cable. The individual cables are marked with the digits 1 - 4 (fig. 17). To protect larger surfaces, multiple safety mats can be connected together to build a large surface. Up to 5 safety mats can be connected to a safety-monitoring module. To this end, individual safety mats are wired in series (fig. 18). The maximum loop impedance must be <40 Ω . More information about the connection of the safety mats can be found in the wiring example in appendix as well as in the operating instructions of the SRB 301HC/R or SRB 301HC/T safety monitoring-module.



5 Set-up and maintenance

5.1 Functional testing

The safety function of the safety mat must be tested. The following conditions must be previously checked and met:

- 1. Secure connection of the safety mats and the possible DIN rails to the subsoil
- 2. Fitting and integrity of the power cable

Step onto the safety mat to check whether the output relays of the safety-monitoring module are disabled and stop the hazardous movement of the machine.

5.2 Maintenance

A regular visual inspection and functional test, including the following steps, is recommended:

• Check the secure fixation of the safety mat and the possible DIN rails to the subsoil and check for damages

- Check the cable for damages
- Functional test to chapter 5.1

Damaged or defective components must be replaced.

6 Disassembly and disposal

6.1 Disassembly

The safety mat must be disassembled in de-energised condition only.

6.2 Disposal

The safety mat must be disposed of in an appropriate manner in accordance with the national prescriptions and legislations.

Operating instructions Safety mats

7 Appendix

7.1 Wiring example

The application examples shown are suggestions. They however do not release the user from carefully checking whether the switchgear and its set-up are suitable for the individual application.





B = Reset button

	S SCHMERSA
EC Declaration of conform	nity
Translation of the original declaration of conformity	K.A. Schmersal GmbH Industrielle Sicherheitsschaltsysteme Möddinghofe 30 • 42279 Wuppertal Germany Internet: www.schmersal.com
We hereby certify that the hereafter described s ruction conform to the applicable European Dire	afety components both in its basic design and const actives.
Name of the safety component / type:	SMS 4; SMS 5
Description of the safety component:	Safety mat with safety monitoring module SRB 301HC/R or SRB 301HC/T
Harmonised EC-Directives:	2006/42/EC EC-Machinery Directive
Person authorized for the compilation of the technical documentation:	Ulrich Loss Möddinghofe 30 42279 Wuppertal
Notified body for the prototype test:	TÜV Nord Cert GmbH Langemarckstr.20 45141 Essen ID n°: 0044
EC- test certificate:	44 205 10 555973
Place and date of issue:	Wuppertal, May 18, 2010
	Junal
	Authorised signature Heinz Schmersal Managing Director

The currently valid declaration of conformity can be downloaded from the internet at www.schmersal.net.



K. A. Schmersal GmbH

Industrielle Sicherheitsschaltsysteme Möddinghofe 30, D - 42279 Wuppertal Postfach 24 02 63, D - 42232 Wuppertal

+49 - (0)2 02 - 64 74 - 0 Telefon Telefax +49 - (0)2 02 - 64 74 - 1 00 info@schmersal.com E-Mail: Internet: http://www.schmersal.com