DEUTSCH DT-SERIES CONNECTORS





TURCK's Deutsch DT Series connectors feature a fully encapsulated rugged overmold ensuring longevity in demanding environments where shock, vibration, cold temperature, moisture and oils can affect performance.

Product Highlights

- Solid contacts
- IEC IP67
- TPU connector body

Cable Features

- 18 AWG Conductors
- Cut Through and Abrasion resistant TPEFlexible and Oil Resistant
- Temperature range -40C to 105C
- Sunlight Resistant
- Cold Bend rated to -40C

Female	Male	Application	Female	Male	Extension	End View Pinout
2.570 (65.3) REF	2.523 (64.1) REF	2-wire	DT06-2S-2125-*M	DT04-2P-2125-*M	DT06-2S-2125-*M-DT04-2P	1. WH 2.BK
2,739 (69.6) REF	2.543 (64.6) REF	3-wire	DT06-3S-2145-*M	DT04-3P-2145-*M	DT06-3S-2145-*M-DT04-3P	1. GN 2. BK 3. WH
2.845 [72.3] REF	2.891 [73.4] REF .856 [21.7]	4-wire	DT06-4S-2146-*M	DT04-4P-2146-*M	DT06-45-2146-*M-DT04-4P	1.BK, 3.RD 2.WH 4.GN
3.042 [77.3] REF	3.020 [76.7] REF	6-wire	OT06-652:132-*M	DT04-6P-2132-*M	DT06-65-2132-*M-DT04-6P	1.WH 4.0G 2.RD 5.BK 3.GN 6.BU
3.205 (81.4) REF	3.120 (79.2 REF	8-wire	DT06-8S-2156-*M	DT04-8P-2156-*M	DT06-85-2156-*M-DT04-8P	1.0G 5.WH 2.BU 6.RD 3.WH/BK 7.GN, 4.BK 8.RD/BK
3.460 [87.5] REF	3.773 (95.8) REF	- 12-wire	DT06-12SA-2157-*M	DT04-12PA-2157-*M	DT06-12SA-2157-*M-DT04-12PA	1.0G 7.BU/BK 2.BU 8.BK/WH 3.WH/BK 9.GN 4.RD/BK 10.RD 5.GN/BK 11.WH 6.0G/BK 12.BK



^{*} Length in meters.