

12, 16 and 19-Pin Field Wireable In-line Connectors

- For Use with Custom Wiring & Junction Boxes
- Convert Hard Wiring into Quick Disconnect
- IEC IP65 Protection



Housing Style	Male Part Number	Features	Pinout
CSS .. Non-rotating coupling nut CS ..	CSS 12-0	Nickel plated brass, PG 13.5 cable gland, accepts 5-12 mm cable diameter, accepts up to 12x18 AWG conductor, 125°C, 300 V, 8.0 A, field wireable 12-pin in-line connector, for use with <i>minifast</i> ®, <i>eurofast</i> ® (single input per port) and <i>microfast</i> ® junctions boxes	Male
	CS 12-0	Nickel plated brass, PG 11 cable gland, accepts 4-10 mm cable diameter, accepts up to 12x18 AWG conductor, 125°C, 300 V, 8.0 A, field wireable 12-pin in-line connector, for use with <i>minifast</i> ®, <i>eurofast</i> ® (single input per port) and <i>microfast</i> ® junctions boxes	Male
	CSS 16-0 CS 16-0	Nickel plated brass, PG 13.5 cable gland, accepts 5-12 mm cable diameter, accepts up to 16x18 AWG conductor, 125°C, 150 V, 8.0 A, field wireable 16-pin in-line connector, for use with <i>eurofast</i> ® (isolated power supply) junctions boxes	Male
	CSS 19-0 CS 19-0	Nickel plated brass, PG 13.5 cable gland, accepts 5-12 mm cable diameter, accepts up to 19x18 AWG conductor, 125°C, 150 V, 8.0 A, field wireable 19-pin in-line connector, for use with <i>eurofast</i> ® (two signals per port) junctions boxes	Male
	CSS 125-0 CS 125-0	Nickel plated brass, IAC, accepts 3-10 mm cable diameter, accepts up to 12x18 AWG conductor, 125°C, 150 V, 8.0 A, field wireable 12-pin in-line connector	Male