

- On-machine Compact fieldbus I/O block
- EtherNet/IP™, Modbus® TCP, or PROFINET slave
- Integrated Ethernet Switch
- 10 Mbps / 100 Mbps supported
- Two 4-pole M12, D-coded, connectors for fieldbus connection
- 2 rotary switches for node address
- IP67, IP69K
- M12 I/O connectors
- LEDs indicating status and diagnostics
- Electronics galvanically separated from the field level via optocouplers
- 8 analog inputs for current or voltage
- 0/4...20 mA or -10/0...+10 VDC (selectable per channel)

Type designation	BLCEN-8M12LT-4AI-VI-4AI-VI
Ident-No.	6811458
Ident-No (TUSA)	F6811458
<hr/>	
Nominal system voltage	24 VDC
System power supply	Via auxiliary power
Voltage supply connection	2 x M12, 5-pin
Admissible range Vi	11...30VDC
Nominal current Vi	149 mA
Max. current Vi	2 A
<hr/>	
Fieldbus transmission rate	10/100 Mbps
Adjustment transmission rate	Automatic detection
Fieldbus address range	1...92 0 (192.168.1.254) 93 (BootP) 94 (DHCP) 95 (PGM) 96 (PGM-DHCP) *Recommended for PROFINET 97...98 (manufacturer specific)
Fieldbus addressing	2 decimally coded rotary switches
Fieldbus connection technology	2 x M12 4-pole, D-coded
Protocol detection	automatic
Web server	Integrated
Service Interface	Ethernet
Vendor ID	48
Product type	12
Product code	11458
<hr/>	
Modbus TCP	
Addressing	Static IP, BOOTP, DHCP
Supported function codes	FC1, FC2, FC3, FC4, FC5, FC6, FC15, FC16, FC23
Number of TCP connections	6
Input Data Size	max. 10 register
Input register start address	0 (0x0000 hex)
<hr/>	
EtherNet/IP™	
Addressing	acc. to EtherNet/IP™ specification
Device Level Ring (DLR)	supported
Number of CIP connections	6
Input Assembly Instance	103
Input Data Size	11 INT
Output Assembly Instance	104
Output Data Size	1 INT
Configuration Assembly Instance	106
Configuration Size	0
Comm Format	Data - INT

PROFINET

Addressing	DCP
Conformance class	B (RT)
MinCycleTime	1 ms
Diagnostics	acc. to PROFINET alarm handling
Topology detection	supported
Automatic addressing	supported
Media Redundancy Protocol (MRP)	supported
Input Data Size	max. 16 BYTE


Analog inputs

Operating modes	0/4 ... 20 mA or -10/0 ... 10 VDC
Type of input diagnostics	Channel diagnostics
Sensor supply	24 VDC, 1 amp max.
Input resistance	Current: < 0.125 K Ω , Voltage: < 98.5 K Ω
Maximum limiting frequency analog	< 20 Hz
Basic fault limit at 23 °C	< 0.3 %
Repeatability	< 0.05 %
Temperature coefficient	< 300 ppm / °C of full scale
Resolution	16 bit
Measuring principle	Sigma Delta
Measurement display	16 bit signed integer 12 bit full range left-justified

Dimensions

Mounting	168 x 71 x 32.5 mm
Weight	2 x 5.4 mm diameter holes, 1.7 Nm torque
Housing material	620 \pm 20 g
Housing color	Glass-filled nylon, nickel plated brass connectors
Window material	Black
Material screw	Lexan
Material label	Nickel-plated brass
Ground tab material	Polyester with polycarbonate overlay
Protection class	Nickel plated brass
Operating temperature	IP67
Storage temperature	IP69K
Relative humidity	-40...+70 °C
Vibration test	-40...+85 °C
Extended vibration resistance	15 to 95% (non-condensing)
- up to 20 g (at 10 up to 150 Hz)	according to IEC 61131-2
Shock test	For mounting on base plate or machinery
Electro-magnetic compatibility	according to IEC 61131-2
MTTF	according to IEC 61131-2
MTTF note	110 years
Approvals and certificates	acc. to SN 29500 (Ed. 99) 20 °C CE, cULus, Class I Div.2



Pinning and wiring diagram



Ethernet

Fieldbus cable (IP67 example): RSSD RSSD 441-2M ID number U-02482 or RSSD-RSSD-441-2M/S2174 ID number 6914218


Pin Assignment (M12, D-code)




Slot 1: Analog Inputs

Extension cable (example): RK 4.5T-2-RS 4.5T/S653 ident-no. U2187-09 or RKC4.5T-2-RSC4.5T/TEL ident-no. 6625212


Pin Assignment




2-wire Technology (Current)




2-wire Technology (Voltage)




3-wire Technology




4-wire Technology





4-wire Technology (External Power)






Slot 2: Analog Inputs
See slot 1

Pin Assignment



Auxiliary Power
Extension cable (example): RKC 4.4T-2-RSC 4.4T ident-no. U5264 or RKC4.4T-2-RSC4.4T/TEL ident-no. 6625208

Pin Assignment



Station LED status

LED	Color	Status	Description
IOs		OFF	No power
	RED	ON	Low power or station error
	RED	FLASHING (1 Hz)	I/O module configuration error
	RED	FLASHING (4 Hz)	No I/O module bus communication
	GREEN	ON	Station ok
	GREEN	FLASHING	Force mode active
BUS		OFF	Power Off
	GREEN	ON	Connected to Master
	GREEN	FLASHING	Ready
	GREEN	FLASHING 3x (1Hz)	ARGEE Running
	RED	ON	Error
	RED	FLASHING	WINK
	YELLOW	ON	DHCP/BOOTP Search
LNK/ACT		OFF	No Link
	GREEN	ON	Link
	GREEN	FLASHING	Traffic
	YELLOW	ON	100 Mbit Linked

I/O LED status slot 1

LED	Color	Status	Description
D1 *		OFF	No diagnostics active
	RED	ON	Station error/ module bus communication failure
	RED	FLASHING (0.5Hz)	Diagnostics active (Slot 1)
AI channels 1 ₀ ...1 ₃		OFF	Not active
	GREEN	ON	Active
	GREEN	FLASHING (0.5 Hz)	Underflow in measuring range
	GREEN	FLASHING (4 Hz)	Overflow in measuring range

* D1 LED also indicates gateway diagnostics

I/O LED status slot 2

LED	Color	Status	Description
D2 *		OFF	No diagnostics active
	RED	ON	Station error/ module bus communication failure
	RED	FLASHING (0.5Hz)	Diagnostics active (Slot 2)
AI channels 2 ₀ ...2 ₃		OFF	Not active
	GREEN	ON	Active
	GREEN	FLASHING (0.5 Hz)	Underflow in measuring range
	GREEN	FLASHING (4 Hz)	Overflow in measuring range

* D2 LED also indicates gateway diagnostics

Process Data Mapping of Each Protocol

EtherNet/IP™ I/O & Diagnostics Data Mapping

INPUT	BYTE	Bit 7	Bit 6	Bit 5	Bit 4	Bit 3	Bit 2	Bit 1	Bit 0
AI 1 ₀	0	AI 1 ₀ LSB							
	1	AI 1 ₀ MSB							
AI 1 ₁	2	AI 1 ₁ LSB							
	3	AI 1 ₁ MSB							
AI 1 ₂	4	AI 1 ₂ LSB							
	5	AI 1 ₂ MSB							
AI 1 ₃	6	AI 1 ₃ LSB							
	7	AI 1 ₃ MSB							
AI 2 ₀	8	AI 2 ₀ LSB							
	9	AI 2 ₀ MSB							
AI 2 ₁	10	AI 2 ₁ LSB							
	11	AI 2 ₁ MSB							
AI 2 ₂	12	AI 2 ₂ LSB							
	13	AI 2 ₂ MSB							
AI 2 ₃	14	AI 2 ₃ LSB							
	15	AI 2 ₃ MSB							
Diagnostics	16	Module number reporting diagnostic data							
	17	Replace Station	-	Diagnostics Active	-	-	-	-	-
Slot X* (ref. Byte 16)	18	-	-	-	-	-	-	Open Circuit AI X ₀	Range Error AI X ₀
	19	-	-	-	-	-	-	Open Circuit AI X ₁	Range Error AI X ₁
	20	-	-	-	-	-	-	Open Circuit AI X ₂	Range Error AI X ₂
	21	-	-	-	-	-	-	Open Circuit AI X ₃	Range Error AI X ₃

* The scheduled diagnostic information changes every 125 ms between Slot 1 and Slot 2, if both slots send active diagnostics.

Legend:

AI	Analog Input	OC	Open Circuit
CFG	Configuration Error	S1	Slot 1
COM	Communication Failure	S2	Slot 2
DIA	Diagnostics Active	SC	Short Circuit / Overcurrent
FCE	Force Mode Active	VI	VI Voltage
MR	Measurement Value Range Error	VO	VO Voltage

Modbus® TCP Register Mapping

	REG	Bit 15	Bit 14	Bit 13	Bit 12	Bit 11	Bit 10	Bit 9	Bit 8	Bit 7	Bit 6	Bit 5	Bit 4	Bit 3	Bit 2	Bit 1	Bit 0
Inputs (RO)	0x0000	AI 1 ₀															
	0x0001	AI 1 ₁															
	0x0002	AI 1 ₂															
	0x0003	AI 1 ₃															
	0x0004	AI 2 ₀															
	0x0005	AI 2 ₁															
	0x0006	AI 2 ₂															
Status (RO)	0x0008	-	FCE	-	-	CFG	COM	VI low	-	VO low	-	-	-	-	-	-	DIA
Diag. (RO)	0x0009	-	-	-	-	-	-	-	-	-	-	-	-	-	-	S2 DIA	S1 DIA
I/O Diag. (RO)	0xA000	-	-	-	-	-	-	OCAI 1 ₁	MRAI 1 ₁	-	-	-	-	-	-	OCAI 1 ₀	MRAI 1 ₀
	0xA001	-	-	-	-	-	-	OCAI 1 ₃	MRAI 1 ₃	-	-	-	-	-	-	OCAI 1 ₂	MRAI 1 ₂
	0xA002	-	-	-	-	-	-	OCAI 2 ₁	MRAI 2 ₁	-	-	-	-	-	-	OCAI 2 ₀	MRAI 2 ₀
	0xA003	-	-	-	-	-	-	OCAI 2 ₃	MRAI 2 ₃	-	-	-	-	-	-	OCAI 2 ₂	MRAI 2 ₂


PROFINET® Process Data

	BYTE	Bit 7	Bit 6	Bit 5	Bit 4	Bit 3	Bit 2	Bit 1	Bit 0
Inputs	0	AI 1 ₀ LSB							

BL compact™ multiprotocol fieldbus station for Industrial Ethernet
8 Analog Inputs for Current or Voltage
BLCEN-8M12LT-4AI-VI-4AI-VI

1	AI 1 ₀ MSB
2	AI 1, LSB
3	AI 1, MSB
4	AI 1 ₂ LSB
5	AI 1 ₂ MSB
6	AI 1 ₃ LSB
7	AI 1 ₃ MSB
8	AI 2 ₀ LSB
9	AI 2 ₀ MSB
10	AI 2, LSB
11	AI 2, MSB
12	AI 2 ₂ LSB
13	AI 2 ₂ MSB
14	AI 2, LSB
15	AI 2 ₂ MSB

Accessories

Type code	Ident-No.	Description	
LOCK-EURO-C	A0885	Locking guard for straight eurofast™ C-body connectors (RKC, RKCV, RSC, RSCV) in a Class I, Division 2 installations	
LOCK-EURO-C (10/BAG)	A0886	Locking guard for straight eurofast™ C-body connectors (RKC, RKCV, RSC, RSCV) in a Class I, Division 2 installations	