



CONNECTIVITY CAPABILITIES



Welcome to the **TURCK** Connectivity Capabilities brochure. **TURCK** is a worldwide leader in industrial automation with the industry's broadest line of connectors, cables and cordset products. **TURCK** connectivity products connect the sensing devices to higher-level control components - and much more!

This brochure contains our standard connectivity products from M5 to M40 connectors, network media, cable and wiring examples, and a sampling of custom solutions we've done for customers in the past.

TURCK



How would **you** like to connect?

**ENDLESS POSSIBILITIES,
ONE MANUFACTURER.**

M5 - *pentafast*®

M8 - *picofast*®

M12 - *eurofast*®

1/2" - *microfast*®

7/8", 1", 1-1/8" - *minifast*®

M16 - *versafast*®

M23, M27 - *multifast*®

M16, M23, M40 - *powerfast*®

Network Media

Custom Solutions

Process Automation

See what we've done...

**...challenge us to
something new.**



1

M5 Thread

- 3 and 4-pin
- 125 V, 1 A

2


PUR *flexlife*®

- Cut/abrasion immune
- Over 2 million cycles

3

M5 Thread

- 3 and 4-pin
- 125 V, 1 A



M5 - pentafast®

M5 - pentafast®

M8 Thread

- 3, 4, and 6-pin
- 125 V, 2 A to 125 V, 4 A

PUR *flexlife*® -20

- Cut/abrasion immune
- Over 20 million cycles

M8 Thread

- 3, 4, and 6-pin
- 125 V, 2 A to 125 V, 4 A

7

M8 Snap Lock (Locking Sleeve)

- 3, 4, and 6-pin
- 125 V, 2 A to 125 V, 4 A



8

PUR Shielded

- EMI/RFI protection
- Cut/abrasion immune



9

M8 Snap Lock with LEDs

- 10 VAC/20 VDC, 2 and 4 A
- PNP and NPN Signals



M8 - picofast®

M8 - picofast®

M8 Connector to Splitter

- 125 V, 4 A

Compact M8 Splitter with Mounting Hole

- Simple connector or connector with extension cable

M8 Connector Branches from Splitter

- 125 V, 4 A

13

M12 Thread

- Accepts 20, 22 and 24 AWG wires
- 2-6, 10 and 12-pin
- 60 VAC/75 VDC, 2 A to 250 VAC/300 VDC, 4 A



M12 - eurofast®

14

PVC *flexlife*®

- Over 2 million cycles



15

M12 Thread

- Accepts 20 and 22 AWG wires
- 3 and 4-pin
- 250 V, 4 A



M12 - eurofast®



M12 Thread

- Accepts 18, 20, 22 and 24 AWG wires
- 2, 6, 8, 10 and 12-pin
- 60 VAC/75 VDC, 2 A to 250 V, 4 A



PUR-Shield and Double Jacket

- Braided shield
- Cut/abrasion immune



M12 Thread

- Accepts 18, 20, 22 and 24 AWG wires
- 3-6, 8, 10 and 12-pin
- 60 VAC/75 VAC, 2 A to 250 V, 4 A

19

M12 Armored

- Shield tied to coupling nut
- 3, 4 and 5-pin
- 250 V, 4 A

20

PVC Armor

- Tray rated

21

M12 Armored

- Shield tied to coupling nut
- 3, 4 and 5-pin
- 250 V, 4 A



M12 - eurofast®

M12 - eurofast®

M12 with LEDs

- 3, 4 and 5-pin
- 10-30 V, 4 A
- PNP and NPN signals

**Irradiated PVC**

- Weld flash immune
- High temperature immune

**M12 316
Stainless Steel**

- Hex coupling nut
- 2-6, 10 and 12-pin
- 60 VAC/75 VAC,
2 A to 250 VDC,
4 A



25

M12 Reverse Key (B-Code)

- 3 and 5-pin
- 250 V, 4 A



M12 - eurofast®

26

PVC Grey *flexlife*®

- Commonly used with reverse key (B-code) connectors
- Over 2 million cycles



27

M12 Reverse Key (B-Code)

- 3 and 5-pin
- 250 V, 4 A



M12 - eurofast®



M12 Incremental Encoder Connector

- 3 indicator LEDs
- 8-pin
- 5-30 VDC

PVC Shielded

- RFI/EMI protection
- Differential and single ended mode applications



M12 Incremental Encoder Connector

- Shield tied to coupling nut
- RFI/EMI protection
- 8-pin
- 60 VAC/75 VDC, 2 A



31

1/2" Thread

- Accepts 20 and 22 AWG wires
- 3, 4, 5 and 6-pin
- 250 V, 4 A



1/2" - microfast®

32

PUR Coil Cord

- For repetitive motion



33

1/2" Thread

- Accepts 18 AWG wires
- 2, 3 and 5-pin
- 250 V, 4 A



1/2" - microfast®

**7/8" Thread**

- Accepts 18 AWG wires
- 2 through 6-pin
- 300 V, 9 A

TPE weldlife®

- STOW rating
- Weld flash immune

**7/8" Thread**

- Accepts 16 AWG wires
- 2 through 6-pin
- 600 V, 9 A

37

7/8" Armored

- Shield tied to coupling nut
- 2 through 6-pin
- 600 V, 9 A



7/8" - minifast®

38

PVC Armor

- Tray rated

39

7/8" Armored

- Shield tied to coupling nut
- 2 through 6-pin
- 600 V, 9 A

7/8" - minifast®

40



Wash Down Connector

- Wash down mold material and contact holders
- Standard or with shielding

41



Wash Down Cable

- Polypropylene cable jacket
- Flame retardant

42



Wash Down Connector

- Wash down mold material and contact holders
- Standard or with shielding

43

1" Thread

- Accepts 16 AWG wires
- 6, 7 and 8-pin
- 600 VAC/VDC, 8 A



1" - minifast®

44

CPE Rubber

- SOOW rating
- Weld flash immune
- Flame immune



45

1-1/8" Thread

- Accepts 16 AWG wires
- 9, 10 and 12-pin
- 600 VAC/VDC, 7 A



1-1/8" - minifast®

M16 Thread


- Accepts 18, 22, 24 and 26 AWG wires
- 5-8, 12, 14 and 19-pin
- 30 V, 3 A to 125 V, 8 A

TPE *flexlife*®

- Over 2 million cycles

M16 Thread 48

- Accepts 18, 22, 24 and 26 AWG wires
- 5-8, 12, 14 and 19-pin
- 30 V, 3 A to 125 V, 8 A



49

M23 Thread

- Shield tied to coupling nut
- 7, 12 and 19-pin
- 150 V, 9 A to 300 V, 20 A



M23 - multifast®

50

PVC Shielded

- EMI/RFI protection
- Tray rated



51

M23 Thread

- Shield tied to coupling nut
- 7, 12 and 19-pin
- 150 V, 9 A to 300 V, 20 A



M23 - multifast®

M23 Thread

- 12, 16 and 19-pin
- 150 V, 9 A to 300 V, 20 A



PVC NAMUR

- Tray rated



M23 Thread Push-Pull Connection

- 12 and 19-pin
- 150 V, 9 A to 300 V, 6 A



55

M27 Thread

- 26 and 28-pin
- 150 V, 5 A



M27 - multifast®

56

PVC Multiconductor

- 25 and 27-wire



57

M27 Thread

- 26 and 28-pin
- 150 V, 5 A



M27 - multifast®

**M16 Thread - Power**

- Accepts 12 and 14 AWG wires
- Shielding available
- 2, 3 and 4-pin
- 600 V, 15-18 A

PVC - High Current

- Tray rated -
exposed run
- Shielding available
- Up to 18 A

**M16 Thread - Power 60**

- Accepts 12 and 14 AWG wires
- Shielding available
- 2, 3 and 4-pin
- 600 V, 15-18 A

61

M23 Thread - Power

- Accepts 12, 14 and 18 AWG wires
- 3-key
- Shielding available
- 6 and 8-pin
- 600 V, 30 A



M23 - powerfast®

62

PVC - High Current

- Tray rated - exposed run
- Shielding available
- Up to 30 A



63

M23 Thread - Power

- Accepts 12, 14 and 18 AWG wires
- 3-key
- Shielding available
- 6 and 8-pin
- 600 V, 30 A



M23 - powerfast®

64

M40 Thread - Power

- Accepts 8 AWG wires
- 4 and 8-pole (shielded)
- 600 V, 40 A



65

PVC - High Current

- Shielding available
- Up to 40 A



66

M40 Thread - Power

- Accepts 8 AWG wires
- 4 and 8-pole (shielded)
- 600 V, 40 A



67

PROFIBUS®-DP D-Sub Connector


- Integrated terminating switch
- Right angle and master connection option
- 250 V, 5 A



68

PROFIBUS®-DP Cable

- Meets requirements of EN50170-2-2:1996 for communications up to 12 Mbaud
- PVC, PUR and TPU cable jackets
- Braided over foil shield
- Aluminium armor option



69

M12 PROFIBUS®-DP Connectors

- 5-pin
- 250 V, 4 A
- Standard reverse key
- Shielded-tied to coupling nut





5-pin Diagnostic Connector for DeviceNet™

- Nylon housing
- 250 V, 12 A

DeviceNet™ Cable, 5-wire

- Meets ODVA requirements of type I (thin), type II (thick), and type III (mid)
- Braided and/or foil shield
- PVC, PUR, TPE cable jacket

M12 Thread DeviceNet™

- 5-pin
- 250 V, 4 A



73

RJ45 Connector

- For Ethernet connections
- 42 V, 1.5 A
- Shielded and economy version options



74

Ethernet Cable, 8-wire

- Meets TIA/EIA 568-B, 2 category 5e cable for 10 and 100 Base-T Ethernet
- PVC jacket, braided and/or foil shield
- Armored option



75

M12 Bulkhead Connector

- 8-pin
- 60 V, 2 A





TURCK Sensor

- Connected to commercial style connector

Jacket Options for any Environment



Commercial Style Connector

- Connected to TURCK Sensor

TURCK Sensor with *weldguard*® Protective Face

- Resists weld slag
- Integral extension cable with silicone tubing



Protective Silicone Tubing with Heat Shrink to Cable

- Protects from weld slag



M8 Thread

- Connected to **TURCK** sensor
- Multiple connector styles available





Valve Connectors

- Use 9.4 to 18 mm cable
- M8 to 7/8" connector extensions
- Field wireable styles
- Custom print labels

Private Label

TOP BRAKE VALVE V458
1163 0906U

Insulated Ferrules

- Multiple color and AWG size options
- Provides cleaner connection
- Private labeling on wires



85

D-Sub Molded or Assembled Connectors

- Connected to **TURCK** connector
- 9, 15 and 25-pin



Custom Solutions

86

Jacket Diameters from
3.5 mm to 18.5 mm

87

M23 Connector

- Connected to D-Sub Connector



Custom Solutions

Approvals

- FM, UL, CSA approvals available



Heat Shrinking of Wires



Ring Terminal and Ferrules

- Any combination



91

TURCK Sensor

- Connected to automotive style connector



Custom Solutions

92

Wire Gauge Ranges from 8 to 26

93

Automotive Style Connector

- Stabilizing pin
- Connected to TURCK sensor



Custom Solutions

TURCK Sensor

- Connected to automotive style connector

**2 to 27 Conductors,
Braided or Foil Shields****Automotive Style
Connector**

- Connected to
TURCK sensor



97

TURCK Sensor

- Custom pad printing and color
- Connected to automotive style connector



Custom Solutions

98

Spoiled Cable in 30, 100 or 200 Meter Lengths



99

Automotive Style Connector

- Connected to
TURCK sensor

Custom Solutions

M12 Receptacles

- **TURCK** offers over 40 styles of M12 receptacles
- Front mount, rear mount, solder cups, PCB mount and more
- Connected to commercial style connector



Ferrite Tubing



Commercial Style Connector

- Connected to **TURCK** M12 receptacle



103

Closure Cap

- Nickel plated brass or stainless steel
- For cordsets or receptacles
- With or without lanyards

104

Closure Cap Lanyards

105

Fork Terminals

- Connected to **TURCK** connector
- Private labeling on wires

Custom Solutions

Custom Solutions

Nylon Coupling Nut

- **TURCK** offers nickel plated brass, nylon and 316 stainless steel coupling nut options



TURCK Can Process Your Cable



USB Connector

- Connected to **TURCK** connector



109

**Multiple Connector
Mold Colors**



Custom Solutions

110

Custom Cable Colors



111

Pigtail Option



Custom Solutions

M12 Connector to Splitter

- Choose from integral connector or connector with extension cable



3 Branch Molded Splitter

- 2 and 4 branch options
- LED options
- Standard, series or parallel wiring
- Custom hot stamp printing
- Coil Cord



Multiple Thread Types and Mold Colors

- 1/2" and M12 threads
- M12 thread reverse key (B-code)



115

Molded on Amp Connector

- Connected to **TURCK** connector



Custom Solutions

116

UL Recognized and CSA Approvals

117

PVC Plug Body and Contact Holders

- Excellent resistance to wash down chemicals
- Available in numerous connector styles




Custom Solutions



Right Angle Connector

- Right angles available in all thread types



2 Branch Molded Splitter

- 3 and 4 branch options
- LED options
- Standard, series or parallel wiring



Molded on Automotive Style Connectors

- Multiple cable jacket colors
- Connected to TURCK splitter

121

Weld Protection

- Weld slag resistant silicone tubing
- Teflon coated coupling nut

122

Silicone Tubing

- Excellent weld slag resistance

123

Weld Protection

- Weld slag resistant silicone tubing
- TPE mold body
- Teflon coated coupling nut




Custom Solutions

Custom Solutions



Expandable Fiberglass Sleeving

- “Heat shrink” like fit
- Abrasion, moisture, cut-through and chemical resistance
- -55 °C to +200 °C



Expandable Fiberglass Sleeving

- “Heat shrink” like fit
- Abrasion, moisture, cut-through and chemical resistance
- -55 °C to +200 °C



AC Wall Plug

- Connected to TURCK connector

127

Stainless Steel Coupling Nut

- Nickel plated brass and nylon coupling nuts available



128


Over 400 Different Cable Styles



129

Insulated Spaid Terminals

- Connected to **TURCK** connector



Custom Solutions

Custom Solutions

130



Spaid Terminals on Private Labeled Wires

- Connected to M16 connector

131



Cable Gland

132



M16 Thread

- Available in 5, 6, 7, 8, 12, 14 and 19-pin
- Spaid terminals connected on opposite end

133

Hybrid Cordsets

- Combine multiple thread sizes in one cordset
- Our project engineers will assist you



Custom Solutions

134

Mix and Match

- M23 on one end, M16 thread on the other end

135

Hybrid Cordsets

- Combine multiple thread sizes in one cordset
- Our project engineers will assist you



Custom Solutions

136

**Commercial Style
Connector**

137

**Multiple Cable
Branches**

- Two cables from commercial style connector to two different receptacle types



138

**Combine Multiple
Receptacles**

- Numerous receptacle styles in all thread sizes

139

M16 Connectors to Drop Tee



140

Drop Tee

141

Commercial Style Connector



Custom Solutions

Custom Solutions



Overmolded Receptacle

Process Connectivity


- 2-wire analog or HART control circuits
- Additional analog or discrete control circuits
- NAMUR circuits
- *extremelife*® marine cable



M23 Home Run Connector with Set Screw Locks

- For Class I, Division 2 hazardous locations
- Render a connection not normally arcing





CONNECT IT YOUR WAY

Our experienced
engineers are ready
to assist you



1-800-544-7769

act Walker EMD • Toll-free: (800) 876-4444 • Tel: (203) 426-7700 • Fax: (203) 426-



USA

TURCK Inc.
3000 Campus Drive
Minneapolis, MN 55441
Phone: (763) 553-7300
Fax: (763) 553-0708
Application Support:
1-800-544-7769
E-mail: turckusa@turck.com
www.turck.us



MEXICO

TURCK MEXICO S. DE R.L. DE C.V.
Carr. Saltillo-Zacatecas km 4.5 s/n
Parque Industrial "La Angostura"
Saltillo, COAH. C.P. 25070
Mexico
Phone: +52 (844) 411-6650/46
Fax: +52 (844) 482-6926
Local Toll Free: 01-800-01-88725
E-mail: ventasmexico@turck.com



CANADA

CHARTWELL ELECTRONICS, INC.
140 Duffield Drive
Markham, Ontario
Canada, L6G 1B5
Phone: (905) 513-7100
Fax: (905) 513-7101
Toll Free: 1-877-513-7769



AUSTRALIA

TURCK Australia Pty. Ltd.
Unit 5, 6-7 Gilda Court
Mulgrave, Victoria 3170
Australia
Phone: (+61) 3 9560 9006
Fax: (+61) 3 9560 1620
Local Toll Free: 1300 132566
E-mail: turckaustralia@turck.com



GERMANY

WORLD HEADQUARTERS
Hans TURCK GmbH & Co. KG
Witzlebenstrasse 7
D-45472 Muelheim an der Ruhr
Federal Republic of Germany
Phone: (+49) 208-49 52-0
Fax: (+49) 208-49 52 264

www-turck-com

....**Sense It!**....**Connect It!**....**Bus It!**....**Solve It!**