

Inductive Sensors



Housing Style	Part Number	ID Number	Features	Sensing Range (mm)	Output
30 mm - Embeddable, minifast® Right Angle Connection 	Bi10-G30-AZ3X-B1431	T4372600		10	2-Wire AC/DC
30 mm - Embeddable, minifast Connection, PTFE Coated 	Bi10-GT30-ADZ30X2-B1131/S34	T4256200	<i>WFI</i>	10	2-Wire AC/DC Short-Circuit Protected
	Bi10-GT30-ADZ30X2-B1131	T4256290		10	
	Bi10-GT30-ADZ30X2-B1131/S34/S1589	T4255280	<i>weldguard®, WFI</i>	10	
	Bi10U-GT30-ADZ30X2-B1131	M4281622	<i>Uprox</i>	10	
30 mm - Nonembeddable, minifast Connection 	Ni15-G30-AN6X-B1141	T4695500		15	3-Wire DC NPN
	Ni15-G30-AP6X-B1141	T4696600		15	3-Wire DC PNP
30 mm - Nonembeddable, minifast Connection 	Ni15-G30-AZ3X-B1131	T4372300		15	2-Wire AC/DC
	Ni20-G30-ADZ30X2-B1131	T4205405		20	2-Wire AC/DC Short-Circuit Protected
	Ni20U-G30-ADZ30X2-B1131	M4281812	<i>Uprox</i>	20	

For detailed sensor specifications see Section M.
 Normally Closed versions available upon request, consult factory.