


#### NOTES:

1. "\*" DESIGNATES CABLE LENGTH IN METERS. CONTACT TURCK TO ORDER SPECIFIC LENGTHS.
2. BOX HEIGHT IS 34.5 [1.36] NOMINAL.
3. CLEARANCE HOLE FOR 1/4-20 MOUNTING SCREWS (NOT INCLUDED).

#### SPECIFICATIONS

CABLE JACKET/COLOR	PVC/BLACK
NUMBER OF CONDUCTORS [AWG]	6x18 AWG
HOUSING MATERIAL	ALUMINUM ALLOY
HOUSING FINISH/COLOR	EPOXY/BLACK
CONTACT CARRIERS	TPU
CONTACTS	BRASS/GOLD
OPERATING VOLTAGE	250 VAC, 300 VDC
OPERATING CURRENT	4.0 AMPS/PORT, 9 AMPS TOTAL
PROTECTION CLASS to DIN 40050	IP 67 – ONLY WHEN ALL RECEPTACLES ARE COVERED WITH PLUGS OR CONNECTED
OPERATING TEMPERATURE	-40°C to +105°C (-40°F to +221°F)




#### CONNECTORS J1-J4



FUNCTION	OUTPUT WIRE COLOR
(+) VDC	WHITE
(-) COMMON	GREEN
J1	RED
J2	ORANGE
J3	BLACK
J4	BLUE

CABLE LENGTH	TOLERANCE
ALL LENGTHS	+ 4% (OR 50mm) OF LENGTH - 0% (OR 0mm) OF LENGTH WHICHEVER IS GREATER
STRIP LENGTH	TOLERANCE
0-7mm	±0.5mm
8-29mm	±1.0mm
30-49mm	±2.0mm
50-69mm	±3.0mm
70-100mm	±4.0mm
OVER 100mm	±5.0mm

SOURCE DRAWING - FOR REFERENCE ONLY

RELATED DOCUMENTS  1.  2.  3.  4.	3RD ANGLE PROJECTION		THIS DRAWING IS CONFIDENTIAL AND THE PROPERTY OF TURCK INC. USE OF THIS DOCUMENT WITHOUT WRITTEN PERMISSION IS PROHIBITED.	<div><b>TURCK inc</b></div> <div><i>High Technology Sensors and Automation Controls</i></div> <div>3000 CAMPUS DRIVE MINNEAPOLIS, MN 55441 1-800-544-7769 (763) 553-7300 (763) 553-0708 fax turck.com</div>			
MATERIAL	ALL DIMENSIONS DISPLAYED ON THIS DRAWING ARE FOR REFERENCE ONLY		DRFT	IK	DATE	01/15/97	DESCRIPTION  4 RKF 40-*M
			APVD		SCALE	1=1.5	
FINISH			CONTACT TURCK FOR MORE INFORMATION		UNIT OF MEASUREMENT		
	MILLIMETER [ INCH ]						
			DO NOT SCALE THIS DRAWING			FILE: 777001282	SHEET 1 OF 1

G	UPDATE CABLE DIAMETER	KMY	04/16/12	37382
REV	DESCRIPTION	BY	DATE	ECO NO.