


SPECIFICATIONS				
CABLE JACKET/COLOR	PVC/BLACK			
NUMBER OF CONDUCTORS [AWG]	8x18 AWG			
HOUSING MATERIAL	ALUMINUM ALLOY			
HOUSING FINISH/COLOR	EPOXY/BLACK			
CONTACT CARRIERS	TPU			
CONTACTS MATERIAL/PLATING	BRASS/GOLD			
OPERATING VOLTAGE	250 VAC / 300 VDC			
OPERATING CURRENT	4 A PER PORT, 9.0 A TOTAL			
PROTECTION CLASS to DIN 40050	IP 67 - ONLY WHEN ALL RECEPTACLES ARE			
	COVERED WITH PLUGS OR CONNECTED			
OPERATING TEMPERATURE	-40°C to 90°C (-40°F to 194°F)			



CONNECTORS J1-J6		
2	<u>3</u>	
1 = GROUND 2 = LOAD (L2) 3 = COMMON (L	1)	
mini iast,		

CABLE LENGTH	TOLERANCE		
ALL LENGTHS	+ 4% (OR 50mm) OF LENGTH - 0% (OR 0mm) OF LENGTH WHICHEVER IS GREATER		
STRIP LENGTH	TOLERANCE		
0-7mm	±0.5mm		
8-29mm	±1.0mm		
30-49mm	±2.0mm		
50-69mm	±3.0mm		
70-100mm	±4.0mm		
OVER 100mm	±5.0mm		

FUNCTION	OUTPUT WIRE COLOR		
COMMON (L1)	WHITE		
GROUND	GREEN		
J1(L2)	RED		
J2(L2)	ORANGE		
J3(L2)	BLACK		
J4(L2)	BLUE		
J5(L2)	YELLOW		
J6(L2)	BROWN		

SOURCE DRAWING - FOR REFERENCE ONLY

NOTES:

- 1. "*" DESIGNATES CABLE LENGTH IN METERS. CONTACT TURCK TO ORDER SPECIFIC LENGTHS.
- 2. BOX HEIGHT IS 1.36 [34.5] NOMINAL.
- 3. CLEARANCE HOLE FOR M4 [#8] MOUNTING SCREWS (2 NOT INCLUDED).

F	UPDATE CABLE DIAMETER	KMY	05/30/12	37625
REV	DESCRIPTION	BY	DATE	ECO NO.

1. 2. 3.	3RD ANGLE PROJECTION	THIS DRAWING IS CONFIDENTIAL AND THE PROPERTY OF TURCK INC. USE OF THIS DOCUMENT WITHOUT WRITTEN PERMISSION IS PROHIBITED.	High Techno		
MATERIAL		DRFT RJP	DATE 6/21/		
	ALL DIMENSIONS DISPLAYED ON THIS	APVD	SCALE $1=2$.		
	DRAWING ARE FOR REFERENCE ONLY	UNIT OF M	EASUREMENT		
FINISH	CONTACT TURCK FOR MORE INFORMATION	MILLIMETER [INCH			
		DO NOT SCALE	THIS DRAWING		

urck iac

echnology Sensors and Automation Controls

3000 CAMPUS DRIVE MINNEAPOLIS, MN 55441 1-800-544-7769 (763) 553-7300 (763) 553-0708 fax turck.com

SHEET 1 OF 1

21/95

=2.0

6 RKF 30-*M

FILE: 777001295

;H]

IDENTIFICATION NO. REV