

---

DATASHEET

# ABB Ability™ Smart Sensor

## Condition monitoring solution for low voltage motors



For questions and support, please contact  
ABB Motors and Generators Service.

Product information:

[www.abb.com/smartsensor](http://www.abb.com/smartsensor)

Support desk e-mail:

[support.smartsensor@abb.com](mailto:support.smartsensor@abb.com)

### Note

We reserve all rights in this document  
and in the information contained therein.  
Reproduction, use or disclosure to third parties  
without express authority is strictly forbidden.

SPECIFICATIONS		Remarks
<b>Temperature measurement</b>		
Measurement range	-40°C ... +85°C	
Resolution	0.05°C	
Accuracy	+/- 0.5°C	baseplate temperature
<b>Vibration measurement (overall velocity values)</b>		
Amplitude range	0.04 - 700 mm/s (25 Hz)	
Frequency range	10 Hz - 1 kHz	
Detection type	RMS	
<b>Wireless communication</b>		
Network standard	Bluetooth® 4.0	
Radio standard	IEEE 802.15.1	
Frequency	2.4 GHz, license free ISM band	
Range (nominal)	>10 m @ line-of-sight	
<b>Power</b>		
Battery type	3.0 V Lithium Permanganate (LI-MnO4) button cell	CR2477N (The battery is not user replaceable)
Estimated battery lifetime	Batteries have a design life of 5 years. Expect 3-5 years depending on usage, settings and temperatures	
Motor body temperature (°C) at ambient temperature of 40 °C	0° to 40°	40° to 70°
Battery life in years	5	3
Default configuration: Sensor measures once per hour and stores data to memory. Stored data must be collected at least monthly with a Bluetooth® mobile device or gateway		
<b>Environmental</b>		
Temperature	Operation: -40°C to +85°C Storage : 40 °C maximum	
IP class	IP66 (dust-tight and resistant to powerful water jetting)	
Vibration (of mounted surface)	< 15g at 100 Hz	
<b>Certifications/Standards</b>		
CE, FCC, IEC		
Safe or ordinary areas		
<b>Physical</b>		
Weight	0.26 kg	
Case material	Stainless steel/Thermoplastic	
Mounting	On cooling ribs of motor frame, ensure good contact	

