

# **BALDOR® • RELIANCE**

## **Product Information Packet**

# **AFL3524A**

**3HP,3450RPM,1PH,60HZ,145TZ,3535LC,TEAO**

Copyright © All product information within this document is subject to Baldor Electric Company copyright © protection, unless otherwise noted.

Part Detail							
Revision:	V	Status:	PRD/A	Change #:		Proprietary:	No
Type:	AC	Prod. Type:	3535LC	Elec. Spec:	35WGY039	CD Diagram:	
Enclosure:	TEAO	Mfg Plant:		Mech. Spec:	35T906	Layout:	
Frame:	145TZ	Mounting:	F1	Poles:	02	Created Date:	06-22-2007
Base:	RG	Rotation:	RS	Insulation:	B	Eff. Date:	08-10-2012
Leads:	2#14 A PH,3#18 B&J	Literature:		Elec. Diagram:		Replaced By:	

Nameplate NP1280L										
CAT.NO.	AFL3524A									
SPEC.	35T906Y039									
HP	3 AIR OVER									
VOLTS	230									
AMP	15									
RPM	3450									
FRAME	145TZ	HZ				60	PH	1		
SER.F.	1.00	CODE				H	DES	-	CL	B
NEMA-NOM-EFF					PF					
RATING	40C AMB-CONT									
CC					USABLE AT 208V					
DE	6205	ODE				6203				
ENCL	TEAO	SN								

Parts List		
Part Number	Description	Quantity
SA111028	SA 35T906Y039	1.000 EA
RA102407	RA 35T906Y039	1.000 EA
OC3012F12SP	CYL OIL CAP 12MFD/370V	1.000 EA
EC1216C06SP	ELEC CAP, 216-259 MFD, 250V, 2.06D X 4.	1.000 EA
RM1001A01	GROMMET (MIDSTATES#541000)	1.000 EA
53XT0832G07	8-32X7/16 PN STD SR TY23G X	1.000 EA
35EP3102A02SP	FR ENDPLATE, MACH	1.000 EA
HW4500A01	1641B(ALEMITE)400 UNIV, GREASE FITT	1.000 EA
51XW0832A07	8-32 X .44, TAPTITE II, HEX WSHR SLTD SE	2.000 EA
35CB3801SP	CAPACITOR COVER, CAST	1.000 EA
34GS3002	GASKET, CAPACITOR BOX	1.000 EA
HA7010	CAPACITOR RETENTION CLAMP	1.000 EA
NS2501A02	INSULATOR, CAPACITOR BOX	1.000 EA
51XB1016A08	10-16X 1/2HXWSSLD SERTYB	2.000 EA
HW5100A03SP	WAVY WASHER (W1543-017)	1.000 EA
35EP3101A01SP	STD PU EP-ENCLOSED-205 BRG-W/GREASER	1.000 EA
HW4500A01	1641B(ALEMITE)400 UNIV, GREASE FITT	1.000 EA
XY1032A02	10-32 HEX NUT DIRECTIONAL SERRATION	4.000 EA
WD4100A01	DP-875 HEYCO PLUG OR 62MP0875 MICRO PLAS	1.000 EA
35CB4500SP	TERMINAL BOX LID STAMPED	1.000 EA
35GS1002	GASKET,1/16 THICK LEXIDE	1.000 EA
51XW0832A07	8-32 X .44, TAPTITE II, HEX WSHR SLTD SE	2.000 EA
HW2501D13SP	KEY, 3/16 SQ X 1.375	1.000 EA
HA7000A01	KEY RETAINER 7/8" DIA SHAFT	1.000 EA


Parts List (continued)		
Part Number	Description	Quantity
85XU0407S04	4X1/4 U DRIVE PIN STAINLESS	2.000 EA
WD1000A15	3-520132-2 AMP FLAG (4M/RL NON-CANC/NON-	2.000 EA
MJ1000A75	GREASE, POLYREX EM EXXON	0.050 LB
MG1025Z20	ACTIVATOR WILKOFAS 060.32	0.010 GA
MG1025C02	PAINT, 787.105 LITE TAN EPOXY (USE W/MG1	0.017 GA
HA3100A22	THRUBOLT 10-32 X 10.125	4.000 EA
34GS5003	FOAM SLEEVE, ID = 2 1/16" X 3 3/8"	2.000 EA
SP5066A03	MODEL 35 TERMINAL PANEL SWITCH WITH LEAD	1.000 EA
LB1118	LABEL,WARNING (ROLL LABEL)	1.000 EA
LB1125C01	STD (STOCK) CARTON LABEL BALDOR WITH FLA	1.000 EA
LC0085	CONNECTION LABEL	1.000 EA
NP1280L	ALUM FARM DUTY UL CSA CC THERMAL	1.000 EA
35PA1066	PACKING GROUP COMBINED PRINT	1.000 EA


Accessories		
Part Number	Description	Multiplier
35-8762	C FACE KIT	A8
35EP1604A01SP	D-FLANGE KIT	A8

**Performance Data at 230V, 60Hz, 3.0HP (Typical performance - Not guaranteed values)**

General Characteristics							
Full Load Torque:	4.5 LB-FT			Start Configuration:	DOL		
No-Load Current:	9.0 Amps			Break-Down Torque:	14.7 LB-FT		
Line-line Res. @ 25°C.:	0.577 Ohms A Ph / 2.53 Ohms B Ph			Pull-Up Torque:	11.0 LB-FT		
Temp. Rise @ Rated Load:				Locked-Rotor Torque:	13.6 LB-FT		
Temp. Rise @ S.F. Load:				Starting Current:	92.0 Amps		
Load Characteristics							
% of Rated Load	25	50	75	100	125	150	S.F.
Power Factor:	47.0	64.0	75.0	83.0	86.0	87.0	0.0
Efficiency:	55.0	70.0	75.0	78.0	78.0	77.0	0.0
Speed:	3560.0	3555.0	3520.0	3500.0	3490.0	3465.0	0.0
Line Amperes:	9.5	11.0	13.0	15.0	18.0	21.5	0.0

Performance Graph at 230V, 60Hz, 3.0HP Typical performance - Not guaranteed values







CD0225A02

