

BALDOR® • RELIANCE

Product Information Packet

CJM3107

.5HP,3450RPM,3PH,60HZ,56J,3413M,OPEN,F1

Copyright © All product information within this document is subject to Baldor Electric Company copyright © protection, unless otherwise noted.

Part Detail									
Revision:	S	Status:	PRD/A	Change #:		Proprietary:	No		
Type:	AC	Prod. Type:	3413M	Elec. Spec:	34WG2718	CD Diagram:			
Enclosure:	OPEN	Mfg Plant:		Mech. Spec:	34F029	Layout:			
Frame:	56J	Mounting:	F1	Poles:	02	Created Date:			
Base:	RG	Rotation:	R	Insulation:	B	Eff. Date:	06-09-2011		
Leads:	9#18	Literature:		Elec. Diagram:		Replaced By:			
Nameplate NP1256L									
CAT.NO.	CJM3107								
SPEC.	34F29-2718								
HP	.5								
VOLTS	230/460								
AMP	2.4/1.2								
RPM	3450								
FRAME	56J	HZ			60	PH	3		
SER.F.	1.60	CODE			N	DES	B	CLASS	B
NEMA-NOM-EFF	70	PF			65				
RATING	40C AMB-CONT								
CC				USABLE AT 208V		3.1			
DE	6203	ODE			6203				
ENCL	OPEN	SN							
	SFA 2.8/1.4								

Parts List		
Part Number	Description	Quantity
SA005837	SA 34F29-2718	1.000 EA
RA002583	RA 34F29-2718	1.000 EA
NS2512A01	INSULATOR, CONDUIT BOX X	1.000 EA
34CB3002A	CB CAST W/.88 DIA HOLE	1.000 EA
51XB1016A07	10-16 X 7/16 HXWSSLD SERTYB	2.000 EA
11XW1032G06	10-32 X .38, TAPTITE II, HEX WSHR SLTD U	1.000 EA
34EP3212A03	FR EP 34L FOR DRIP CVR	1.000 EA
HW5100A03SP	WAVY WASHER (W1543-017)	1.000 EA
34EP3401A01SP	PU ENDPLATE, MACH	1.000 EA
34AD2000	BAFFLE PLATE, STAMPED	1.000 EA
51XT0632A06	6-32X3/8 TY23 HXWS SLDSR	4.000 EA
51XN1032A20	10-32 X 1 1/4 HX WS SL SR	2.000 EA
34FH4001A04	DRIP COVER, STAMPED	1.000 EA
51XW1032A06	10-32 X .38, TAPTITE II, HEX WSHR SLTD S	3.000 EA
WD4101A09	STIMPSON D3560, .875 DIA. HOLE PLUG	1.000 EA
34CB4517	CB LID 4 MTG HOLES .22 DIA STAMPED, FOR	1.000 EA
51XW0832A07	8-32 X .44, TAPTITE II, HEX WSHR SLTD SE	4.000 EA
RM1010A01	35-968-1 VINYL CLS	1.000 EA
MG1000G27	PAINT- S9282E CHARCOAL GREY	0.014 GA
10XF0440S02	04-40 X 1/8 TYPE F HEX HD STAINLESS STIC	2.000 EA
HA3100A12	THRUBOLT 10-32 X 7.375	4.000 EA
LB1125C01	STD (STOCK) CARTON LABEL BALDOR WITH FLA	1.000 EA
LC0005E01	CONN.DIA./WARNING LABEL (LC0005/LB1119)	1.000 EA
NP1256L	ALUM UL CSA CC	1.000 EA

Parts List (continued)		
Part Number	Description	Quantity
34PA1002	PACKING GROUP, BALDOR	1.000 EA
PK3083T	STYROFOAM PACKING CRADLE W/TAPE	1.000 EA

Performance Data at 460V, 60Hz, 0.5HP (Typical performance - Not guaranteed values)**General Characteristics**

Full Load Torque:	0.75 LB-FT	Start Configuration:	DOL
No-Load Current:	0.88 Amps	Break-Down Torque:	5.3 LB-FT
Line-line Res. @ 25°C.:	6.0 Ohms A Ph / 0.0 Ohms B Ph	Pull-Up Torque:	3.38 LB-FT
Temp. Rise @ Rated Load:	31 C	Locked-Rotor Torque:	3.8 LB-FT
Temp. Rise @ S.F. Load:	44 C	Starting Current:	8.75 Amps

Load Characteristics

% of Rated Load	25	50	75	100	125	150	S.F.
Power Factor:	33.0	44.0	55.0	65.0	69.0	75.0	76.0
Efficiency:	46.9	60.4	67.2	71.3	72.1	72.7	73.2
Speed:	3574.0	3553.0	3533.0	3507.0	3486.0	3456.0	3447.0
Line Amperes:	0.88	0.92	0.96	1.05	1.15	1.3	1.36

Performance Graph at 460V, 60Hz, 0.5HP Typical performance - Not guaranteed values





