

BALDOR® • RELIANCE

Product Information Packet

EM2547T-12

60HP,1775RPM,3PH,60HZ,364T,4278M,OPSB,F1

Copyright © All product information within this document is subject to Baldor Electric Company copyright © protection, unless otherwise noted.

Part Detail									
Revision:	E	Status:	PRD/A	Change #:		Proprietary:	No		
Type:	AC	Prod. Type:	4278M	Elec. Spec:	42WGW658	CD Diagram:			
Enclosure:	OPSB	Mfg Plant:		Mech. Spec:	42E211	Layout:			
Frame:	364T	Mounting:	F1	Poles:	04	Created Date:	07-29-2009		
Base:	RG	Rotation:	R	Insulation:	F	Eff. Date:	09-08-2011		
Leads:	12#8	Literature:		Elec. Diagram:		Replaced By:			
Nameplate NP2138L									
CAT.NO.	EM2547T-12	P/N		ENCLOSURE			OPSB		
SPEC.	42E211W658	CC	010A	FRAME			364T	S/N	
HP	60	CLASS	F	HZ			60		
RPM	1775	PH	3	DES			B		
VOLT	230/460	KVA-CODE	G	ODE BRG			6311	DE BRG	6313
AMP	136/68	USABLE AT 208V	144						
RATING	40C AMB-CONT	GREASE	POLYREX EM						
NEMA-NOM-EFF	95	PF	87	SER.F.			1.15		
HTR-VOLTS		HTR-AMPS		MAX. SPACE HEATER TEMP.					

Parts List		
Part Number	Description	Quantity
SA184472	SA 42E211W658	1.000 EA
RA172307	RA 42E211W658	1.000 EA
S/P107-000-004	SUPER-E(284 FR. & UP)-CL PLANT,POLYREX E	1.000 EA
HA6360	LIFTING LUG FOR 42 FRAME MOTORS.	2.000 EA
HA6017A01	CAST ADAPTOR	1.000 EA
19XW3118A12	.31-18 X .75 HEX WASHER HEAD TAPTITE II	2.000 EA
HW1001A31	LOCKWASHER 5/16, ZINC PLT.591 OD, .319 I	2.000 EA
10CB3002	CONDUIT BOX CAST W/3.625 LEAD HOLE	1.000 EA
19XW3118A12	.31-18 X .75 HEX WASHER HEAD TAPTITE II	4.000 EA
HW1001A31	LOCKWASHER 5/16, ZINC PLT.591 OD, .319 I	4.000 EA
WD1000B16	KPA-4C BURNDY TERMINAL	1.000 EA
51XF2520A08	SCREW, HEX SER SLT HD, ZN 1/4-20 X .50 L	1.000 EA
42EP3200A01	FR ENDPLATE, MACH 324-6T	1.000 EA
HW5100A13	W4627-047 WVY WSHR	1.000 EA
42EP1202A01	STD PU ENDPLATE MODEL 42 313 BRG.	1.000 EA
10XN3816K44	3/8-16 X 2.75 HEX HD CAP SCREW, GRADE 5	4.000 EA
HW1001A38	LOCKWASHER 3/8, ZINC PLT .688 OD, .382 I	4.000 EA
XY5013A12	NUT,1/2-13,HEX,STEEL,ZINCPLATED	8.000 EA
10CB3500SP	CONDUIT BOX LID, CAST	1.000 EA
51XW2520A12	.25-20 X .75, TAPTITE II, HEX WSHR SLTD	4.000 EA
HW2501J36	KEY, 5/8 SQ X 4.250	1.000 EA
LB1115	LABEL,LIFTING DEVICE	1.000 EA
LB5040	INSTRUCTION TAG, AC & DC	1.000 EA
HA4051A00	PLASTIC CAP FOR GREASE FITTING	1.000 EA

Parts List (continued)		
Part Number	Description	Quantity
HW4500A03	GREASE FITTING, .125 NPT 1610(ALEMITE) 8	1.000 EA
HW4500A20	1/8NPT SL PIPE PLUG	1.000 EA
MJ1000A75	GREASE, POLYREX EM EXXON	0.030 LB
HA4051A00	PLASTIC CAP FOR GREASE FITTING	1.000 EA
HW4500A03	GREASE FITTING, .125 NPT 1610(ALEMITE) 8	1.000 EA
HW4500A20	1/8NPT SL PIPE PLUG	1.000 EA
MG1000Y03	WILKO 689.710 GOLD PAINT SUPER E	0.080 GA
85XU0407A04	#4-7 X 1/4 DRIVE PIN	2.000 EA
42AD2001A01	BAFFLE PLATE 42 OPEN, SLOTTED BAND MTRS	1.000 EA
42AD2001A01	BAFFLE PLATE 42 OPEN, SLOTTED BAND MTRS	1.000 EA
HA3151A12	THRUBOLT STUD 1/2-13 X 23.00	4.000 EA
LB1119	WARNING LABEL	1.000 EA
LB1125C02	SUPER-E (STOCK CTN LABEL SUPER-E WITH FL	4.000 EA
LB1357	ENERGY GUIDE LABEL (BOX LABEL)	1.000 SH
LC0104A01	CONNECTION DIAGRAM	1.000 EA
NP2138L	ALUM SUPER-E UL CSA-EEV PREM CC (300	1.000 EA
42PA1000	PACKAGING GROUP 42 FRAME PK1024A06	1.000 EA

Performance Data at 460V, 60Hz, 60.0HP (Typical performance - Not guaranteed values)**General Characteristics**

Full Load Torque:	177.0 LB-FT	Start Configuration:	DOL
No-Load Current:	22.2 Amps	Break-Down Torque:	624.0 LB-FT
Line-line Res. @ 25°C.:	0.0815 Ohms A Ph / 0.0 Ohms B Ph	Pull-Up Torque:	245.0 LB-FT
Temp. Rise @ Rated Load:	30 C	Locked-Rotor Torque:	314.0 LB-FT
Temp. Rise @ S.F. Load:	36 C	Starting Current:	470.0 Amps

Load Characteristics

% of Rated Load	25	50	75	100	125	150	S.F.
Power Factor:	56.0	77.0	85.0	87.0	88.0	88.0	88.0
Efficiency:	92.7	94.9	95.5	95.0	94.5	93.9	94.7
Speed:	1793.0	1787.0	1781.0	1775.0	1769.0	1762.0	1771.0
Line Amperes:	27.3	38.7	52.1	67.6	83.6	101.0	77.2

Performance Graph at 460V, 60Hz, 60.0HP Typical performance - Not guaranteed values





