

BALDOR® • RELIANCE

Product Information Packet

WALKER INDUSTRIAL PRODUCTS, INC.

EM3611T-9

3HP,1750RPM,3PH,60HZ,182T,3636M,TEFC,F1

Part Detail							
Revision:	A	Status:	PRD/A	Change #:		Proprietary:	No
Type:	AC	Prod. Type:	3636M	Elec. Spec:	36WGR666	CD Diagram:	CD0005
Enclosure:	TEFC	Mfg Plant:		Mech. Spec:	36Q306	Layout:	36LYQ306
Frame:	182T	Mounting:	F1	Poles:	04	Created Date:	10-28-2015
Base:	RG	Rotation:	R	Insulation:	F	Eff. Date:	03-15-2016
Leads:	9#16					Replaced By:	
Literature:		Elec. Diagram:					

Nameplate NP1267L

CAT.NO.	EM3611T-9											
SPEC.	36Q306R666G1											
HP	3											
VOLTS	230/460											
AMP	8.6/4.3											
RPM	1750											
FRAME	182T				HZ		60			PH		3
SER.F.	1.15		CODE		J	DES		C	CL		F	
NEMA-NOM-EFF	89.5			PF		74						
RATING	40C AMB-CONT											
CC	010A			USABLE AT 208V								9.4
DE	6206				ODE		6205					
ENCL	TEFC		SN									

Parts List		
Part Number	Description	Quantity
SA310035	SA 36Q306R666G1	1.000 EA
RA297409	RA 36Q306R666G1	1.000 EA
36FN3000C01SP	EXFN, PLASTIC, 5.25 OD, .912 ID	1.000 EA
36CB3005A03	36 CB .75 NPT @ 6	1.000 EA
35GS1022A02	GASKET BOX .06 THK NEOP BLK HDN 30-40 DU	1.000 EA
51XB1016A08	10-16X 1/2HXWSSLD SERTYB	2.000 EA
11XW1032G06	10-32 X .38, TAPTITE II, HEX WSHR SLTD U	1.000 EA
36EP3104A39	FREP MACH W/GRSR,REL, .125 NPT RAISED FH	1.000 EA
HW4500A17	317400 ALEMITE GREASE RELIEF	1.000 EA
HW4500A01	1641B(ALEMITE)400 UNIV, GREASE FITT	1.000 EA
HA4054	SHORT T-DRAIN FITTING, .125" N.P.T.	1.000 EA
HW5100A05	WVY WSHR F/205 & 304 BRGS	1.000 EA
36EP3100B80	PU ENDPLATE, MACH, GRSR, RLF, .125 DRAIN	1.000 EA
HW4500A17	317400 ALEMITE GREASE RELIEF	1.000 EA
HW4500A01	1641B(ALEMITE)400 UNIV, GREASE FITT	1.000 EA
HA4054	SHORT T-DRAIN FITTING, .125" N.P.T.	1.000 EA
XY2520A12	1/4-20 HEX NUT, DIRECTIONAL SERRATIONS	4.000 EA
51XB1214A16	12-14X1.00 HXWSSLD SERTYB	1.000 EA
36FH4009A102	IEC FH GREASER PRIMED	1.000 EA
51XW1032A06	10-32 X .38, TAPTITE II, HEX WSHR SLTD S	3.000 EA
36CB4516	36 LIPPED CB LID - GALVANNEAL	1.000 EA
37GS1003	1/16 NEOPRENE GASKET-BLACK, CONDUIT BOX	1.000 EA
51XW0832A07	8-32 X .44, TAPTITE II, HEX WSHR SLTD SE	4.000 EA
HW4600B32SP	V-RING SLINGER 1.000 X 1.540 X .24 VITON	1.000 EA

Parts List (continued)		
Part Number	Description	Quantity
HW4600B36SP	V-RING SLINGER 1.188 X 1.690 X .24 VITON	1.000 EA
HW2501E16	3KEY, 1/4 SQ X 1.750	1.000 EA
HA7000A02	KEY RETAINER RING, 1 1/8 DIA, 1 3/8 DIA	1.000 EA
MJ5001A27	32220KN GRAY SEALER *MIN BUY 4 QTS=1GAL	0.001 QT
85XU0407S04	4X1/4 U DRIVE PIN STAINLESS	2.000 EA
HW3200A01	3/8-16X3/4 I-BLT WELDED F/S	1.000 EA
MJ1000A02	GREASE, POLYREX EM EXXON (USe 4824-15A)	0.050 LB
MG1025N19	WILKOFAS, 778.50, RELIANCE BLUE-GREEN	0.022 GA
HA3101A28	THRUBOLT 1/4-20 X 12.500 OHIO ROD	4.000 EA
LC0005E01	CONN.DIA./WARNING LABEL (LC0005/LB1119N)	1.000 EA
NP1267L	SS SUPER-E LASER BLANK	1.000 EA
G0PA1000	PKG GRP, PRINT PK1026A06	1.000 EA
MN416A01	TAG-INSTAL-MAINT no wire (1000/bx) 11/14	1.000 EA

AC Induction Motor Performance Data

Record # 58092 - Typical performance - not guaranteed values

Winding: 36WGR666-R002	Type: 3636M	Enclosure: TEFC
-------------------------------	--------------------	------------------------

Nameplate Data				460 V, 60 Hz: High Voltage Connection	
Rated Output (HP)	3			Full Load Torque	9.1 LB-FT
Volts	230/460			Start Configuration	direct on line
Full Load Amps	8.6/4.3			Breakdown Torque	28.2 LB-FT
R.P.M.	1750			Pull-up Torque	24.9 LB-FT
Hz	60	Phase	3	Locked-rotor Torque	31.6 LB-FT
NEMA Design Code	C	KVA Code	J	Starting Current	27.5 A
Service Factor (S.F.)	1.15			No-load Current	2.28 A
NEMA Nom. Eff.	89.5	Power Factor	74	Line-line Res. @ 25°C	3.43 Ω
Rating - Duty	40C AMB-CONT			Temp. Rise @ Rated Load	43°C
S.F. Amps				Temp. Rise @ S.F. Load	52°C
				Locked-rotor Power Factor	45.5
				Rotor inertia	0.335 LB-FT ²

Load Characteristics 460 V, 60 Hz, 3 HP

% of Rated Load	25	50	75	100	125	150	S.F.
Power Factor	35	56	67	74	78	80	76
Efficiency	82.9	88.8	89.9	89.5	88.4	87.6	88.8
Speed	1787	1777	1766	1753	1739	1725	1745
Line amperes	2.46	2.92	3.52	4.27	5.12	6.02	4.78

Performance Graph at 460V, 60Hz, 3.0HP Typical performance - Not guaranteed values





