

BALDOR® • RELIANCE

Product Information Packet

IR3510M

1HP,1725RPM,1PH,60HZ,56,3528L,TEFC,F1,N

Copyright © All product information within this document is subject to Baldor Electric Company copyright © protection, unless otherwise noted.

Part Detail									
Revision:	Y	Status:	PRD/A	Change #:		Proprietary:	No		
Type:	AC	Prod. Type:	3528L	Elec. Spec:	35WGY986	CD Diagram:			
Enclosure:	TEFC	Mfg Plant:		Mech. Spec:	35K634	Layout:			
Frame:	56	Mounting:	F1	Poles:	04	Created Date:			
Base:	RG	Rotation:	R	Insulation:	F	Eff. Date:	07-10-2012		
Leads:	8#18	Literature:		Elec. Diagram:		Replaced By:			
Nameplate NP1280L									
CAT.NO.	IR3510M								
SPEC.	35K634Y986								
HP	1								
VOLTS	230								
AMP	6.2								
RPM	1725								
FRAME	56	HZ			60	PH	1		
SER.F.	1.15	CODE			K	DES	L	CL	F
NEMA-NOM-EFF	65	PF			70				
RATING	40C AMB-CONT								
CC				USABLE AT 208V					
DE	6205	ODE			6203				
ENCL	TEFC	SN							

Parts List		
Part Number	Description	Quantity
SA026506	SA 35K634Y986	1.000 EA
RA022556	RA 35K634Y986	1.000 EA
TPMRJ26AB	THERMAL 1PH .75 MAN 120C X	1.000 EA
EC1072D06	72MFD 330V 2X4.3ELEC CAP	2.000 EA
NS2512A01	INSULATOR, CONDUIT BOX X	1.000 EA
35CB3007A59	35 CB .88 DIA @ 6:00, .75 MTO W/BOOT @ 3	1.000 EA
36GS1000SP	GASKET-CONDUIT BOX, .06 THICK #SV-330 LE	1.000 EA
51XB1016A07	10-16 X 7/16 HXWSSLD SERTYB	2.000 EA
11XW1032G06	10-32 X .38, TAPTITE II, HEX WSHR SLTD U	1.000 EA
51XT0632A06	6-32X3/8 TY23 HXWS SLDSR	2.000 EA
HA6001A01	THERMAL RETAINER (PLATED)	1.000 EA
51XB1214A10	12-14 X 5/8HX WS SL SR TYBX	2.000 EA
RM1014A01SP	BUTYL RUB.THRM COV. (MENA)	1.000 EA
35EP3100M41	FREP TEFC 203 BRG W/O GRSR (RAISED FH MT	1.000 EA
NS2501A02	INSULATOR, CAPACITOR BOX	1.000 EA
35CB3801SP	CAPACITOR COVER, CAST	1.000 EA
34GS3002	GASKET, CAPACITOR BOX	1.000 EA
HA7010	CAPACITOR RETENTION CLAMP	1.000 EA
51XB1016A08	10-16X 1/2HXWSSLD SERTYB	2.000 EA
HW5100A03SP	WAVY WASHER (W1543-017)	1.000 EA
35EP3101A02SP	STD PU ENDPLATE-ENCL-205 BRG LESS GREASE	1.000 EA
XY1032A02	10-32 HEX NUT DIRECTIONAL SERRATION	4.000 EA
35FN3002A05SP	EXFN, PLASTIC, 6.376 OD, .638 ID	1.000 EA
51XB1214A16	12-14X1.00 HXWSSLD SERTYB	2.000 EA

Parts List (continued)		
Part Number	Description	Quantity
51XW1032A06	10-32 X .38, TAPTITE II, HEX WSHR SLTD S	3.000 EA
35FH4005A32SP	IEC FH NO GRSR W/3 HOLES - W/AUTOPHERETI	1.000 EA
35CB4521GX	CONDUIT BOX LID KIT	1.000 EA
51XW0832A07	8-32 X .44, TAPTITE II, HEX WSHR SLTD SE	6.000 EA
HW2501D13SP	KEY, 3/16 SQ X 1.375	1.000 EA
HA7000A04	KEY RETAINER 0.625 DIA SHAFTS	1.000 EA
85XU0407S04	4X1/4 U DRIVE PIN STAINLESS	2.000 EA
WD1000A15	3-520132-2 AMP FLAG (4M/RL NON-CANC/NON-	4.000 EA
MJ1000A75	GREASE, POLYREX EM EXXON	0.050 LB
MG1025Z20	ACTIVATOR WILKOFAS 060.32	0.010 GA
HA3100A18	THRUBOLT 10-32 X 9.250	4.000 EA
SP5179A01	STATIONARY SWITCH ASSY. INSTANT REV.	1.000 EA
MG1025C02	PAINT, 787.105 LITE TAN EPOXY (USE W/MG1	0.017 GA
LB1087	LABEL,MANUAL RESET (ROLL LABEL)	1.000 EA
LB1119	WARNING LABEL	1.000 EA
LB1125C01	STD (STOCK) CARTON LABEL BALDOR WITH FLA	1.000 EA
LC0045	CONNECTION LABEL X	1.000 EA
NP1280L	ALUM FARM DUTY UL CSA CC THERMAL	1.000 EA
35PA1066	PACKING GROUP COMBINED PRINT	1.000 EA

Accessories		
Part Number	Description	Multiplier
35-8762	C FACE KIT	A8
35EP1506A01SP	D-FLANGE KIT	A8

Performance Data at 230V, 60Hz, 1.0HP (Typical performance - Not guaranteed values)**General Characteristics**

Full Load Torque:	3.0 LB-FT	Start Configuration:	DOL
No-Load Current:	5.4 Amps	Break-Down Torque:	8.1 LB-FT
Line-line Res. @ 25°C.:	2.49 Ohms A Ph / 7.3 Ohms B Ph	Pull-Up Torque:	6.7 LB-FT
Temp. Rise @ Rated Load:	79 C	Locked-Rotor Torque:	8.7 LB-FT
Temp. Rise @ S.F. Load:	89 C	Starting Current:	40.4 Amps

Load Characteristics

% of Rated Load	25	50	75	100	125	150	S.F.
Power Factor:	37.0	48.0	59.0	68.0	74.0	79.0	72.0
Efficiency:	40.0	55.0	62.0	65.0	66.0	66.0	65.6
Speed:	1785.0	1774.0	1763.0	1750.0	1736.0	1719.0	1742.0
Line Amperes:	5.5	5.8	6.3	7.1	8.1	9.1	7.7

Performance Graph at 230V, 60Hz, 1.0HP Typical performance - Not guaranteed values





