

BALDOR® • RELIANCE

Product Information Packet

M3531

.25HP,1140RPM,3PH,60HZ,56,3411M,TEFC,F1

Copyright © All product information within this document is subject to Baldor Electric Company copyright © protection, unless otherwise noted.

Part Detail									
Revision:	L	Status:	PRD/A	Change #:		Proprietary:	No		
Type:	AC	Prod. Type:	3411M	Elec. Spec:	34WG5882	CD Diagram:			
Enclosure:	TEFC	Mfg Plant:		Mech. Spec:	34A061	Layout:			
Frame:	56	Mounting:	F1	Poles:	06	Created Date:			
Base:	RG	Rotation:	R	Insulation:	B	Eff. Date:	07-16-2007		
Leads:	9#18	Literature:		Elec. Diagram:		Replaced By:			
Nameplate NP1256L									
CAT.NO.	M3531								
SPEC.	34A61-5882								
HP	.25								
VOLTS	230/460								
AMP	1.4/.7								
RPM	1140								
FRAME	56	HZ		60	PH	3			
SER.F.	1.35	CODE		K	DES	B	CLASS	B	
NEMA-NOM-EFF	68	PF		51					
RATING	40C AMB-CONT								
CC				USABLE AT 208V	1.6				
DE	6203	ODE			6203				
ENCL	TEFC	SN							
	SFA 1.5/.75								

Parts List		
Part Number	Description	Quantity
SA009788	SA 34A61-5882	1.000 EA
RA006233	RA 34A61-5882	1.000 EA
NS2512A01	INSULATOR, CONDUIT BOX X	1.000 EA
34CB3002A	CB CAST W/.88 DIA HOLE	1.000 EA
34GS1029A01	GASKET, CONDUIT BOX	1.000 EA
51XB1016A07	10-16 X 7/16 HXWSSLD SERTYB	2.000 EA
11XW1032G06	10-32 X .38, TAPTITE II, HEX WSHR SLTD U	1.000 EA
34EP3102A01SP	FR ENDPLATE, MACH	1.000 EA
HW5100A03SP	WAVY WASHER (W1543-017)	1.000 EA
34EP3102A02SP	FR/PU ENDPLATE, MACH	1.000 EA
XY1032A02	10-32 HEX NUT DIRECTIONAL SERRATION	4.000 EA
34FN3002A01SP	EXTERNAL FAN, PLASTIC, .637/.639 HUB W/	1.000 EA
34FH4002A01	IEC FH NO GREASER	1.000 EA
51XW1032A06	10-32 X .38, TAPTITE II, HEX WSHR SLTD S	3.000 EA
34CB4517	CB LID 4 MTG HOLES .22 DIA STAMPED, FOR	1.000 EA
34GS1031A01	GASKET, FLAT CONDUIT BOX LID (LEXIDE)	1.000 EA
51XW0832A07	8-32 X .44, TAPTITE II, HEX WSHR SLTD SE	4.000 EA
HW2501D13SP	KEY, 3/16 SQ X 1.375	1.000 EA
HA7000A04	KEY RETAINER 0.625 DIA SHAFTS	1.000 EA
MG1000G27	PAINT- S9282E CHARCOAL GREY	0.014 GA
10XF0440S02	04-40 X 1/8 TYPE F HEX HD STAINLESS STIC	2.000 EA
HA3100A12	THRUBOLT 10-32 X 7.375	4.000 EA
LB1125C01	STD (STOCK) CARTON LABEL BALDOR WITH FLA	1.000 EA
LC0005E01	CONN.DIA./WARNING LABEL (LC0005/LB1119)	1.000 EA

Parts List (continued)		
Part Number	Description	Quantity
NP1256L	ALUM UL CSA CC	1.000 EA
34PA1002	PACKING GROUP, BALDOR	1.000 EA

Accessories		
Part Number	Description	Multiplier
34-171	C FACE KIT	A8

Performance Data at 460V, 60Hz, 0.25HP (Typical performance - Not guaranteed values)**General Characteristics**

Full Load Torque:	1.15 LB-FT	Start Configuration:	DOL
No-Load Current:	0.57 Amps	Break-Down Torque:	3.8 LB-FT
Line-line Res. @ 25°C.:	80.7 Ohms A Ph / 0.0 Ohms B Ph	Pull-Up Torque:	2.9 LB-FT
Temp. Rise @ Rated Load:	41 C	Locked-Rotor Torque:	3.0 LB-FT
Temp. Rise @ S.F. Load:	53 C	Starting Current:	2.5 Amps

Load Characteristics

% of Rated Load	25	50	75	100	125	150	S.F.
Power Factor:	24.0	34.0	43.0	51.0	58.0	61.0	61.0
Efficiency:	44.0	57.0	64.0	67.4	68.0	67.7	68.2
Speed:	1184.0	1171.0	1157.0	1139.0	1122.0	1109.0	1115.0
Line Amperes:	0.57	0.6	0.63	0.68	0.73	0.78	0.75

Performance Graph at 460V, 60Hz, 0.25HP Typical performance - Not guaranteed values





