

BALDOR® • RELIANCE

Product Information Packet

VNM3541

.75HP,3450RPM,3PH,60HZ,56C,3520M,TENV,F1

Copyright © All product information within this document is subject to Baldor Electric Company copyright © protection, unless otherwise noted.

Part Detail									
Revision:	K	Status:	PRD/A	Change #:		Proprietary:	No		
Type:	AC	Prod. Type:	3520M	Elec. Spec:	35WGR090	CD Diagram:			
Enclosure:	TENV	Mfg Plant:		Mech. Spec:	35E010	Layout:			
Frame:	56C	Mounting:	F1	Poles:	02	Created Date:	01-08-2008		
Base:	N	Rotation:	R	Insulation:	H	Eff. Date:	11-01-2011		
Leads:	9#18	Literature:		Elec. Diagram:		Replaced By:			
Nameplate NP1256L									
CAT.NO.		VNM3541							
SPEC.		35E010R090G2							
HP		.75							
VOLTS		208-230/460							
AMP		2.2-2/1							
RPM		3480							
FRAME		56C		HZ		60	PH	3	
SER.F.		1.25		CODE		N	DES	B	CLASS H
NEMA-NOM-EFF		84		PF		82			
RATING		40C AMB-CONT							
CC				USABLE AT 208V		2.2			
DE		6205		ODE		6203			
ENCL		TENV		SN					
		SFA 2.6-2.4/1.2							

Parts List		
Part Number	Description	Quantity
SA166778	SA 35E010R090G2	1.000 EA
RA155140	RA 35E010R090G2	1.000 EA
S/P111-000-002	CORONA TEST, SUPER E MOTORS - FT. SMITH	1.000 EA
NS2512A01	INSULATOR, CONDUIT BOX X	1.000 EA
35CB3007	35 CB CASTING W/.88 DIA. LEAD HOLE	1.000 EA
36GS1000SP	GASKET-CONDUIT BOX, .06 THICK #SV-330 LE	1.000 EA
51XB1016A07	10-16 X 7/16 HXWSSLD SERTYB	2.000 EA
11XW1032G06	10-32 X .38, TAPTITE II, HEX WSHR SLTD U	1.000 EA
35EP3100M69	STD FR EP-TENV-35L OR M--203 BRG	1.000 EA
HW5100A03SP	WAVY WASHER (W1543-017)	1.000 EA
35EP3300A33	SPL FACE MTD EP -ENCL-205 BRG	1.000 EA
51XN1032A20	10-32 X 1 1/4 HX WS SL SR	2.000 EA
35CB4521GX	CONDUIT BOX LID KIT	1.000 EA
51XW0832A07	8-32 X .44, TAPTITE II, HEX WSHR SLTD SE	4.000 EA
HA7000A04	KEY RETAINER 0.625 DIA SHAFTS	1.000 EA
85XU0407S04	4X1/4 U DRIVE PIN STAINLESS	2.000 EA
MJ1000A75	GREASE, POLYREX EM EXXON	0.050 LB
HW2501D13SP	KEY, 3/16 SQ X 1.375	1.000 EA
MG1000G27	PAINT- S9282E CHARCOAL GREY	0.017 GA
HA3100A12	THRUBOLT 10-32 X 7.375	4.000 EA
LC0005E01	CONN.DIA./WARNING LABEL (LC0005/LB1119)	1.000 EA
LB1125C01	STD (STOCK) CARTON LABEL BALDOR WITH FLA	1.000 EA
NP1256L	ALUM UL CSA CC	1.000 EA
35PA1066	PACKING GROUP COMBINED PRINT	1.000 EA

Parts List (continued)		
Part Number	Description	Quantity
PK3082	STYROFOAM CRADLE	1.000 EA
LB5040	INSTRUCTION TAG, AC & DC	1.000 EA

Performance Data at 460V, 60Hz, 0.75HP (Typical performance - Not guaranteed values)**General Characteristics**

Full Load Torque:	1.12 LB-FT	Start Configuration:	DOL
No-Load Current:	0.545 Amps	Break-Down Torque:	6.1 LB-FT
Line-line Res. @ 25°C.:	15.4 Ohms A Ph / 0.0 Ohms B Ph	Pull-Up Torque:	4.3 LB-FT
Temp. Rise @ Rated Load:	52 C	Locked-Rotor Torque:	5.1 LB-FT
Temp. Rise @ S.F. Load:	63 C	Starting Current:	11.3 Amps

Load Characteristics

% of Rated Load	25	50	75	100	125	150	S.F.
Power Factor:	45.0	65.0	77.0	82.0	87.0	86.0	87.0
Efficiency:	65.0	77.1	81.7	83.6	84.5	83.9	84.5
Speed:	3573.0	3550.0	3528.0	3503.0	3478.0	3451.0	3478.0
Line Amperes:	0.599	0.71	0.848	1.02	1.18	1.41	1.18

Performance Graph at 460V, 60Hz, 0.75HP Typical performance - Not guaranteed values





